

Model: Model S-F1.5		Date: 20-Oct-04	No.: RH555010
Subject: New product release (Model S-F1.5)		Prepared by: T.Shintani	
From: 1st Tech. Support Sec. Service Support Dept.			
Classification:	<input type="checkbox"/> Troubleshooting <input type="checkbox"/> Mechanical <input type="checkbox"/> Paper path <input type="checkbox"/> Other (      )	<input type="checkbox"/> Part information <input type="checkbox"/> Electrical <input type="checkbox"/> Transmit/receive	<input type="checkbox"/> Action required <input checked="" type="checkbox"/> Service manual revision <input type="checkbox"/> Retrofit information

In accordance with the release of the new model for the S-F1.5, this bulletin shows the differences between the model S-F1 and S-F1.5.

## Service Manual Information

- The following are the updated specifications for S-F1.5 from S-F1.

## SPECIFICATIONS

### 1. GENERAL SPECIFICATIONS

#### Memory Capacity

ECM: 128 Kbytes

SAF:

Standard:

3 MB (240 pages) —→ 6MB (480 pages)

\*\*\*\*\*

### 2.2 CAPABILITIES OF PROGRAMMABLE ITEMS

The following table shows the maximum capacity for each programmable item.

Item	Standard
Number of Speed Dials	50*



Item	Standard
Number of Speed Dials	100

### 2. OTHERS

A new PDI (new design) was applied for the release of the new model S-F1. Please see the following details:

- \*New machine PDI graphics are adapted to “Original Table”.
- \*New PDI coloring are adapted to “Original Table” and “Original Tray”.
- \*New PDI operation panel coloring are adapted to the Operation panel.
- \*New PDI branding are adapted to the brand holder.