

⇒ Please use this guide from behind your PC ⇐

### Printer

#### How to install a printer driver...

- 1 Insert the supplied CD-ROM into the CD-ROM drive.
- 2 Select a language and click [OK].
- 3 Click [DDST Printer Driver].
- 4 Click [I accept the agreement.], click [Next >].
- 5 Follow the instructions on the display.

#### How to prepare printing...

- 1 Select [Start], [Printers and Faxes].
- 2 Select the required printer.
- 3 Select [Set as Default Printer].
- 4 Select [Printing Preferences...].
- 5 Make the settings you want, click [OK].

#### How to print...

- 1 Open your document.
- 2 Press directly the 'Print' icon, or press [File], [Print], [Properties].
- 3 Make the settings you want, click [OK].

### Scanner



#### How to install a TWAIN Driver...

- 1 Insert the supplied CD-ROM into the CD-ROM drive.
- 2 Select a language and click [OK].
- 3 Click [DDST TWAIN Driver].
- 4 Follow the instructions on the display.

#### Scanning Originals

To use the network TWAIN scanner, a TWAIN-compliant application and the TWAIN driver must be installed on the client computer. When scanning originals using a TWAIN-compliant application, select the TWAIN driver, and then specify the scan settings in the Scanner Control dialog box. How to start the TWAIN driver varies depending on the application. For details, see your application's help.

#### Setting Originals

1 An original to be scanned	<b>R</b>			
2 Decide the placement method.	Exposure glass		ADF	
3 Place the original. (There are two original orientations.)	Place the original so that the top edge touches the top left of the exposure glass. 	Place the original so that the top edge touches the rear of the exposure glass. 	Place the top edge of the original first. 	Place the original so that the top edge touches the back of the ADF. 
4 The original displayed on a computer				