Fax Option Type C7500 Machine Code: D356

SERVICE MANUAL

October 2007 Subject to change

Important Safety Notices

WARNING

- Never install telephone wiring during a lightning storm.
- Never install telephone jacks in wet locations unless the jack is specifically designed for wet locations.
- Never touch uninsulated telephone wires or terminals unless the telephone line has been disconnected at the network interface.
- Use caution when installing or modifying telephone lines.
- Avoid using a telephone (other than a cordless type) during an electrical storm. There may be a remote risk of electric shock from lightning.
- Do not use a telephone or cellular phone to report a gas leak in the vicinity of the leak.

- Before installing the fax unit, switch off the main switch, and disconnect the power cord.
- The fax unit contains a lithium battery. The danger of explosion exists if a battery of this type is incorrectly replaced. Replace only with the same or an equivalent type recommended by the manufacturer. Discard batteries in accordance with the manufacturer's instructions and local regulations.

Vote

- Note for Australia:
- Unit must be connected to Telecommunication Network through a line cord which meets the requirements of ACA Technical Standard TS008.

Symbols and Abbreviations

Conventions Used in this Manual

This manual uses several symbols.

Symbol	What it means
•	Refer to section number
Ĩ	Screw
E)	Connector
C	E-ring
$\langle n \rangle$	Clip ring
۲¢	Clamp
	▲ Г

Sideways, LEF

(Long Edge Feed)

Cautions, Notes, etc.

The following headings provide special information:

Lengthwise, SEF

(Short Edge Feed)

WARNING

• Failure to obey warning information could result in serious injury or death.

• Obey these guidelines to ensure safe operation and prevent minor injuries.

🔂 Important

- Obey these guidelines to avoid problems such as misfeeds, damage to originals, loss of valuable data and to prevent damage to the machine.
- Always obey these guidelines to avoid serious problems such as misfeeds, damage to originals, loss of valuable data and to prevent damage to the machine. bold is added for emphasis.

Note

• This document provides tips and advice about how to best service the machine.

TABLE OF CONTENTS

Important Safety Notices	1
Symbols and Abbreviations	2
Conventions Used in this Manual	2
Cautions, Notes, etc	2
1. Installation	
Installation	7
Fax Unit (D356)	7
G3Interface Unit (d357)	13
2. Replacement and Adjustment	
FCU	
3. Troubleshooting	
Error Codes	
IFAX Troubleshooting	
IP-Fax Troubleshooting	
IP-Fax Transmission	
IP-Fax Reception	
4. Service Table	
Cautions	
Service Program Tables	
SP1-XXX (Bit Switches)	
SP2-XXX (RAM Data)	51
SP3-XXX (Tel Line Settings)	
SP4-XXX (ROM Versions)	54
SP5-XXX (Initializing)	54
SP6-XXX (Reports)	
SP7-XXX (Test Modes)	
SP9-XXX (Design Switch Mode)	
Bit Switches	60
System Switches	60
I-Fax Switches	73
Printer Switches	
Communication Switches	
G3 Switches	

G3-2 and G3-3 Switches	
G4 Internal Switches	
G4 Parameter Switches	
IP Fax Switches	
NCU Parameters	
Dedicated Transmission Parameters	
Programming Procedure	
Parameters	
Service RAM Addresses	
5. Detailed Section Descriptions	
Overview	
Boards	
FCU	
MBU	
SG3 Board	
Video Data Path	
Transmission	
Reception	
Fax Communication Features	
Multi-port	
Document Server	
Internet Mail Communication	
IP-Fax	173
What is IP-FAX?	173
T.38 Packet Format	
Settings	
6. Specifications	
General Specifications	
Capabilities of Programmable Items	
IFax Specifications	
IP-Fax Specifications	
Fax Unit Configuration	


Installation

Fax Unit (D356)

Component Check


Check the quantity and condition of the components against the following list.

No.	Description	Q'ty
1	PCB: VITS	1
2	PCB: FCU	1
3	Speaker	1
4	Ferrite Core	1
5	S/N Decal	1
6	Screws	10
7	Fax Key	2
8	G3 Decal	1
9	Telephone Cable (NA only)	
10	Multi-Language Decals (EU only)	2
11	Fax NA Decal (NA, AA only)	1
12	EMC Address Decal (EU only	1
13	Numeric Key Decal (AA only) 1	
14	Quick Reference Fax Guide (AA only)	
15	FCC Decal (NA only)	1




Installation Procedure


- Before installing this fax unit,
- Print out all data in the printer buffer.
- Turn off the main power switch and disconnect the power cord and the network cable.




- 1. Disconnect the ARDF connector [A].
- 2. Remove:
 - [B] Upper cover (⋛x2, ⋛ Stepped x2)
 - [C] Lower Cover ((곍x2)



3. Remove the controller box cover [A] ($\hat{\mathscr{B}}x16$).



- 4. Attach the speaker [A] (🖗 x11)
- 5. Use the tip of a small screwdriver to break out plastic covers [B] of the "TEL" and "LINE 1" jacks.



- 6. Attach the FCU [A] to the controller box ($\hat{\mathscr{F}}x4$).
- 7. Attach the VITS [B] to the FCU and controller box ($\hat{\mathscr{F}}x4$)
- 8. Detach the MBU battery jumper [C] and reattach it at the "ON" position.


Note

• If the MBU jumper is not set to ON, this can cause SC819 or SC820 when the main power switch is turned on. Also, when the main power switch is turned off, fax memory will be cleared.

9. Press down on the MBU to confirm that it is seated correctly.


• Note

- If the MBU is not attached correctly, this will cause SC672.
- 10. Connect the speaker harness [D] to the FCU (⊑^Jx1).
- 11. Check the FCU connection and confirm that it is secure.



d356i106


- 12. Reattach:
 - Controller box [A] (⋛x16)
 - Rear lower cover (𝔅 x2)
 - Rear upper cover (🖗 x3, Stepped 🖗 x2)
 - 1. Connect the telephone cable to the "LINE 1" jack.




2. Attach the ferrite core to the telephone cable.

Note

• The end of the ferrite core must be about 5 cm (2.1") from the end of the cable.



3. Replace the key slot cover [A] (fourth from the bottom) with the fax key [B].




- 4. Attach:
 - SUPER G3 decal [A]
 - Serial number decal under machine serial number decal
 - Numeric key decal on the operation panel keypad (for AA only)
- 5. Attach the FCC decal on the rear cover of the copier (NA only).
- 6. Confirm that the machine is grounded correctly at the power source.
- 7. Switch on the machine and confirm that it is operating correctly.
- 8. Confirm that the date and time settings (User Tools) are correct.
- 9. Keep the EMC address decal at the customer site.

G3Interface Unit (d357)

Component check

Check the quantity and condition of the components against the following list.

No.	Description	Q'ty
1	PCB: CCUIF	1
2	PCB: SG3	1
3	Screws	7
4	Harness Clamp	1
5	Ferrite Core	1
6	Telephone Cable (NA only)	1
7	Harness	1
8	Flat Cable	1
9	EMC Address Decal (EU only)	1
10	FCC Decal (NA only)	1




d357i101

• Before installing this optional unit,

- Print out all data in the printer buffer.
- Turn off the main switch and disconnect the power cord and the network cable.


You can add two more SG3 boards to this model. Follow the procedures for adding the single SG3 board installation or double SG3 boards installation.



- 1. Disconnect the ARDF connector [A].
- 2. Remove:

[B] Upper cover ($\hat{\mathscr{F}} x2$, $\hat{\mathscr{F}}$ Stepped x2)

[C] Lower Cover (⋛x2)




3. Remove the controller box cover [A] ($\hat{\mathscr{F}}x16$)

😪 Important

- Important! If the Fax Unit (D356) has already been installed, skip Steps 4, 5 and go to Step 6.
- 4. Disconnect the speaker harness (\mathbb{E}_{x1}).
- 5. Remove the FCU and VITS ($\hat{\beta}$ x5).


To install a Single G3 Board



- 1. Attach the CCUIF [A] to the SG3 board [B].
- 2. Attach the assembled CCUIF/SG3 board to the FCU [C] ($\not\!\!\!/ x7).$


3. Connect harness [D] to the FCU [C].

To install the Double SG3 Boards




- 1. Connect the CCUIF [A] to the SG3 boards [B].
- 2. Attach the assembled CCUIF/SG3 boards to the FCU [C] ($\not Fx9$).


To complete the installation



- 1. Connect the flat cable [A] to the CCUIF and FCU.
- 2. Attach the clamp [B] as shown.



- Use the tip of a small screwdriver to break out the "LINE2" jack cover [A] (for one SG3 board), or the "LINE2" and "LINE3" jack covers [A] and [B] (for two SG3 boards).
- 4. Attach the speaker [C] (⋛x1)




- 5. Install the FCU [A] on the controller board ($\hat{\mathscr{F}}x4$).
- 6. Attach the VITS [B] to the FCU and controller box ($\hat{\mathscr{F}}x4$).
- 7. Detach the MBU battery jumper [C] and reattach it at the "ON" position.

• Note

- If the MBU jumper is not set to ON, this can cause SC819 or SC820 when the main power switch is turned on. Also, when the main power switch is turned off, fax memory will be cleared.
- 8. Press down on the MBU to confirm that it is seated correctly.


Vote

- If the MBU is not attached correctly, this will cause SC672.
- 9. Connect the speaker harness [D] to the FCU (⊑^Jx1).
- 10. Check the FCU connection and confirm that it is secure.



d356i106

- 11. Reattach:
 - Controller box [A] (𝔅x16)
 - Rear lower cover (\$\$x2)
 - Rear upper cover (🕅 x3, Stepped 🖗 x2)
 - 1. Connect the telephone cable to the "LINE 2" or "LINE 3" jack.



2. Attach the ferrite core to the telephone cable.

Note

- The end of the ferrite core must be about 5 cm (2.1") from the end of the cable.
- 3. Attach the FCC decal to the rear cover of the copier (NA only).
- 4. Confirm that the machine is grounded correctly at the power source.
- 5. Switch on the machine and confirm that it is operating correctly.
- 6. Confirm that the date and time settings (User Tools) are correct.
- 7. Enter the SP mode.
- 8. Do either of these settings:

If one SG3 board is installed:

- Do SP1104-23
- Set Bit 1 of Communication Switch 16 to "1".

-or-

If two SG3 boards are installed:

- Do SP1104-23
- Set Bit 1 and Bit 3 of the Communication Switch 16 to "1".
- 9. Exit the SP mode.
- 10. Cycle the machine off/on.
- 11. Print out the system parameter list and confirm that "G3" is listed as an option.
- 12. Do the program settings required for PSTN-2 communication.
- 13. Keep the EMC address decal at the customer site (EU only).

1. Installation

2. Replacement and Adjustment

FCU

- 1. When you replace the FCU board, remove the MBU board from the old FCU board and install it on the new FCU board.
- 2. Set the correct date and time with the User Tools:
 - User Tools> System Settings> Timer Setting> Set Date/Time

Note

- Do not turn off the battery switch (SW1).
- Do SP6101 to print the system parameters. Then check the settings.

2. Replacement and Adjustment

Error Codes

If an error code occurs, retry the communication. If the same problem occurs, try to fix the problem as suggested below. Note that some error codes appear only in the error code display and on the service report.

Code	Meaning	Suggested Cause/Action
0-00	DIS/NSF not detected within 40 s of Start being pressed	 Check the line connection. Check the NCU - FCU connectors. The machine at the other end may be incompatible. Replace the NCU or FCU. Check for DIS/NSF with an oscilloscope. If the rx signal is weak, there may be a bad line.
0-01	DCN received unexpectedly	The other party is out of paper or has a jammed printer.The other party pressed Stop during communication.
0-03	Incompatible modem at the other end	• The other terminal is incompatible.
0-04	CFR or FTT not received after modem training	 Check the line connection. Check the NCU - FCU connectors. Try changing the tx level and/or cable equalizer settings. Replace the FCU or NCU. The other terminal may be faulty; try sending to another machine. If the rx signal is weak or defective, there may be a bad line. Cross reference Tx level - NCU Parameter 01 (PSTN) Cable equalizer - G3 Switch 07 (PSTN) Dedicated Tx parameters - Section 4
0-05	Unsuccessful after modem training at 2400 bps	Check the line connection.Check the NCU - FCU connectors.

Code	Meaning	Suggested Cause/Action
		 Try adjusting the tx level and/or cable equalizer. Replace the FCU or NCU. Check for line problems. Cross reference See error code 0-04.
0-06	The other terminal did not reply to DCS	 Check the line connection. Check the FCU - NCU connectors. Try adjusting the tx level and/or cable equalizer settings. Replace the NCU or FCU. The other end may be defective or incompatible; try sending to another machine. Check for line problems. Cross reference See error code 0-04.
0-07	No post-message response from the other end after a page was sent	 Check the line connection. Check the FCU - NCU connectors. Replace the NCU or FCU. The other end may have jammed or run out of paper. The other end user may have disconnected the call. Check for a bad line. The other end may be defective; try sending to another machine.
0-08	The other end sent RTN or PIN after receiving a page, because there were too many errors	 Check the line connection. Check the FCU - NCU connectors. Replace the NCU or FCU. The other end may have jammed, or run out of paper or memory space. Try adjusting the tx level and/or cable equalizer settings. The other end may have a defective modem/NCU/ FCU; try sending to another machine.

Code	Meaning	Suggested Cause/Action
		Check for line problems and noise.
		Cross reference
		 Tx level - NCU Parameter 01 (PSTN)
		 Cable equalizer - G3 Switch 07 (PSTN)
		Dedicated Tx parameters - Section 4
		• Check the FCU - NCU connectors.
		 Incompatible or defective remote terminal; try sending to another machine.
		• Noisy line: resend.
0-14	Non-standard post message response code received	 Try adjusting the tx level and/or cable equalizer settings.
		Replace the NCU or FCU.
		Cross reference
		• See error code 0-08.
	The other terminal is not capable of specific functions.	• The other terminal is not capable of accepting the following functions, or the other terminal's memory is full.
0-15		Confidential rx
		Transfer function
		SEP/SUB/PWD/SID
		Check the line connection.
	CFR or FTT not detected after modem training in confidential or transfer mode	• Check the FCU - NCU connectors.
		Replace the NCU or FCU.
0-16		 Try adjusting the tx level and/or cable equalizer settings.
		 The other end may have disconnected, or it may be defective; try calling another machine.
		 If the rx signal level is too low, there may be a line problem.
		Cross reference
		• See error code 0-08.

Code	Meaning	Suggested Cause/Action
0-20	Facsimile data not received within 6 s of retraining	 Check the line connection. Check the FCU - NCU connectors. Replace the NCU or FCU. Check for line problems. Try calling another fax machine. Try adjusting the reconstruction time for the first line and/or rx cable equalizer setting. Cross reference Reconstruction time - G3 Switch 0A, bit 6 Rx cable equalizer - G3 Switch 07 (PSTN)
0-21	EOL signal (end-of-line) from the other end not received within 5 s of the previous EOL signal	 Check the connections between the FCU, NCU, & line. Check for line noise or other line problems. Replace the NCU or FCU. The remote machine may be defective or may have disconnected. Cross reference Maximum interval between EOLs and between ECM frames - G3 Bit Switch OA, bit 4
0-22	The signal from the other end was interrupted for more than the acceptable modem carrier drop time (default: 200 ms)	 Check the line connection. Check the FCU - NCU connectors. Replace the NCU or FCU. Defective remote terminal. Check for line noise or other line problems. Try adjusting the acceptable modem carrier drop time. Cross reference Acceptable modem carrier drop time - G3 Switch 0A, bits 0 and 1
0-23	Too many errors during reception	 Check the line connection. Check the FCU - NCU connectors. Replace the NCU or FCU. Defective remote terminal. Check for line noise or other line problems.

Code	Meaning	Suggested Cause/Action
		• Try asking the other end to adjust their tx level.
		 Try adjusting the rx cable equalizer setting and/or rx error criteria.
		Cross reference
		• Rx cable equalizer - G3 Switch 07 (PSTN)
		 Rx error criteria - Communication Switch 02, bits 0 and 1
		Check the line connection.
		• Check the FCU - NCU connectors.
0-30	The other terminal did not reply to NSS(A) in Al short	 Try adjusting the tx level and/or cable equalizer settings.
	protocol mode	• The other terminal may not be compatible.
		Cross reference
		• Dedicated tx parameters - Section 4
0-32	The other terminal sent a DCS, which contained functions that the receiving machine cannot handle.	Check the protocol dump list.Ask the other party to contact the manufacturer.
	Polarity changed during	Check the line connection.
0-52	communication	Retry the communication.
	FCE does not detect the SG3- V34.	FCU firmware or board defective.
0-55		• SG3-V34 firmware or board defective.
0-56	The stored message data exceeds the capacity of the mailbox in the SG3-V34.	• SG3-V34 firmware or board defective.
0-70	The communication mode specified in CM/JM was not available	 The other terminal did not have a compatible communication mode (e.g., the other terminal was a V.34 data modem and not a fax modem.)
	(V.8 calling and called terminal)	• A polling tx file was not ready at the other terminal when polling rx was initiated from the calling terminal.
0-74	The calling terminal fell back to T.30 mode, because it	 The calling terminal could not detect ANSam due to noise, etc. ANSam was too short to detect.

Code	Meaning	Suggested Cause/Action
	could not detect ANSam after sending CI.	Check the line connection and condition.Try making a call to another V.8/V.34 fax.
0-75	The called terminal fell back to T.30 mode, because it could not detect a CM in response to ANSam (ANSam timeout).	 The terminal could not detect ANSam. Check the line connection and condition. Try receiving a call from another V.8/V.34 fax.
0-76	The calling terminal fell back to T.30 mode, because it could not detect a JM in response to a CM (CM timeout).	 The called terminal could not detect a CM due to noise, etc. Check the line connection and condition. Try making a call to another V.8/V.34 fax.
0-77	The called terminal fell back to T.30 mode, because it could not detect a CJ in response to JM (JM timeout).	 The calling terminal could not detect a JM due to noise, etc. A network that has narrow bandwidth cannot pass JM to the other end. Check the line connection and condition. Try receiving a call from another V.8/V.34 fax.
0-79	The called terminal detected CI while waiting for a V.21 signal.	 Check for line noise or other line problems. If this error occurs, the called terminal falls back to T. 30 mode.
0-80	The line was disconnected due to a timeout in V.34 phase 2 – line probing.	The guard timer expired while starting these phases. Serious noise, narrow bandwidth, or low signal level can cause these errors.
0-81	The line was disconnected due to a timeout in V.34 phase 3 – equalizer training.	 If these errors happen at the transmitting terminal: Try making a call at a later time. Try using V.17 or a slower modem using dedicated tx
0-82	The line was disconnected due to a timeout in the V.34 phase 4 – control channel start-up.	 parameters. Try increasing the tx level. Try adjusting the tx cable equalizer setting. If these errors happen at the receiving terminal:
0-83	The line was disconnected due to a timeout in the V.34	Try adjusting the rx cable equalizer setting.Try increasing the tx level.

Code	Meaning	Suggested Cause/Action
	control channel restart sequence.	• Try using V.17 or a slower modem if the same error is frequent when receiving from multiple senders.
0-84	The line was disconnected due to abnormal signaling in V.34 phase 4 – control channel start-up.	 The signal did not stop within 10 s. Turn off the machine, then turn it back on. If the same error is frequent, replace the FCU.
0-85	The line was disconnected due to abnormal signaling in V.34 control channel restart.	 The signal did not stop within 10 s. Turn off the machine, then turn it back on. If the same error is frequent, replace the FCU.
0-86	The line was disconnected because the other terminal requested a data rate using MPh that was not available in the currently selected symbol rate.	The other terminal was incompatible.Ask the other party to contact the manufacturer.
0-87	The control channel started after an unsuccessful primary channel.	 The receiving terminal restarted the control channel because data reception in the primary channel was not successful. This does not result in an error communication.
0-88	The line was disconnected because PPR was transmitted/received 9 (default) times within the same ECM frame.	Try using a lower data rate at the start.Try adjusting the cable equalizer setting.
2-11	Only one V.21 connection flag was received	• Replace the FCU.
2-12	Modem clock irregularity	Replace the FCU.
2-13	Modem initialization error	 Turn off the machine, then turn it back on. Update the modem ROM. Replace the FCU.
2-23	JBIG compression or reconstruction error	Turn off the machine, then turn it back on.Replace the EXFUNC board if the error is frequent.

Code	Meaning	Suggested Cause/Action
2-24	JBIG ASIC error	Turn off the machine, then turn it back on.Replace the EXFUNC board if the error is frequent.
2-25	JBIG data reconstruction error (BIH error)	
2-26	JBIG data reconstruction error (Float marker error)	 JBIG data error Check the sender's JBIG function.
2-27	JBIG data reconstruction error (End marker error)	Update the MBU ROM.
2-28	JBIG data reconstruction error (Timeout)	
2-29	JBIG trailing edge maker error	FCU defectiveCheck the destination device.
2-50	The machine resets itself for a fatal FCU system error	• If this is frequent, update the ROM, or replace the FCU.
2-51	The machine resets itself because of a fatal communication error	• If this is frequent, update the ROM, or replace the FCU.
2-53	Snd msg() in the manual task is an error because the mailbox for the operation task is full.	 The user did the same operation many times, and this gave too much load to the machine.
4-01	Line current was cut	 Check the line connector. Check the connection between FCU and NCU. Check for line problems. Replace the FCU or the NCU.
4-10	Communication failed because of an ID Code mismatch (Closed Network) or Tel. No./CSI mismatch (Protection against Wrong Connections)	 Get the ID Codes the same and/or the CSIs programmed correctly, then resend. The machine at the other end may be defective.
5-10	DCR timer expired	Replace the FCU.

Code	Meaning	Suggested Cause/Action
5-20	Storage impossible because of a lack of memory	Temporary memory shortage.Test the SAF memory.
5-21	Memory overflow	Replace the FCU or optional EXMEM board
5-23	Print data error when printing a substitute rx or confidential rx message	Test the SAF memory.Ask the other end to resend the message.Replace the FCU or optional EXMEM board.
5-25	SAF file access error	• Replace the FCU or EXMEM board.
6-00	G3 ECM - T1 time out during reception of facsimile data	
6-01	G3 ECM - no V.21 signal was received	Try adjusting the rx cable equalizer.Replace the FCU or NCU.
6-02	G3 ECM - EOR was received	
6-04	G3 ECM - RTC not detected	 Check the line connection. Check connections from the NCU to the FCU. Check for a bad line or defective remote terminal. Replace the FCU or NCU.
6-05	G3 ECM - facsimile data frame not received within 18 s of CFR, but there was no line fail	 Check the line connection. Check connections from the NCU to the FCU. Check for a bad line or defective remote terminal. Replace the FCU or NCU. Try adjusting the rx cable equalizer Cross reference Rx cable equalizer - G3 Switch 07 (PSTN)
6-06	G3 ECM - coding/decoding error	Defective FCU.The other terminal may be defective.
6-08	G3 ECM - PIP/PIN received in reply to PPS.NULL	The other end pressed Stop during communication.The other terminal may be defective.
6-09	G3 ECM - ERR received	Check for a noisy line.Adjust the tx levels of the communicating machines.

Code	Meaning	Suggested Cause/Action
		• See code 6-05.
6-10	G3 ECM - error frames still received at the other end after all communication attempts at 2400 bps	 Check for line noise. Adjust the tx level (use NCU parameter 01 or the dedicated tx parameter for that address). Check the line connection. Defective remote terminal.
6-21	V.21 flag detected during high speed modem communication	• The other terminal may be defective or incompatible.
6-22	The machine resets the sequence because of an abnormal handshake in the V. 34 control channel	 Check for line noise. If the same error occurs frequently, replace the FCU. Defective remote terminal.
6-99	V.21 signal not stopped within 6 s	• Replace the FCU.
13-17	SIP user name registration error	 Double registration of the SIP user name. Capacity for user-name registration in the SIP server is not sufficient.
13-18	SIP server access error	Incorrect initial setting for the SIP server.Defective SIP server.
14-00	SMTP Send Error	Error occurred during sending to the SMTP server. Occurs for any error other than 14-01 to 16. For example, the mail address of the system administrator is not registered.
14-01	SMTP Connection Failed	 Failed to connect to the SMTP server (timeout) because the server could not be found. The PC is not ready to transfer files. SMTP server not functioning correctly. The DNS IP address is not registered. Network not operating correctly. Destination folder selection not correct.
14-02	No Service by SMTP Service (421)	SMTP server operating incorrectly, or the destination for direct SMTP sending is not correct.

Code	Meaning	Suggested Cause/Action
		 Contact the system administrator and check that the SMTP server has the correct settings and operates correctly. Contact the system administrator for direct SMTP sending and check the sending destination.
14-03	Access to SMTP Server Denied (450)	Failed to access the SMTP server because the access is denied.
		• SMTP server operating incorrectly. Contact the system administrator to determine if there is a problem with the SMTP server and to check that the SMTP server settings are correct.
		 Folder send destination is incorrect. Contact the system administrator to determine that the SMTP server settings and path to the server are correct.
		 Device settings incorrect. Confirm that the user name and password settings are correct.
		 Direct SMTP destination incorrect. Contact the system administrator to determine if there is a problem at the destination at that the settings at the destination are correct.
14-04	Access to SMTP Server	SMTP server operating incorrectly
14-04	Denied (550)	Direct SMTP sending not operating correctly
	SMTP Server HDD Full (452)	Failed to access the SMTP server because the HDD on the server is full.
14-05		 Insufficient free space on the HDD of the SMTP server. Contact the system administrator and check the amount of space remaining on the SMTP server HDD.
		 Insufficient free space on the HDD where the destination folder is located. Contact the system administrator and check the amount of space remaining on the HDD where the target folder is located.
		 Insufficient free space on the HDD at the target destination for SMTP direct sending. Contact the system administrator and check the amount of space remaining on the target HDD.

Code	Meaning	Suggested Cause/Action
14-06	User Not Found on SMTP Server (551)	 The designated user does not exist. The designated user does not exist on the SMTP server. The designated address is not for use with direct SMTP sending.
14-07	Data Send to SMTP Server Failed (4XX)	 Failed to access the SMTP server because the transmission failed. PC not operating correctly. SMTP server operating incorrectly Network not operating correctly. Destination folder setting incorrect. Direct SMTP sending not operating correctly.
14-08	Data Send to SMTP Server Failed (5XX)	 Failed to access the SMTP server because the transmission failed. SMTP server operating incorrectly Destination folder setting incorrect. Direct SMTP sending not operating correctly. Software application error.
14-09	Authorization Failed for Sending to SMTP Server	POP-Before-SMTP or SMTP authorization failed.Incorrect setting for file transfer
14-10	Addresses Exceeded	Number of broadcast addresses exceeded the limit for the SMTP server.
14-11	Buffer Full	The send buffer is full so the transmission could not be completed. Buffer is full due to using Scan-to-Email while the buffer is being used send mail at the same time.
14-12	Data Size Too Large	Transmission was cancelled because the detected size of the file was too large.
14-13	Send Cancelled	Processing is interrupted because the user pressed Stop.
14-30	MCS File Creation Failed	 Failed to create the MCS file because: The number of files created with other applications on the Document Server has exceeded the limit. HDD is full or not operating correctly.

Code	Meaning	Suggested Cause/Action
		Software error.
14-31	UFS File Creation Failed	 UFS file could not be created: Not enough space in UFS area to handle both Scanto-Email and IFAX transmission. HDD full or not operating correctly. Software error.
14-32	Cancelled the Mail Due to Error Detected by NFAX	Error detected with NFAX and send was cancelled due to a software error.
14-33	No Mail Address For the Machine	Neither the mail address of the machine nor the mail address of the network administrator is registered.
14-34	Address designated in the domain for SMTP sending does not exist	 Operational error in normal mail sending or direct SMTP sending. Check the address selected in the address book for SMTP sending. Check the domain selection.
14-50	Mail Job Task Error	 Due to an FCU mail job task error, the send was cancelled: Address book was being edited during creation of the notification mail. Software error.
14-51	UCS Destination Download Error	 Not even one return notification can be downloaded: The address book was being edited. The number for the specified destination does not exist (it was deleted or edited after the job was created).
14-60	Send Cancel Failed	The cancel operation by the user failed to cancel the send operation.
14-61	Notification Mail Send Failed for All Destinations	All addresses for return notification mail failed.
15-01	POP3/IMAP4 Server Not Registered	At startup, the system detected that the IP address of the POP3/IMAP4 server has not been registered in the machine.
15-02	POP3/IMAP4 Mail Account Information Not Registered	The POP3/IMAP4 mail account has not been registered.

Code	Meaning	Suggested Cause/Action	
15-03	Mail Address Not Registered	The mail address has not been registered.	
15-10	DCS Mail Receive Error	Error other than 15-11 to 15-18.	
15-11	Connection Error	 The DNS or POP3/IMAP4 server could not be found: The IP address for DNS or POP3/IMAP4 server is not stored in the machine. The DNS IP address is not registered. Network not operating correctly. 	
15-12	Authorization Error	 POP3/IMAP4 send authorization failed: Incorrect IFAX user name or password. Access was attempted by another device, such as the PC. POP3/IMAP4 settings incorrect. 	
15-13	Receive Buffer Full	Occurs only during manual reception. Transmission cannot be received due to insufficient buffer space. The buffer is being used for mail send or Scan-to-Email.	
15-14	Mail Header Format Error	The mail header is not standard format. For example, the Date line description is incorrect.	
15-15	Mail Divide Error	The e-mail is not in standard format. There is no boundary between parts of the e-mail, including the header.	
15-16	Mail Size Receive Error	The mail cannot be received because it is too large.	
15-17	Receive Timeout	May occur during manual receiving only because the network is not operating correctly.	
15-18	Incomplete Mail Received	Only one portion of the mail was received.	
15-31	Final Destination for Transfer Request Reception Format Error	The format of the final destination for the transfer request was incorrect.	
15-39	Send/Delivery Destination Error	 The transmission cannot be delivered to the final destination: Destination file format is incorrect. Could not create the destination for the file transmission. 	

Code	Meaning	Suggested Cause/Action
15-41	SMTP Receive Error	Reception rejected because the transaction exceeded the limit for the "Auth. E-mail RX" setting.
15-42	Off Ramp Gateway Error	The delivery destination address was specified with Off Ramp Gateway OFF.
15-43	Address Format Error	Format error in the address of the Off Ramp Gateway.
15-44	Addresses Over	The number of addresses for the Off Ramp Gateway exceeded the limit of 30.
15-61	Attachment File Format Error	The attached file is not TIFF format.
15-62	TIFF File Compatibility Error	 Could not receive transmission due to: Resolution error Image of resolution greater than 200 dpi without extended memory. Resolution is not supported. Page size error The page size was larger than A3. Compression error File was compressed with other than MH, MR, or MMR.
15-63	TIFF Parameter Error	 The TIFF file sent as the attachment could not be received because the TIFF header is incorrect: The TIFF file attachment is a type not supported. The TIFF file attachment is corrupted. Software error.
15-64	TIFF Decompression Error	 The file received as an attachment caused the TIFF decompression error: The TIFF format of the attachment is corrupted. Software error.
15-71	Not Binary Image Data	The file could not be received because the attachment was not binary image data.
15-73	MDN Status Error	Could not find the Disposition line in the header of the Return Receipt, or there is a problem with the firmware.

Code	Meaning	Suggested Cause/Action
15-74	MSDN Message ID Error	Could not find the Original Message ID line in the header of the Return Receipt, or there is a problem with the firmware.
15-80	Mail Job Task Read Error	Could not receive the transmission because the destination buffer is full and the destination could not be created (this error may occur when receiving a transfer request or a request for notification of reception).
15-81	Repeated Destination Registration Error	Could not repeat receive the transmission because the destination buffer is full and the destination could not be created (this error may occur when receiving a transfer request or a request for notification of reception).
15-91	Send Registration Error	 Could not receive the file for transfer to the final destination: The format of the final destination or the transfer destination is incorrect. Destinations are full so the final and transfer destinations could not be created.
15-92	Memory Overflow	Transmission could not be received because memory overflowed during the transaction.
15-93	Memory Access Error	Transaction could not complete due to a malfunction of SAF memory.
15-94	Incorrect ID Code	The machine rejected an incoming e-mail for transfer request, because the ID code in the incoming e-mail did not match the ID code registered in the machine.
15-95	Transfer Station Function	The machine rejected an incoming e-mail for transfer because the transfer function was unavailable.
22-00	Original length exceeded the maximum scan length	 Divide the original into more than one page. Check the resolution used for scanning. Lower the scan resolution if possible. Add optional page memory.
22-01	Memory overflow while receiving	 Wait for the files in the queue to be sent. Delete unnecessary files from memory. Transfer the substitute reception files to another fax machine, if the machine's printer is busy or out of order. Add an optional SAF memory card or hard disk.

Code	Meaning	Suggested Cause/Action
22-02	Tx or rx job stalled due to line disconnection at the other end	 The job started normally but did not finish normally; data may or may not have been received fully. Restart the machine.
22-04	The machine cannot store received data in the SAF	Update the ROMReplace the FCU.
22-05	No G3 parameter confirmation answer	• Defective FCU board or firmware.
23-00	Data read timeout during construction	 Restart the machine. Replace the FCU
25-00	The machine software resets itself after a fatal transmission error occurred	Update the ROMReplace the FCU.
FO-xx	V.34 modem error	• Replace the FCU.
F6-xx	SG3-V34 modem error	 Update the SG3-V34 modem ROM. Replace the SG3-V34 board. Check for line noise or other line problems. Try communicating another V.8/V.34 fax.

IFAX Troubleshooting

Use the following procedures to determine whether the machine or another part of the network is causing the problem.

Communication Route	ltem	Action	Remarks
General LAN	1. Connection with the LAN	 Check that the LAN cable is connected to the machine. Check that the LEDs on the hub are lit. 	
	2. LAN activity	 Check that other devices connected to the LAN can communicate through the LAN. 	
	1. Network settings on the PC	 Check the network settings on the PC. 	 Is the IP address registered in the TCP/ IP properties in the network setup correct? Check the IP address with the administrator of the network.
Between IFAX and PC	2. Check that PC can connect with the machine	 Use the "ping" command on the PC to contact the machine. 	• At the MS-DOS prompt, type ping then the IP address of the machine, then press Enter.
	3. LAN settings in the machine	 Check the LAN parameters Check if there is an IP address conflict with other PCs. 	 Use the "Network" function in the User Tools. If there is an IP address conflict, inform the administrator.

Communication Route	ltem	Action	Remarks
	1. LAN settings in the machine	 Check the LAN parameters Check if there is an IP address conflict with other PCs. 	 Use the "Network" function in the User Tools. If there is an IP address conflict, inform the administrator.
Between machine and e-mail server	2. E-mail account on the server	 Make sure that the machine can log into the e-mail server. Check that the account and password stored in the server are the same as in the machine. 	• Ask the administrator to check.
	3. E-mail server	 Make sure that the client devices which have an account in the server can send/ receive e-mail. 	 Ask the administrator to check. Send a test e-mail with the machine's own number as the destination. The machine receives the returned e-mail if the communication is performed successfully.
Between e-mail server and internet	1. E-mail account on the Server	 Make sure that the PC can log into the e-mail server. Check that the account and password stored in the server are the same as in the machine. 	 Ask the administrator to check.

Communication Route	ltem	Action	Remarks
	2. E-mail server	 Make sure that the client devices which have an account in the server can send/ receive e-mail. 	 Ask the administrator to check. Send a test e-mail with the machine's own number as the destination. The machine receives the returned e-mail if the communication is performed successfully.
	3. Destination e-mail address	 Make sure that the e- mail address is actually used. Check that the e-mail address contains no incorrect characters such as spaces. 	
	4. Router settings	 Use the "ping" command to contact the router. Check that other devices connected to the router can sent data over the router. 	• Ask the administrator of the server to check.
	5. Error message by e-mail from the network of the destination.	 Check whether e-mail can be sent to another address on the same network, using the application e-mail software. Check the error e-mail message. 	 Inform the administrator of the LAN.

IP-Fax Troubleshooting

IP-Fax Transmission

Cannot send by IP Address/Host Name

	Check Point	Action
1	LAN cable connected?	Check the LAN cable connection.
2	Specified IP address/host name correct?	Check the IP address/host name.
3	Firewall/NAT is installed?	Cannot breach the firewall. Send by using another method (Fax, Internet Fax)
4	Transmission sent manually?	Manual sending not supported.
5	IP address of local machine registered?	Register the IP address.
6	Remote terminal port number setting other than 1720?	Send by specifying the port number.
7	Specified port number correct?	Confirm the port number of the remote fax.
8	DNS server registered when host name specified?	Contact the network administrator.
9	Remote fax a T.38 terminal?	Check whether the remote fax is a T38 terminal.
10	Remote fax switched off or busy?	Check that the remote fax is switched on.
		Request the network administrator to increase the bandwidth.
11	Network bandwidth too narrow?	Raise the delay level. IPFAX SW 01 Bit 0 to 3
		IP-Fax bandwidth is the same as the DCS speed. Set IP-Fax SW00 Bit 6 to 1.
12	Remote fax cancelled transmission?	Check whether the remote fax cancelled the transmission.

Cannot send via VoIP Gateway

	Check Point	Action
1	LAN cable connected?	Check the LAN cable connection.
2	VoIP Gateway T.38 standard?	Contact the network administrator.
3	VoIP Gateway installed correctly?	Contact the network administrator.
4	VoIP Gateway power switched on?	Contact the network administrator.
5	Is the IP address/host name of the specified Gateway correct?	Check the IP address/host name.
6	Number of the specified fax correct?	Check the remote fax number.
7	Firewall/NAT is installed?	Cannot breach the firewall. Send by using another method (Fax, Internet Fax)
8	Transmission sent manually?	Manual sending not supported.
9	IP address of local fax registered?	Register the IP address.
10	DNS registered when host name specified?	Contact the network administrator.
11	Remote fax a G3 fax?	Check that the remote fax is a G3 fax.
12	G3 fax is connected to VoIP gateway?	Check that G3 fax is connected.
13	Remote G3 fax turned on?	Check that G3 fax is switched on.
		Request the network administrator to increase the bandwidth.
14	Network bandwidth too narrow?	Raise the network delay level. IPFAX SW 01 Bit 0 to 3
		IP-Fax bandwidth is the same as the DCS speed. Set IP-Fax SW00 Bit 6 to 1.

Cannot send by Alias Fax number.

Check Point		Action
1	LAN cable connected?	Check the LAN cable connection.

Check Point		Action
2	Number of specified Alias fax correct?	Confirm the Alias of the remote fax. Error Code: 13-14
3	Firewall/NAT installed?	Cannot breach the firewall. Send by using another method (Fax, Internet Fax)
4	Transmission sent manually?	Manual sending not supported.
5	Gatekeeper installed correctly?	Contact the network administrator.
6	Gatekeeper power switched on?	Contact the network administrator.
7	IP address/host name of Gatekeeper correct?	Check the IP address/host name.
8	DNS server registered when Gatekeeper host name specified?	Contact the network administrator.
9	Enable H.323 SW is set to on?	Check the settings. See User Parameter SW 34 Bit 0
10	IP address of local fax registered?	Register the IP address of the local fax.
11	Alias number of local fax registered?	Register the Alias number of the local fax.
12	Remote fax registered in Gatekeeper?	Contact the network administrator.
13	Remote fax a T.38 terminal?	Check whether the remote fax is a T38 terminal.
14	Remote fax switched off or busy?	Contact the network administrator.
		Request the system administrator to increase the bandwidth.
15	Network bandwidth too narrow?	Raise the delay level. IPFAX SW 01 Bit 0 to 3
		Lower the modem transmission baud rate. IPFAX SW 05
16	Remote fax cancelled transmission?	Check whether the remote fax cancelled the transmission.

IP-Fax Reception

Cannot receive by IP Address/Host name

	Check Point	Action
1	LAN cable connected?	Check the LAN cable connection.
2	Firewall/NAT is installed?	Cannot breach the firewall. Send by using another method (Fax, Internet Fax)
3	IP address of local fax registered?	Register the IP address.
4	Port number specified at remote sender fax (if required)?	Request the sender to specify the port number.
5	Specified port number correct (if required)?	Request the sender to check the port number.
6	DNS server registered when host name specified on sender side?	Contact the network administrator. Note: The sender machine displays this error code if the sender fax is a Ricoh model.
7	7 Network bandwidth too narrow?	Request the system administrator to increase the bandwidth.
		Lower the start modem reception baud rate on the receiving side. IPFAX SW06
8	Remote fax cancelled transmission?	Check whether the remote fax cancelled the transmission.

Cannot receive by VoIP Gateway.

	Check Point	Action
1	LAN cable connected?	Check the LAN cable connection.
2	Firewall/NAT is installed?	Cannot breach the firewall. Request the remote fax to send by using another method (Fax, Internet Fax)
3	VoIP Gateway installed correctly?	Contact the network administrator.
4	VoIP Gateway power switched on?	Contact the network administrator.

	Check Point	Action
5	IP address/host name of specified VoIP Gateway correct on sender's side?	Request the remote fax to check the IP address/ host name.
6	DNS server registered when host name specified on sender side?	Contact the network administrator.
7	Network bandwidth too narrow?	Request the network administrator to increase the bandwidth.
8	G3 fax connected?	Check that G3 fax is connected.
9	G3 fax power switched on?	Check that G3 fax is switched on.

Cannot receive by Alias Fax number.

	Check Point	Action
1	LAN cable connected?	Check the LAN cable connection.
2	Firewall/NAT is installed?	Cannot the breach firewall. Request the remote fax to send by using another method (Fax, Internet Fax)
3	Gatekeeper installed correctly?	Contact the network administrator. Note: The sender machine displays this error code if the sender fax is a Ricoh model.
4	Power to Gatekeeper switched on?	Contact the network administrator. Note: The sender machine displays this error code if the sender fax is a Ricoh model.
5	IP address/host name of Gatekeeper correct on the sender's side?	Request the sender to check the IP address/host name. Note: The sender machine displays this error code if the sender fax is a Ricoh model.
6	DNS server registered when Gatekeeper host name specified on sender's side?	Contact the network administrator. Note: The sender machine displays this error code if the sender fax is a Ricoh model.
7	Enable H.323 SW is set to on?	Request the sender to check the settings. User Parameter SW 34 Bit 0

	Check Point	Action
		Note: Only if the remote sender fax is a Ricoh fax.
8	Local fax IP address registered?	Register the IP address.
9	Local fax Alias number registered?	Register the Alias number.
		Request the system administrator to increase the bandwidth.
10	10 Network bandwidth too narrow?	Lower the start modem reception baud rate on the receiving side. IPFAX SW06
11	Remote fax cancelled transmission?	Check whether the remote fax cancelled the transmission.
12	Local fax registered in Gatekeeper?	Contact the network administrator. Note: The sender machine displays this error code if the sender fax is a Ricoh model.

4. Service Table

Cautions

• Never turn off the main power switch when the power LED is lit or flashing. To avoid damaging the hard disk or memory, press the operation power switch to switch the power off, wait for the power LED to go off, and then switch the main power switch off.

Vote

• The main power LED (★①) lights or flashes while the platen cover or ARDF is open, while the main machine is communicating with a facsimile or the network server, or while the machine is accessing the hard disk or memory for reading or writing data.

Service Program Tables

SP1-XXX (Bit Switches)

1	Mode	No.	Function		
	System Switch				
101	001 - 032	00 – 1F	Changes the bit switches for system settings for the fax option.		
			See section 4.2 Bit Switches		
	Ifax Switch				
102	001 – 016	00 – 0F	Changes the bit switches for internet fax settings for the fax option.		
			See section 4.2 Bit Switches		
	Printer Switch	,			
103	001 – 016	00 – 0F	Changes the bit switches for printer settings for the fax option.		
			See section 4.2 Bit Switches		
	Communication Switch				
104	001 - 032	00 – 1F	Changes the bit switches for communication settings for the fax option.		
			See section 4.2 Bit Switches		
	G3-1 Switch				
105	001 - 016	00 – 0F	Changes the bit switches for the protocol settings of the standard G3 board.		
			See section 4.2 Bit Switches		
	G3-2 Switch	•			
106	001 - 016	00 – 0F	Changes the bit switches for the protocol settings of the optional G3 board.		
			See section 4.2 Bit Switches		
107	G3-3 Switch				

1	Mode I	No.	Function	
	001 – 016	00 – 0F	Changes the bit switches for the protocol settings of the optional G3 board. See section 4.2 Bit Switches	
108	G4 Internal Switch	G4 Internal Switch		
108	001 – 032	00 – 1F	Not used (Do not change the bit switches)	
109	G4 Parameter Switch			
109	001 – 016	00 – 0F	Not used (Do not change the bit switches)	
	IP fax Switch			
111	001 – 016	00 – 0F	Changes the bit switches for optional IP fax parameters. See section 4.2 Bit Switches	

SP2-XXX (RAM Data)

2		Mode No.	Function
	RAM Read/W	′rite	
101	001		Changes RAM data for the fax board directly. See section 4.5 Service RAM Addresses.
	Memory Dump)	
	001	G3-1 Memory Dump	Prints out RAM data for the fax board. See section 4.5 Service RAM Addresses.
102	002	G3-2 Memory Dump	Prints out RAM data for the optional SG3 board.
	003	G3-3 Memory Dump	Prints out RAM data for the optional SG3 board.
	004	G4 Memory Dump	Prints out RAM data for the SiG4 board.
	G3-1 NCU Pa	rameters	
103	001 – 023	CC, 01 – 22	NCU parameter settings for the standard G3 board. See section 4.3 NCU Parameters.

2		Mode No.	Function
104	G3-2 NCU Pa	rameters	
	001 – 023	CC, 01 – 22	NCU parameter settings for the optional G3 board. See section 4.3 NCU Parameters.
	G3-3 NCU Parameters		
105	001 – 023	CC, 01 – 22	NCU parameter settings for the optional G3 board. See section 4.3 NCU Parameters.

SP3-XXX (Tel Line Settings)

3		Mode No.	Function			
	Service Station	Service Station				
101	001	Fax Number	Enter the fax number of the service station.			
	002	Select Line	Select the line type.			
102	Serial Number					
102	000		Enter the fax unit's serial number.			
	PSTN-1 Port Se	ettings				
	001	Select Line	Select the line type setting for the G3-1 line. If the machine is installed on a PABX line, select "PABX", "PABX(GND)" or "PABX(FLASH)".			
103	002	PSTN Access Number	Enter the PSTN access number for the G3-1 line.			
	003	Memory Lock Disabled	If the customer does not want to receive transmissions using Memory Lock on this line, turn this SP on.			
	PSTN-2 Port Settings					
104	001	Select Line	Select the line setting for the G3-2 line. If the machine is installed on a PABX line, select "PABX", "PABX(GND)" or "PABX(FLASH)".			
	002	PSTN Access Number	Enter the PSTN access number for the G3-2 line.			

3		Mode No.	Function
	003	Memory Lock Disabled	If the customer does not want to receive transmissions using Memory Lock on this line, change this SP to on.
	004	Transmission Disabled	If you turn this SP on, the machine does not send any fax messages on the G3-2 line.
	PSTN-3 Port Se	ettings	
	001	Select Line	Select the line setting for the G3-3 line. If the machine is installed on a PABX line, select "PABX", "PABX(GND)" or "PABX(FLASH)".
105	002	PSTN Access Number	Enter the PSTN access number for the G3-3 line.
	003	Memory Lock Disabled	If the customer does not want to receive transmissions using Memory Lock on this line, change this SP to on.
	004	Transmission Disabled	If you turn this SP on, the machine does not send any fax messages on the G3-3 line.
	ISDN Port Settings		
10/	001	Select Line	
106	002	PSTN Access Number	
	003	Memory Lock Disabled	Not used (Do not change the bit switches)
106	004	Transmission Disabled	
	IPFAX Port Setti	ngs	
	001	H323 Port	
	002	SIP Port	
107	003	RAS Port	
107	004	Gatekeeper port	
	005	T.38 Port	
	006	SIP Server Port	
	007	IPFAX Protocol Priority	Select "H323" or "SIP".

3	Mode No.		Function
201	FAX SW		
201	001 – 032	00 – 1F	

SP4-XXX (ROM Versions)

4		Mode No.	Function
101	001	FCU ROM Version	Displays the FCU ROM version.
102	001	Error Codes	Displays the latest 64 fax error codes.
103	001	G3-1 ROM Version	Displays the G3-1 modem version.
104	001	G3-2 ROM Version	Displays the G3-2 modem version.
105	001	G3-3 ROM Version	Displays the G3-3 modem version.
106	001	G4 ROM Version	Not used (Do not change the bit switches)
107	001	Charge ROM Version	Not used (Do not change the bit switches)

SP5-XXX (Initializing)

5	Mod	e No.	Function
	Initialize SRAM		
101	000		Initializes the bit switches and user parameters, user data in the SRAM, files in the SAF memory, and clock.
102	Erase All Files		
102	000		Erases all files stored in the SAF memory.
103	Reset Bit Switches		
103	000		Resets the bit switches and user parameters.
104	Factory setting		

5	Mode No.		Function
	000		Resets the bit switches and user parameters, user data in the SRAM and files in the SAF memory.
105	Initialize All Bit	Switches	
105	000		Initializes all the current bit switch settings.
	Initialize Securi	ity Bit Switches	
106	000		Initializes only the security bit switches. If you select automatic output/display for the user parameter switches, the security settings are initialized.

SP6-XXX (Reports)

6		Mode No.	Function
	System Parameter List		
101	000		Touch the "ON" button to print the system parameter list.
	Service Monitor Report		
102	000		Touch the "ON" button to print the service monitor report.
	G3 Protocol Dump List		
103	001	G3 All Communications	Prints the protocol dump list of all communications for all G3 lines.
	002	G3-1 (All Communications)	Prints the protocol dump list of all communications for the G3-1 line.
	003	G3-1 (1 Communication)	Prints the protocol dump list of the last communication for the G3-1 line.
103	004	G3-2 (All Communications)	Prints the protocol dump list of all communications for the G3-2 line.
	005	G3-2 (1 Communication)	Prints the protocol dump list of the last communication for the G3-2 line.

6		Mode No.	Function	
	006	G3-3 (All Communications)	Prints the protocol dump list of all communications for the G3-3 line.	
	007	G3-3 (1 Communication)	Prints the protocol dump list of the last communication for the G3-3 line.	
	G4 Protocol Dump List			
	001	Dch + Bch 1		
	002	Dch		
104	003	Bch 1 Link Layer		
	004	Dch Link Layer	Not used (Do not change the bit switches)	
	005	Dch +Bch 2		
	006	Bch 2 Link Layer		
	All Files print out			
			Prints out all the user files in the SAF memory, including confidential messages.	
105	000		Note: Do not use this function, unless the customer is having trouble printing confidential messages or recovering files stored using the memory lock feature.	
	Journal Print out			
106	001	All Journals	The machine prints all the communication records on the report.	
	002	Specified Date	The machine prints all communication records after the specified date.	
	Log List Print out			
	001	All log files		
107	002	Printer	These log print out functions are for designer use	
	003	SC/TRAP Stored	only.	
	004	Decompression		

6	Mode No.		Function
	005	Scanner	
	006	JOB/SAF	
	007	Reconstruction	
	008	JBIG	
	009	Fax Driver	
	010	G3CCU	
	011	Fax Job	
	012	ССИ	
	013	Scanner Condition	
	IP Protocol Dur	np List	
108	001	All Communications	Prints the protocol dump list of all communications for the IP fax line.
	002	1 Communication	Prints the protocol dump list of the last communication for the IP fax line.

SP7-XXX (Test Modes)

These are the test modes for PTT approval.

7	Function
101	G3-1 Modem Tests
102	G3-1 DTMF Tests
103	Ringer Test
104	G3-1 V34 (S2400baud)
105	G3-1 V34 (S2800baud)
106	G3-1 V34 (S3000baud)
107	G3-1 V34 (S3200baud)

7	Function
108	G3-1 V34 (S3429baud)
109	Recorded Message Test
110	G3-2 Modem Tests
111	G3-2 DTMF Tests
112	G3-2 V34 (S2400baud)
113	G3-2 V34 (S2800baud)
114	G3-2 V34 (S3000baud)
115	G3-2 V34 (S3200baud)
116	G3-2 V34 (S3429baud)
117	G3-3 Modem Tests
118	G3-3 DTMF Tests
119	G3-3 V34 (S2400baud)
120	G3-3 V34 (S2800baud)
121	G3-3 V34 (S3000baud)
122	G3-3 V34 (S3200baud)
123	G3-3 V34 (S3429baud)
124	IG3-1 Modem Tests - Not used
125	IG3-1 DTMF Tests - Not used
126	IG3-1 V34 (S2400baud) - Not used
127	IG3-1 V34 (S2800baud) - Not used
128	IG3-1 V34 (S3000baud) - Not used
129	IG3-1 V34 (S3200baud) - Not used
130	IG3-1 V34 (S3429baud) - Not used
131	IG3-2 Modem Tests - Not used
132	IG3-2 DTMF Tests - Not used

7	Function
133	IG3-2 V34 (S2400baud) - Not used
134	IG3-2 V34 (S2800baud) - Not used
135	IG3-2 V34 (S3000baud) - Not used
136	IG3-2 V34 (S3200baud) - Not used
137	IG3-2 V34 (S3429baud) - Not used

SP9-XXX (Design Switch Mode)

9	Mode No.	Function
702	Design Switch DFU	

Bit Switches

Vote

• Do not adjust a bit switch or use a setting that is described as "Not used", as this may cause the machine to malfunction or to operate in a manner that is not accepted by local regulations. Such bits are for use only in other areas, such as Japan.

Default settings for bit switches are not listed in this manual. Refer to the System Parameter List printed by the machine.

Dedicated trans	Inction	
		Comments
0 programming 0: Disabled 1: Enabled	mission parameter	Set this bit to 1 before changing any dedicated transmission parameters. Reset this bit to 0 after programming dedicated transmission parameters.
1 Not used		Do not change
Technical data p 0: Disabled 1: Enabled	rintout on the Journal	1: Instead of the personal name, the following data are listed on the Journal for each G3 communication.
 (1) (2)(3) 2 (1): EQM value (2): Symbol rate (3): Final moder (4): Starting data (5): Final data rate (6): Rx revel (set 	0000 32V34 288/264 L0100 03 04	

System Switches

	System Switch (00 (SP No. 1-101-001)
No	Function	Comments
	reception records. Rx level calculation Example: 0000 32V34 288/264 L01 (1) (2)(3) (4) (5) (6) The four-digit hexadecimal value (N)	are fixed at "00" for transmission records and ECM 00 03 04 (7) (8) after "L" indicates the rx level. y the low byte. Divide the decimal value of N by -16 to
	So, the actual rx level is 256/-16 = -	16 dB
3	Not used	Do not change this setting.
4	Line error mark print 0: OFF, 1: ON (print)	When "1" is selected, a line error mark is printed on the printout if a line error occurs during reception.
5	G3/G4 communication parameter display 0: Disabled 1: Enabled	This is a fault-finding aid. The LCD shows the key parameters (see below). This is normally disabled because it cancels the CSI display for the user. Be sure to reset this bit to 0 after testing.
6	Protocol dump list output after each communication 0: Off 1: On	This is only used for communication troubleshooting. It shows the content of the transmitted facsimile protocol signals. Always reset this bit to 0 after finishing testing. If system switch 09 bit 6 is at "1", the list is only printed if there was an error during the communication.
7	Not used	Do not change the setting.

G3 Communication Parameters

Modem rate 336: 33600 bps 168: 16800 bps
--

	212 212001 144 144001
	312: 31200 bps 144: 14400 bps
	288: 28800 bps 120: 12000 bps
	264: 26400 bps 96: 9600 bps
	240: 24000 bps 72: 7200 bps
	216: 21600 bps 48: 4800 bps
	192: 19200 bps 24: 2400 bps
	S: Standard (8 x 3.85 dots/mm)
	D: Detail (8 x 7.7 dots/mm)
	F: Fine (8 x 15.4 dots/mm)
Resolution	SF: Superfine (16 x 15.4 dots/mm)
	21: Standard (200 x 100 dpi)
	22: Detail (200 x 200 dpi)
	44: Superfine (400 x 400 dpi)
	MMR: MMR compression
	MR: MR compression
Compression mode	MH: MH compression
	JBO: JBIG compression (Optional mode)
	JBB: JBIG compression (Basic mode)
C	ECM: With ECM
Communication mode	NML: With no ECM
	A4: A4 (8.3"), no reduction
Width and reduction	B4: B4 (10.1"), no reduction
	A3: A3 (11.7"), no reduction
	0: 0 ms/line
	5: 5 ms/line
	10: 10 ms/line
	20: 20 ms/line
I/O rate	25: 2.5 ms/line
	40: 40 ms/line
	• Note
	• "40" is displayed while receiving a fax message using AI short protocol.

System Switch 01 - Not used (Do not change the factory settings.)

System Switch 02 (SP No. 1-101-003)				02 (SP No. 1-101-003)
No		F	unction	Comments
0	Not us	ed		Do not change these settings.
2	Forced reset after transmission stalls 0: Off 1: On			With this setting on, the machine resets itself automatically if a transmission stalls and fails to complete the job.
3	Not us	ed		Do not change these settings.
4]	ne User Parameter 24	1 : A file that had a communication error will not be erased unless the communication is successful.
5	Not used			Do not change this setting.
	Memory read/write by RDS		write by RDS	(0,0): All RDS systems are always locked out.
	Bit 7	Bit 6	Setting	(0, 1), (1,0): Normally, RDS systems are locked out, but the user can temporarily switch RDS on to allow RDS
	0	0 Always disabled operations	operations to take place. RDS will automatically be	
6-7	0	1	User selectable	locked out again after a certain time, which is stored in System Switch 03. Note that if an RDS operation takes
	1	0	User selectable	place, RDS will not switch off until this time limit has expired.
	1	1	Always enabled	(1,1): At any time, an RDS system can access the machine.

	System Switch 03 (SP No. 1-101-004)		
No	Function	Comments	
0 to 7	Length of time that RDS is temporarily switched on when bits 6 and 7 of System Switch 02 are set to "User selectable"	00 - 99 hours (BCD). This setting is only valid if bits 6 and 7 of System Switch 02 are set to "User selectable". The default setting is 24 hours.	

	System Switch 04 (SP No. 1-101-005)		
No	Function	Comments	
0-2	Not used	Do not change these settings.	
3	Printing dedicated tx parameters on Quick/Speed Dial Lists O: Disabled 1: Enabled	1: Each Quick/Speed dial number on the list is printed with the dedicated tx parameters (10 bytes each). The first 10 bytes of data are the programmed dedicated tx parameters; 34 bytes of data are printed (the other 24 bytes have no use for service technicians).	
4-7	Not used	Do not change these settings.	

System Switch 05 - Not used (Do not change the factory settings.)

System Switch 06 (SP No. 1-101-007)

No	Function	Comments
0 to 7	Margin setting for Create Margin Transmission	71 to 99 (BCD) %. This setting determines the reduction ratio when the user uses the Create Margin Transmission feature. Default setting: 1001 0011 (93%)

System Switch 07 - Not used (Do not change the factory settings.)

System Switch 08 - Not used (Do not change the factory settings.)

System Switch 09 (SP No. 1-101-010)

No	Function	Comments
0	Addition of image data from confidential transmissions on the transmission result report O: Disabled 1: Enabled	If this feature is enabled, the top half of the first page of confidential messages will be printed on transmission result reports.
1	Inclusion of communications on the Journal when no image data was exchanged. O: Disabled 1: Enabled	0: Communications that reached phase C (message tx/rx) of the T.30 protocol are listed on the Journal.

	System Switch 09 (SP No. 1-101-010)		
No	Function	Comments	
		1: Communications that reached phase A (call setup) of T.30 protocol are listed on the Journal. This will include telephone calls.	
2	Automatic error report printout 0: Disabled 1: Enabled	0: Error reports will not be printed. 1: Error reports will be printed automatically after failed communications.	
3	Printing of the error code on the error report 0: No 1: Yes	1: Error codes are printed on the error reports.	
4	Not used	Do not change this setting.	
5	Power failure report O: Disabled 1: Enabled	1: A power failure report will be automatically printed after the power is switched on if a fax message disappeared from the memory when the power was turned off last.	
6	Conditions for printing the protocol dump list O: Print for all communications 1: Print only when there is a communication error	This switch becomes effective only when system switch 00 bit 6 is set to 1. 1: Set this bit to 1 when you wish to print a protocol dump list only for communications with errors.	
7	Priority given to various types of remote terminal ID when printing reports O: RTI > CSI > Dial label > Tel. number 1: Dial label > Tel. number > RTI > CSI	This bit determines which set of priorities the machine uses when listing remote terminal names on reports. Dial Label: The name stored, by the user, for the Quick/ Speed Dial number.	

System Switch OA (SP No. 1-101-011)		
No	Function	Comments
0	Automatic port selection 0: Disabled, 1: Enabled	When "1" is selected, a suitable port is automatically selected if the selected port is not used.
1-2	Not used	Do not change these settings.

E.

System Switch 0A (SP No. 1-101-011)			
No	Function	Comments	
3	Continuous polling reception 0: Disabled 1: Enabled	This feature allows a series of stations to be polled in a continuous cycle. This will continue until the polling reception file is erased. The dialing interval is the same as memory transmission.	
4	Dialing on the ten-key pad when the external telephone is off-hook 0: Disabled 1: Enabled	 0: Prevents dialing from the ten-key pad while the external telephone is off-hook. Use this setting when the external telephone is not by the machine, or if a wireless telephone is connected as an external telephone. 1: The user can dial on the machine's ten-key pad when the handset is off-hook. 	
5	On hook dial 0: Disabled 1: Enabled	0: On hook dial is disabled.	
6-7	Not used	Do not change the factory settings	

System Switch OB - Not used (Do not change the factory settings.)	
System Switch OC - Not used (Do not change the factory settings.)	
System Switch OD - Not used (Do not change the factory settings.)	

System Switch OE (SP No. 1-101-015)			
No	Function	Comments	
0-1	Not used	Do not change the settings.	
2	Enable/disable for direct sending selection O: Direct sending off 1: Direct sending on	Direct sending cannot operate when the capture function is on during sending. Setting this switch to "1" enables direct sending without capture. Setting this switch to "0" masks the direct sending function on the operation panel so it cannot be selected.	
3	Action when the external handset goes off-hook 0: Manual tx and rx operation	 0: Manual tx and rx are possible while the external handset is off-hook. However, memory tx is not possible. 1: The display stays in standby mode even when the external handset is used, so that other people can use 	

	System Switch OE (SP No. 1-101-015)			
No	o Function Comments			
	1: Memory tx and rx operation (the display remains the same)	the machine for memory tx operation. Note that manual tx and rx are not possible with this setting.		
4-7	Not used	Do not change these settings.		

System Switch OF (SP No. 1-101-016)				
No	Function		Comments	
	Country/area code for functional settings (Hex)			
	00: France	11: USA		
	01: Germany	12: Asia		
	02: UK	13: Japan		
	03: Italy	14: Hong Kong		
	04: Austria	15: South Africa	This country/area code determines the factory settings of bit switches and RAM addresses.	
	05: Belgium	16: Australia	However, it has no effect on the NCU parameter settings and communication parameter RAM	
0	06: Denmark	17: New Zealand	addresses.	
to	07: Finland	18: Singapore	Cross reference	
7	08: Ireland	19: Malaysia	NCU country code: SP No. 2-103-001 for G3-1	
	09: Norway	1A: China	SP No. 2-104-001 for G3-2	
	0A: Sweden	1B: Taiwan	SP No. 2-105-001 for G3-3	
	OB: Switz.	1C: Korea		
	OC: Portugal	20: Turkey		
	0D: Holland	21: Greece		
	OE: Spain	22: Hungary		
	OF: Israel	23: Czech		
	10: 24: Poland			

System Switch 10 (SP No. 1-101-017)				
No	Function	Comments		
0-7	Threshold memory level for parallel memory transmission	Threshold = N x 128 KB + 256 KB N can be between 00 - FF(H) Default setting: 02(H) = 512 KB		

System Switch 11 (SP No. 1-101-018)				
No	Function	Comments		
0	TTI printing position O: Superimposed on the page data 1: Printed before the data leading edge	Change this bit to 1 if the TTI overprints information that the customer considers to be important (G3 transmissions).		
1	TSI (G3) printing position O: Superimposed on the page data 1: Printed before the data leading edge	Change this bit to 1 if the TSI (G3) overprints information that the customer considers to be important.		
2	Not used	Do not change the factory settings.		
3	TTI used for broadcasting O: The TTIs selected for each Quick/ Speed dial are used 1: The same TTI is used for all destinations	1: The TTI (TTI_1 or TTI_2) which is selected for all destinations during broadcasting.		
4-7	Not used	Do not change the factory settings.		

System Switch 12 (SP No. 1-101-019)				
No	Function	Comments		
0-7	TTI printing position in the main scan direction	TTI: 08 to 92 (BCD) mm Input even numbers only. This setting determines the print start position for the TTI from the left edge of the paper. If the TTI is moved too far to the right, it may overwrite the file number which is on the top right of the page. On an A4 page, if the TTI		

System Switch 12 (SP No. 1-101-019)		
No Function Comments		Comments
		is moved over by more than 50 mm, it may overwrite the page number.

System Switch 13 - Not used (do not change these settings)

System Switch 14 - Not used (do not change these settings)

			System Switch 1	15 (SP No. 1-101-022)
No	Function			Comments
0	Not us	ed		Do not change the settings.
1	Going into the Energy Saver mode automatically O: Enabled 1: Disabled			1 : The machine will restart from the Energy Saver mode quickly, because the +5V power supply is active even in the Energy Saver mode.
2-3	Not used			Do not change these settings.
	Interval for preventing the machine from entering Energy Saver mode if there is a pending transmission file.		nergy Saver mode if	If there is a file waiting for transmission, the machine
	Bit 5	Bit 4	Setting	does not go to Energy Saver mode during the selected
4-5	0	0	1 min	period. After transmitting the file, if there is no file waiting for
	0	1	30 min	transmission, the machine goes to the Energy Saver mode.
	1	0	1 hour	mode.
	1	1	24 hours	
6-7	Not used		·	Do not change

System Switch 16 (SP No. 1-101-023)				
No	Function	Comments		
0	Parallel Broadcasting O: Disabled	1: The machine sends messages simultaneously using all available ports during broadcasting.		

System Switch 16 (SP No. 1-101-023)				
No	Function	Comments		
	1: Enabled			
1	Priority setting for the G3 line. 0: PSTN-1 > PSTN-2 or 3 1: PSTN-2 or 3 > PSTN-1	This function allows the user to select the default G3 line type. The optional SG3 units are required to use the PSTN-2 or 3 setting.		
2-7	Not used	Do not change these settings.		

System Switch 17 - Not used (do not change these settings)

System Switch 18 - Not used (do not change these settings)

System Switch 19 (SP No. 1-101-026) Function No Comments 0-5 Not used Do not change the settings. 0: After installing the memory expansion option, the Extended scanner page memory after scanner page memory is extended to 4 MB from 2 MB. memory option is installed 1: If this bit is set to 1 after installing the memory 6 0: Disabled expansion option, the scanner page memory is extended to 12 MB. But the SAF memory decreases to 1: Enabled 18 MB. 1: If the customer frequently wishes to transmit a form or Special Original mode letterhead which has a colored or printed background, 7 change this bit to "1". "Original 1" and "Original 2" can 0: Disabled be selected in addition to the "Text", "Text/Photo" and 1: Enabled "Photo" modes.

System Switch 1A (SP No. 1-101-027)				
No	Function	Comments		
0 to 7	LS RX memory capacity threshold setting 00-FF (0-1020 Kbyte: Hex)	Sets the value to x4KB. When the amount of available memory drops below this setting, RX documents are printed to conserve memory. Initial setting 0x80 (512 KB)		

System Switch 1B - Not used (do not change these settings)

System Switch 1C - Not used (do not change these settings)

System Switch 1D (SP No. 1-101-030)				
No	Function	Comments		
0	RTI/CSI/CPS code display O: Enable 1: Disable	0: RTI, CSI, CPS codes are displayed on the top line of the LCD panel during communication. 1: Codes are switched off (no display)		
1	Not used	Do not change this setting.		
2	Destination telephone number display limitation 0: OFF, 1: ON	When "1" is selected, the destination telephone number display is limited and redial is disabled.		
3-7	Not used	Do not change these settings.		

	System Switch 1E (SP No. 1-101-031)				
No	Function	Comments			
0	Communication after the Journal data storage area has become full O: Impossible 1: Possible	 0: When this switch is on and the journal history becomes full, the next report prints. If the journal history is not deleted, the next transmission cannot be received. This prevents overwriting communication records before the machine can print them. 1: If the buffer memory of the communication records for the Journal is full, fax communications are still possible. But the machine will overwrite the oldest communication records. Note This setting is effective only when Automatic Journal printout is enabled but the machine cannot print the report (e.g., no paper). 			
1	Action when the SAF memory has become full during scanning 0: The current page is erased.	0: If the SAF memory becomes full during scanning, the successfully scanned pages are transmitted.			
	1: The entire file is erased.	1: If the SAF memory becomes full during scanning, the file is erased and no pages are transmitted.			

System Switch 1E (SP No. 1-101-031)		
No	Function	Comments
		 Note This setting is effective only when Automatic Journal printout is enabled but the machine cannot print the report (e.g., no paper).
2	RTI/CSI display priority 0: RTI 1: CSI	This bit determines which identifier, RTI or CSI, is displayed on the LCD while the machine is communicating in G3 non-standard mode.
3	File No. printing O: Enabled 1: Disabled	1: File numbers are not printed on any reports.
4	Action when authorized reception is enabled but authorized RTIs/CSIs are not yet programmed O: All fax reception is disabled 1: Faxes can be received if the sender has an RTI or CSI	If authorized reception is enabled but the user has stored no acceptable sender RTIs or CSIs, the machine will not be able to receive any fax messages. If the customer wishes to receive messages from any sender that includes an RTI or CSI, and to block messages from senders that do not include an RTI or CSI, change this bit to "1", then enable Authorized Reception. Otherwise, keep this bit at "0 (default setting)".
5-7	Not used	Do not change the settings

System Switch 1F (SP No. 1-101-032)		
No	Function	Comments
0	Not used	Do not change the settings.
1	Report printout after an original jam during SAF storage or if the SAF memory fills up O: Enabled 1: Disabled	0: When an original jams, or the SAF memory overflows during scanning, a report will be printed. Change this bit to "1" if the customer does not want to have a report in these cases. Memory tx – Memory storage report Parallel memory tx – Transmission result report
2	Not used	Do not change the settings.

	System Switch 1F (SP No. 1-101-032)		
No	Function	Comments	
3	Received fax print start timing (G3 reception) 0: After receiving each page 1: After receiving all pages	0: The machine prints each page immediately after the machine receives it.1: The machine prints the complete message after the machine receives all the pages in the memory.	
4-6	Not used	Do not change the factory settings.	
7	Action when a fax SC has occurred 0: Automatic reset 1: Fax unit stops	 0: When the fax unit detects a fax SC code other than SC1201 and SC1207, the fax unit automatically resets itself. 1: When the fax unit detects any fax SC code, the fax unit stops. Cross Reference Fax SC codes - See "Troubleshooting" 	

I-Fax Switches

	I-fax Switch 00 (SP No. 1-102-001)		
No	Function	Comments	
Origino	al Width of TX Attachment File	This setting sets the maximum size of the original that the destination can receive. (Bits 3~7 are reserved for future use or not used.)	
0	A4	0: Off (not selected), 1: On (selected)	
1	B4	If more than one of these three bits is set to "1", the larger size has priority. For example, if both Bit 2 and Bit 1 are	
2	A3	set to "1" then the maximum size is "A3" (Bit 2).	
3-6	Reserved	When mail is sent, there is no negotiation with the receiving machine at the destination, so the sending	
7	Not used	machine cannot make a selection for the receiving capabilities (original width setting) of the receiving machine. The original width selected with this switch used as the RX machine's original width setting, and th original is reduced to this size before sending. The default is A4.	

I-fax Switch 00 (SP No. 1-102-001)		
No Function Comments		Comments
		If the width selected with this switch is higher than the receiving machine can accept, the machine detects this and this causes an error.

I-fax Switch 01 (SP No. 1-102-002)		
No	Function	Comments
Original Line Resolution of TX Attachment File		These settings set the maximum resolution of the original that the destination can receive.
0	200x100 Standard	
1	200x200 Detail	0: Not selected
2	200x400 Fine	1: Selected
3	300 x 300 Reserve	If more than one of these three bits is set to "1", the higher
4	400 x 400 Super Fine	resolution has priority. For example, if both Bit 0 and Bit 2 are set to "1" Then The Resolution is set for "Bit 2 200
5	600 x 600 Reserve	x 400.
6	Reserve	
7	mm/inch	
	 This setting selects mm/inch conversion for mail transmission. O: Off (No conversion), 1: On (Conversion) When on (set to "1"), the machine converts millimeters to inches for sending mail. There is no switch for converting inches to millimeters. Unlike G3 fax transmissions which can negotiate between sender and receiver to determine the setting, mail cannot negotiate between terminals; the mm/inch selection is determined by the sender fax. When this switch is Off (0): Images scanned in inches are sent in inches. Images received in inches are transmitted in inches. Images received in mm are transmitted in mm. 	

I-fax Switch 01 (SP No. 1-102-002)		
No	Function Comments	
	Images scanned in inches are sent in inches.	
	Images scanned in mm are converted to inches.	
	• Images received in inches are transmitted in inches.	
	Images received in mm are converted to inches.	

I-fax Switch 02 (SP No. 1-102-003)		
No	Function	Comments
	RX Text Mail Header Processing	
	This setting determines whether the hec received.	ader information is printed with text e-mails when they are
	0: Prints only text mail.	
0	1: Prints mail header information attac	hed to text mail.
	When a text mail is received with this s are printed as header information.	switch On (1), the "From" address and "Subject" address
When a mail with only binary data is received (a TIFF-F file, for example), this se and no header is printed.		eceived (a TIFF-F file, for example), this setting is ignored
	Output from Attached Document at E-mail TX Error	
1	This setting determines whether only the first page or all pages of an e-mail attachment are printed at the sending station when a transmission error occurs. This allows the customer to see which documents have not reached their intended destinations if sent to the wrong e-mail addresses, for example.	
	0: Prints 1st page only.	
	1: Prints all pages.	
	Text String for Return Receipt	
	This setting determines the text string output for the Return Receipt that confirms the transmission was received normally at the destination.	
2-3	00: "Dispatched"	
	Sends from PC mail a request for a Retu in the 2nd part:	urn Receipt. Receives the Return Receipt with "dispatched"
Disposition: Automatic-action/MDN-send automatically; dispatched		end automatically; dispatched

I-fax Switch 02 (SP No. 1-102-003)			
No	Function	Comments	
	The "dispatched" string is included in t	he Subject string.	
	01: "Displayed" Sends from PC mail a request for a Return Receipt. Receives the Return Receipt with "displayed" in the 2nd part:		
	Disposition: Automatic-action/MDN-s	send automatically; displayed	
	The "displayed" string is included in th	e Subject string.	
	10: Reserved		
	11: Reserved		
	A mail requesting a Return Receipt sent from an IFAX with this switch set to "00" (for "dispatched") received by Microsoft Outlook 2000 may cause an error. If any setting other than "displayed" (01) causes a problem, change the setting to "01" to enable normal sending of the Return Receipt.		
	Media accept feature		
	This setting adds or does not add the media accept feature to the answer mail to confirm a reception.		
4	0: Does not add the media accept fea	ture to the answer mail	
	1: Adds the media accept feature to the	ne answer mail.	
	Use this bit switch if a problem occurs when the machine receives an answer mail, which contains the media accept feature field.		
5-6	Not Used		
	Image Resolution of RX Text Mail		
	This setting determines the image reso	lution of the received mail.	
7	0: 200 x 200		
	1: 400 x 400		
	The "1" setting requires installation of t (Store and Forward) memory to receiv	he Function Upgrade Card in order to have enough SAF /e images at 400 x 400 resolution.	

	I-fax Switch 03 (SP No. 1-102-004)		
No	No Function Comments		
0	0 Original Output at Transfer Station		

I-fax Switch 03 (SP No. 1-102-004)		
No	Function	Comments
	This setting determines whether the original is output at the transfer station when it is received from the sender that initiated the transfer transmission. This feature is the same as for G3 transfer transmissions.	
	0: Received original not output at the t	transfer station.
	1: Received original output. The original is printed after the transfer station has transferred it to the destinations, so its output confirms that the original has been transferred.	
	Transfer Result Report	
1	This setting determines when a Transfe requestor.	er Result Report is generated and returned to the transfer
	0: Returns the report after each transfe	er.
	1: Returns the report only if an error occurred during transfer.	
	Destination Error Handling for Reception Transfer Request	
	This setting restricts transfer transmission based on whether the final destinations are correct or not.	
	0: The transfer station transmits to corr	ect destinations only (addresses with no errors in them).
2	1: If any address has an error in it, the transfer transmission failure report to the	e transfer station transfers no transmissions and returns a he requestor that initiated the transfer.
	the final destination addresses are cor	nsfer initiator and the transfer station to determine whether rect or not. This setting determines whether or not the ons if there is a mistake in even one of the final destination
	Polling ID Check for Reception of Tran	nsfer Request
3	This setting determines whether the pol that the polling IDs match.	lling IDs of incoming transmissions are checked to ensure
	0: Receives and transfers only messag	es that have matching polling IDs.
	1: Receives and transfers all messages	s, even if the polling IDs do not match.
4-7	Not Used	

I-fax Switch 04 (SP No. 1-102-005)		
No	Function	Comments
	Subject for Delivery TX/Memory Tran	sfer
0	This setting determines whether the RTI originator is used in the subject lines o	/CSI registered on this machine or the RTI/CSI of the ftransferred documents.
	0: Puts the RTI/CSI of the originator in t Only one of these can be received for	he Subject line. If this is used, either the RTI or CSI is used. use in the subject line.
	1: Puts the RTI/CSI registered on this r	nachine in the Subject line.
		d deliver mail to a PC, the information in the Subject line originated can be used to determine automatically the
	Subject corresponding to mail post da	tabase
	0: Standard subject	
	1: Mail post database subject	
	The standard subject is replaced by the	e mail post database subject in the following three cases:
	1) When the service technician sets the	e service (software) switch.
1	2) When memory sending or delivery	specified by F code is applied by the SMTP server
	3) With relay broadcasting (1st stage	without the Schmidt 4 function).
	↓ Note	
	,	dition 3) when the RX system is set up for memory sending, SMTP RX and when operators are using FOL (to prevent ssions).
2-7	Not Used	

I-fax Switch 05 (SP No. 1-102-006)				
No	Function Comments			
	Mail Addresses of SMTP Broadcast Recipients			
0	Determines whether the e-mail addresses of the destinations that receive transmissions broadcasted using SMTP protocol are recorded in the Journal.			
	For example:			
	"1st destination + Total number of destinations: 9" in the Journal indicates a broadcast to 9 destinations.			

I-fax Switch 05 (SP No. 1-102-006)				
No	Function Comments			
	0: Not recorded			
	1: Recorded			
1-7	Not Used			

I-fax Switch 06 - Not used (do not change the settings)

I-fax Switch 07 - Not used (do not change the settings)

I-fax Switch 08 (SP No. 1-102-009)				
No	Function Comments			
	Memory Threshold for POP Mail Reception			
0-7	This setting determines the amount of SAF (Store and Forward) memory. (SAF stores fax messages to send later for transmission to more than one location, and also holds incoming messages if they cannot be printed.) When the amount of SAF memory available falls below this setting, mail can no longer be received; received mail is then stored on the mail server.			
	00-FF (0 to 1024 KB: HEX)			
The hexadecimal number you enter is multiplied by 4 KB to determine the amount of		is multiplied by 4 KB to determine the amount of memory.		

I-fax Switch 09 (SP No. 1-102-010)		
No	Function	Comments
0-3	Not used	Do not change the settings
4-7	Restrict TX Retries	This setting determines the number of retries when connection and transmission fails due to errors. 01-F (1-15 Hex)

I-fax Switch OA - Not used (do not change the settings)	
I-fax Switch OB - Not used (do not change the settings)	
I-fax Switch OC - Not used (do not change the settings)	
I-fax Switch OD - Not used (do not change the settings)	

I-fax Switch OE - Not used (do not change the settings)

I-fax Switch OF (SP No. 1-102-016)				
No	Function	Comments		
	Delivery Method for SMTP RX Files			
0	This setting determines whether files received with SMTP protocol are delivered or output immediately.			
	0: Off. Files received via SMTP are output immediately without delivery.			
	1: On. Files received via SMTP are delivered immediately to their destinations.			
1-7	Not used			

Printer Switches

Printer Switch 00 (SP No. 1-103-001)		
No	Function	Comments
0		O: If a 2 page RX transmission is split, [*] is printed in the bottom right corner of the 1st page and only a [2] is printed in the upper right corner of the 2nd page.
	Select page separation marks 0: Off 1: On	1: If a 2 page RX transmission is split into two pages, for example, [*] [2] is printed in the bottom right corner of the 1st page and only a [2] is printed in the upper right corner of the 2nd page.
		♦ Note
		• This helps the user to identify pages that have been split because the size of the paper is smaller than the size of the document received. (When A5 is used to print an A4 size document, for example.)
1	Repetition of data when the received page is longer than the printer paper 0: Off	 Default. 10 mm of the trailing edge of the previous page are repeated at the top of the next page. The next page continues from where the previous page stopped without any repeated text.
	1: On	, ,

Printer Switch 00 (SP No. 1-103-001)			
No	Function	Comments	
2	Prints the date and time on received fax messages O: Disabled 1: Enabled	 This switch is only effective when user parameter 02 - bit 2 (printing the received date and time on received fax messages) is enabled. 1: The machine prints the received and printed date and time at the bottom of each received page. 	
3-7	Not used	Do not change the settings.	

			Printer Switch (01 (SP No. 1-103-002)
No	Function			Comments
0-2	Not used			Do not change the settings.
	Maximum print width used in the setup protocol			
	Bit 4	Bit 3	Setting	
3-4	0	0	Not used	These bits are only effective when bit 7 of printer switch
	0	1	A3	O1 is "1".
	1	0	B4	
	1	1	A4	
5-6	Not used	Not used		Do not change the settings.
	Received	message w	ridth restriction in	O: The machine informs the transmitting machine of the print width depending on the paper size available from the paper feed stations.
7	the protocol signal to the sender 0: Disabled			Refer to the table on the next page for how the machine chooses the paper width used in the setup protocol (NSF/DIS).
	1: Enabled			1: The machine informs the transmitting machine of the fixed paper width which is specified by bits 3 and 4 above.

Relationship between available paper sizes and printer width used in the setup protocol

Available Paper Size	Printer width used in the Protocol (NSF/DIS)
A4 or 8.5" x 11"	297 mm width
В5	256 mm width
A5 or 8.5" x 5.5"	216 mm width
No paper available (Paper end)	216 mm width

	Printer Switch 02 (SP No. 1-103-003)				
No	Function	Comments			
0	1 st paper feed station usage for fax printing 0: Enabled 1: Disabled				
1	2nd paper feed station usage for fax printing O: Enabled 1: Disabled	0: The paper feed station can be used to print fax messages and reports.			
2	3rd paper feed station usage for fax printing 0: Enabled 1: Disabled	 1: The specified paper feed station will not be used for printing fax messages and reports. Note Do not disable usage for a paper feed station which has been specified by User Parameter 			
3	4th paper feed station usage for fax printing 0: Enabled 1: Disabled	Switch OF (15), or which is used for the Specified Cassette Selection feature.			
4	LCT usage for fax printing O: Enabled 1: Disabled				
5-7	Not used	Do not change the settings.			

Printer Switch 03 (SP No. 1-103-004)		
No	Function	Comments
0	Length reduction of received data O: Disabled 1: Enabled	 0: Incoming pages are printed without length reduction. (Page separation threshold: Printer Switch 03, bits 4 to 7) 1: Incoming page length is reduced when printing. (Maximum reducible length: Printer Switches 04, bits 0 to 4)
1-3	Not used	Do not change the settings
4 to 7	Page separation setting when sub scan compression is forbidden 00-0F (0-15 mm: Hex) Default: 6 mm	Page separation threshold (with reduction disabled with switch 03-0 above). For example, if this setting is set to "10", and A4 is the selected paper size: If the received document is 10 mm or less longer than A4, then the 10 mm are cut and only 1 page prints. If the received document is 10 mm longer than A4, then the document is split into 2 pages.

	Printer Switch 04 (SP No. 1-103-005)						
No	Function				С	omments	
	Maximum reducible length when length reduction is enabled with switch 03-0 above. [Maximum reducible length] = [Paper length] + (N x 5mm) "N" is the decimal value of the binary setting of bits 0 to 4.						
	Bit 4	Bit 3	Bit 2		Bit 1	Bit O	Setting
0	0	0	0		0	0	0 mm
to 4	0 0 0 1	1	5 mm				
	0	0	1		0	0	20 mm
	1	1	1		1	1	155 mm
		ys and B5 sidew ucible length] =	,		0.75 x (N x 5n	nm)	

Printer Switch 04 (SP No. 1-103-005)					
No	Function		C	omments	
	Length of the duplicated image	eparation has taken place.			
	Bit 6		Bit 5	Setting	
5	0		0	4 mm	
6	0		1	10 mm	
	1		0	15 mm	
	1		1	Not used	
7	Not used.		Do not change the setting.		

Printer Switch 05 - Not used (do not change the settings)

	Printer Switch 06 (SP No. 1-103-007)				
No	Function	Comments			
	Printing while a paper cassette is pulled out, when the Just Size Printing feature is enabled.				
0	O: Printing will not start 1: Printing will start if another cassette has a suitable size of paper, based on the paper size selection priority tables.	Cross reference Just size printing on/off – User switch 05, bit 5			
1-7	Not used.	Do not change the settings.			

Printer Switch 07 (SP No. 1-103-008)				
No	Function	Comments		
0	Reduction for Journal printing 0: Off 1: On	1: The Journal is reduced to 91% to ensure that there is enough space in the left margin for punch holes or staples.		
2-3	Not used.	Do not change the settings.		

	Printer Switch 07 (SP No. 1-103-008)				
No	Function	Comments			
4	List of destinations in the Communication Failure Report for broadcasting 0: All destinations 1: Only destinations where communication failure occurred	1: Only destinations where communication failure occurred are printed on the Communication Failure Report.			
5-7	Not used.	Do not change the settings.			

Printer Switch 08 - Not used (do not change the settings)
Printer Switch 09 - Not used (do not change the settings)
Printer Switch OA - Not used (do not change the settings)
Printer Switch OB - Not used (do not change the settings)
Printer Switch OC - Not used (do not change the settings)
Printer Switch OD - Not used (do not change the settings)

	Printer Switch OE (SP No. 1-103-015)				
No	Function	Comments			
0	Paper size selection priority O: Width 1: Length	0: A paper size that has the same width as the received data is selected first.1: A paper size which has enough length to print all the received lines without reduction is selected first.			
1	Paper size selected for printing A4 width fax data 0: 8.5" x 1 1" size 1: A4 size	This switch determines which paper size is selected for printing A4 width fax data, when the machine has both A4 and 8.5" x 11" size paper.			
2	Page separation O: Enabled 1: Disabled	1: If all paper sizes in the machine require page separation to print a received fax message, the machine does not print the message (Substitute Reception is used).			

			Printer Switch OE (SP No. 1	1-103-015)
No	Function			Comments
				After a larger size of paper is set in a cassette, the machine automatically prints the fax message.
	Printing	the sampl	e image on reports	
	Bit 4	Bit 3	Setting	"Same size" means the sample image is printed at 100%, even if page separation
	0	0	The upper half only	occurs.
3-4	0	1	50% reduction (sub-scan only)	User Parameter Switch 19 (13H) bit 4 must be set to "0" to enable this switch.
	1	0	Same size	Refer to Detailed Section Descriptions for more on this feature.
	1	1	Not used	
5-6	Not use	d		Do not change the settings.
	Equalizing the reduction ratio among separated pages			0: When page separation has taken place, all the pages are reduced with the same reduction ratio.
7	(Page Separation) O: Enabled 1: Disabled)	1: Only the last page is reduced to fit the selected paper size when page separation has taken place. Other pages are printed without reduction.

	Printer Switch OF (SP No. 1-103-016)						
No		Function		Comments			
	Smoothing feature						
	Bit 1	Bit O	Setting				
0.1	0	0	Disabled	(0, 0) (0, 1): Disable smoothing if the machine			
0-1	0	1	Disabled	receives halftone images from other manufacturers fax machines frequently.			
	1	0	Enabled				
	1	1	Not used				

	Printer Switch OF (SP No. 1-103-016)				
No	Function	Comments			
2	Duplex printing O: Disabled 1: Enabled	1: The machine always prints received fax messages in duplex printing mode:			
3	Binding direction for Duplex printing O: Left binding 1: Top binding	0: Sets the binding for the left edge of the stack. 1: Sets the binding for the top of the stack.			
4-7	Not used	Do not change the settings.			

Communication Switches

	Communication Switch 00 (SP No. 1-104-001)						
No	Function			Comments			
	Compress	ion modes av	vailable in receive mode				
	Bit 1	Bit O	Modes				
0-1	0	0	MH only	These bits determine the compression			
0-1	0	1	MH/MR	 capabilities to be declared in phase B (handshaking) of the T.30 protocol. 			
	1	0	MH/MR/MMR				
	1	1	MH/MR/MMR/JBIG				
	Compression modes available in transmit mode						
	Bit 3	Bit 2	Modes				
2-3	0	0	MH only	These bits determine the compression capabilities to be used in the transmission			
2-3	0	1	MH/MR	and to be declared in phase B (handshaking) of the T.30 protocol.			
	1	0	MH/MR/MMR				
	1	1	MH/MR/MMR/JBIG				
4	Not used			Do not change the settings.			

Communication Switch 00 (SP No. 1-104-001)				
No	Function	Comments		
5	JBIG compression method: Reception 0: Only basic supported 1: Basic and optional both supported	Change the setting when communication problems occur using JBIG compression.		
6	JBIG compression method: Transmission 0: Basic mode priority 1: Optional mode priority	Change the setting when communication problems occur using JBIG compression.		
7	Closed network (reception) 0: Disabled 1: Enabled	1: Reception will not go ahead if the polling ID code of the remote terminal does not match the polling ID code of the local terminal. This function is only available in NSF/NSS mode.		

	Communication Switch 01 (SP No. 1-104-002)				
No		Function			Comments
0	ECM 0: Off 1: On		If this bit is set to 0, ECM is switched off for all communications. In addition, V.8 protocol and JBIG compression are switched off automatically.		
1	Not used		Do not ch	ange the setting.	
	Wrong connection prevention method			(0, 1): The machine will disconnect the line without sending a fax message, if the last 8 digits of the received	
	Bit 3	Bit 2	Setting	 CSI do not match the last 8 digits of the dialed teleph number. This does not work when manually dialed (1,0): The same as above, except that only the las digits are compared. (1,1): The machine will disconnect the line without sending a fax message, if the other end does not ide 	č
	0	0	None		
2-3	0	1	8 digit CSI		·
	1	0	4 digit CSI		fax message, if the other end does not identify
	1 1 CSI/RTI		 itself with an RTI or CSI. (0,0): Nothing is checked; transmission will always grahead. 		

	Communication Switch 01 (SP No. 1-104-002)					
No		Function			Comments	
				 Note This function does not work when dialing is done from the external telephone. 		
4-5	Not use	d		Do not ch	ange the setting.	
	Maximum printable page length available					
	Bit 7	Bit 6	Setting	The setting determined by these bits is informed transmitting terminal in the pre-message protoco		
6-7	0	0	No limit			
	0	1	B4 (364 mm)	exchange	(in the DIS/NSF frames).	
	1	0	A4 (297 mm)			
	1	1	Not used			

Communication Switch 02 (SP No. 1-104-003)				
No	Function		Comments	
	G3 Burst error threshold	If there are more consecutive error lines in the received page than the threshold, the machine will send a negative response. The Low and High threshold values depend on the sub-scan resolution, and are as follows.		
0	0: Low 1: High	100 dpi	$6(L) \rightarrow 12(H)$	
		200 dpi	$12(L) \rightarrow 24(H)$	
		300 dpi	$18(L) \rightarrow 36(H)$	
		400 dpi	$24(L) \rightarrow 48(H)$	
1	Acceptable total error line ratio 0: 5% 1: 10%		e ratio for a page exceeds the atio, RTN will be sent to the other end.	
2	Treatment of pages received with errors during G3 reception 0: Deleted from memory without printing	0: Pages rece	eived with errors are not printed.	

	Communication Switch 02 (SP No. 1-104-003)			
No	Function	Comments		
	1: Printed			
3	Hang-up decision when a negative code (RTN or PIN) is received during G3 immediate transmission 0: No hang-up, 1: Hang-up	 0: The next page will be sent even if RTN or PIN is received. 1: The machine will send DCN and hang up if it receives RTN or PIN. This bit is ignored for memory transmissions or if ECM is being used. 		
4-7	Not used	Do not change the settings.		

Communication Switch 03 (SP No. 1-104-004)				
No	Function	Comments		
0-7	Maximum number of page retransmissions in a G3 memory transmission	00 - FF (Hex) times. This setting is not used if ECM is switched on. Default setting - 03(H)		

Communication Switch 04 - Not used (do not change the settings)		
Communication Switch 05 - Not used (do not change the settings)		
Communication Switch 06 - Not used (do not change the settings)		
Communication Switch 07 - Not used (do not change the settings)		
Communication Switch 08 - Not used (do not change the settings)		
Communication Switch 09 - Not used (do not change the settings)		

Communication	Switch	0A (S	P No.	1-104-0	11)
---------------	--------	-------	-------	---------	-----

No	Function	Comments	
0	Point of resumption of memory transmission upon redialing O: From the error page	0: The transmission begins from the page where transmission failed the previous time. 1: Transmission begins from the first page, using normal	
	1: From page 1	memory transmission.	

Communication Switch OA (SP No. 1-104-011)				
No	Function	Comments		
1-7	Not used	Do not change the settings.		

	Communication Switch OB (SP No. 1-104-012)			
No	Function	Comments		
0	Use of Economy Transmission during a Transfer operation to end receivers 0: Disabled, 1: Enabled	These bits determine whether the machine uses the Economy Transmission feature when it is carrying out a Transfer operation as a Transfer Station.		
1	Use of Economy Transmission during a Transfer operation to the Next Transfer Stations O: Disabled, 1: Enabled			
2	Use of Label Insertion for the End Receivers in a Transfer operation O: Disabled, 1: Enabled	This bit determines whether the machine uses the Label Insertion feature when it is carrying out a Transfer operation as a Transfer Station.		
3	Conditions required for Transfer Result Report transmission O: Always transmitted 1: Only transmitted if there was an error	 0: When acting as a Transfer Station, the machine will always send a Transfer Result Report back to the Requesting Station after completing the Transfer Request, even if there were no problems. 1: The machine will only send back a Transfer Result Report if there were errors during communication, meaning one or more of the End Receivers could not be contacted. 		
4	Printout of the message when acting as a Transfer Station O: Disabled, 1: Enabled	When the machine is acting as a Transfer Station, this bit determines whether the machine prints the fax message coming in from the Requesting Terminal.		
5	Action when there is no fax number in the programmed Quick/Speed dials which meets the requesting terminal's own fax number O: Transfer is disabled 1: Transfer is enabled	After the machine receives a transfer request, the machine compares the last N digits of the requesting terminal's own fax number with all the Quick/Speed dials programmed in the machine. (N is the number programmed in communication switch OC.) O: If there is no matching number programmed in the machine, the machine rejects the transfer request.		

	Communication Switch OB (SP No. 1-104-012)			
No	Function	Comments		
		1: Even if there is no matching number programmed in the machine, the machine accepts the transfer request. The result report will be printed at the transfer terminal, but will not be sent back to the requesting terminal.		
6-7	Not used	Do not change the settings.		

	Communication Switch OC (SP No. 1-104-013)			
No	Function	Comments		
0-4	Number of digits compared to find the requester's fax number from the programmed Quick/Speed Dials when acting as a Transfer Station	 00 – 1F (0 to 31 digits) After the machine receives a transfer request, the machine compares the own telephone number sent from the Requesting Terminal with all Quick/Speed Dials programmed in the machine, starting from Quick Dial 01 to the end of the Speed Dials. This number determines how many digits from the end of the telephone numbers the machine compares. If it is set to 00, the machine will send the report to the first Quick/Speed Dial that the machine compared. If Quick Dial 01 is programmed, the machine will send the report to Quick 01. If Quick Dial 01 through 04 are not programmed and Quick Dial 05 is programmed, the machine will send the report to Quick 05. Default setting – 05(H) = 5 digits 		
5-7	Not used	Do not change the settings.		

Communication Switch 0D (SP No. 1-104-014)			
No	Function	Comments	
0-7	The available memory threshold, below which ringing detection (and therefore reception into memory) is disabled	00 to FF (Hex), unit = 4 kbytes (e.g., 06(H) = 24 kbytes) One page is about 24 kbytes.	

Communication Switch 0D (SP No. 1-104-014)		
No	Function	Comments
		The machine refers to this setting before each fax reception. If the amount of remaining memory is below this threshold, the machine cannot receive any fax messages.
		If this setting is kept at 0, the machine will detect ringing signals and go into receive mode even if there is no memory available. This will result in communication failure.

Communication Switch OE (SP No. 1-104-015)			
No	Function	Comments	
0-7	Minimum interval between automatic dialing attempts	O6 to FF (Hex), unit = 2 s (e.g., O6(H) = 12 s) This value is the minimum time that the machine waits before it dials the next destination.	

Communication Switch OF – Not used (do not change the settings.)

Communication Switch 10 (SP No. 1-104-017)			
No	Function	Comments	
0-7	Memory transmission: Maximum number of dialing attempts to the same destination	01 – FE (Hex) times	

Communication Switch 11 – Not used (do not change the settings.)

Communication Switch 12 (SP No. 1-104-019)			
No	Function	Comments	
0-7	Memory transmission: Interval between dialing attempts to the same destination	01 – FF (Hex) minutes	

Communication Switch 13 – Not used (do not change the settings.)

Communication Switch 14 (SP No. 1-104-021)				
No		Fu	nction	Comments
0	Inch-to-mm conversion during transmission O: Disabled, 1: Enabled			 0: In immediate transmission, data scanned in inch format are transmitted without conversion. In memory transmission, data stored in the SAF memory in mm format are transmitted without conversion.
				Note: When storing the scanned data into SAF memory, the fax unit always converts the data into mm format.
				1: The machine converts the scanned data or stored data in the SAF memory to the format which was specified in the set-up protocol (DIS/ NSF) before transmission.
1-5	Not used			Do not change the factory settings.
	Available unit of resolution in which fax messages are received			
	Bit 7	Bit 6	Unit	For the best performance, do not change the
6-7	0	0	mm	factory settings. The setting determined by these bits is informed
	0	1	inch	to the transmitting terminal in the pre-message protocol exchange (in the DIS/NSF frames).
	1	0	mm and inch	protocor exchange (in the Dis/ Nor trames).
	1	1 1 Not used		

 $\label{eq:communication} \begin{array}{l} \textbf{Communication Switch 15} - \textbf{Not used} \ (do \ not \ change \ the \ settings) \end{array}$

Communication Switch 16 (SP No. 1-104-023)			
No	Function	Comments	
0	Not used	Do not change the settings.	
1	Optional G3 unit (G3-2) 0: Not installed 1: Installed	Change this bit to 1 when installing the first optional G3 unit.	

Communication Switch 16 (SP No. 1-104-023)			
No	Function	Comments	
2	Not used		
3	Select PSTN connection 0: Off 1: On	 This switch enables the G3-2. O: Off, no connection 1: Recognizes and enables G3-2. This switch can be used only after G3-2 has been installed. 	
4-7	Not used	Do not change the settings.	

Communication Switch 17 (SP No. 1-104-024)			
No	Function	Comments	
0	SEP reception O: Disabled 1: Enabled	O: Polling transmission to another maker's machine using the SEP (Selective Polling) signal is disabled.	
1	SUB reception O: Disabled 1: Enabled	0: Confidential reception to another maker's machine using the SUB (Sub-address) signal is disabled.	
2	PWD reception O: Disabled 1: Enabled	0: Disables features that require PWD (Password) signal reception.	
3-6	Not used	Do not change the settings.	
7	Action when there is no box with an F-code that matches the received SUB code O: Disconnect the line 1: Receive the message (using normal reception mode)	Change this setting when the customer requires.	

Communication Switch 18 - Not used (do not change the settings)

Communication Switch 19 - Not used (do not change the settings)

Communication Switch 1A - Not used (do not change the settings)

Communication Switch 1B (SP No. 1-104-028)			
No	Function	Comments	
0-7	Extension access code (0 to 7) to turn V.8 protocol On/Off 0: On 1: Off	If the PABX does not support V.8/V.34 protocol procedure, set this bit to "1" to disable V.8. Example: If "0" is the PSTN access code, set bit 0 to 1. When the machine detects "0" as the first dialed number, it automatically disables V.8 protocol. (Alternatively, if "3" is the PSTN access code, set bit 3 to 1.)	

Communication Switch 1C (SP No. 1-104-029)			
No	Function	Comments	
0-1	Extension access code (8 and 9) to turn V.8 protocol On/Off 0: On 1: Off	Refer to communication switch 1B. Example: If "8" is the PSTN access code, set bit 0 to 1. When the machine detects "8" as the first dialed number, it automatically disables V.8 protocol. (If "9" is the PSTN access code, use bit 1.)	
2-7	Not used	Do not change the settings.	

Communication Switch 1D - Not used (do not change the settings)	
Communication Switch 1E - Not used (do not change the settings)	
Communication Switch 1F - Not used (do not change the settings)	

G3 Switches

	G3 Switch 00 (SP No. 1-105-001)								
No	Function	Comments							
0 1	Monitor speaker during communication (tx and rx)	(0, 0): The monitor speaker is disabled all through the communication.							

			G3 Switch 00 (SF	° No. 1-105-001)	
No			Function	Comments	
	Bit 1	Bit O	Setting		
	0 0 Disabled		Disabled	(0, 1): The monitor speaker is on up to phase B in the T.30 protocol.	
	0 1 Up to	Up to Phase B	(1, 0): Used for testing. The monitor speaker is on		
	1	0	All the time	all through the communication. Make sure that you reset these bits after testing.	
	1 1 Not used		Not used		
2	transmi	•	er during memory Enabled	1: The monitor speaker is enabled during memory transmission.	
3-7	Not use	ed		Do not change the settings.	

	G3 Switch 01 (SP No. 1-105-002)						
No	Function	Comments					
0	Not used	Do not change the settings.					
1	Select V.8 protocol for manual RX function 0: No 1: Yes	This switch switches the V.8 protocol for manual receiving off and on.					
2-3	Not used	Do not change the settings.					
4	DIS frame length 0: 10 bytes 1: 4 bytes	1: The bytes in the DIS frame after the 4th byte will not be transmitted (set to 1 if there are communication problems with PC-based faxes which cannot receive the extended DIS frames).					
5	Not used	Do not change the setting.					
6	Forbid CED/AMsam output 0: Off 1: On (Forbid output)	Do not change this setting (Default: 0: Off), unless communication problem is caused by a CED or ANSam transmission.					
7	Not used	Do not change the setting.					

	G3 Switch 02 (SP No. 1-105-003)							
No	Function	Comments						
0	G3 protocol mode used 0: Standard and non-standard 1: Standard only	Change this bit to 1 only when the other end can only communicate with machines that send T.30-standard frames only. 1: Disables NSF/NSS signals (these are used in non- standard mode communication)						
1-4	Not used	Do not change the settings.						
5	Use of modem rate history for transmission using Quick/Speed Dials 0: Disabled 1: Enabled	 0: Communications using Quick/Speed Dials always start from the highest modem rate. 1: The machine refers to the modem rate history for communications with the same machine when determining the most suitable rate for the current communication. 						
6	Not Used	Do not change the settings.						
7	Short preamble 0: Disabled 1: Enabled	Refer to Appendix B in the Group 3 Facsimile Manual for details about Short Preamble.						

	G3 Switch 03 (SP No. 1-105-004)					
No	Function	Comments				
0	DIS detection number (Echo countermeasure) O: 1 1: 2	0: The machine will hang up if it receives the same DIS frame twice.1: Before sending DCS, the machine will wait for the second DIS which is caused by echo on the line.				
1	Not Used	Do not change the settings.				
2	V.8 protocol O: Disabled 1: Enabled	 0: V.8/V.34 communications will not be possible. Note Do not set to 0 unless the line condition is always bad enough to slow down the data rate to 14.4 kbps or lower. 				
3	ECM frame size 0: 256 bytes	Keep this bit at "O" in most cases.				

	G3 Switch 03 (SP No. 1-105-004)					
No	Function	Comments				
	1: 64 bytes					
4	CTC transmission conditions O: After one PPR signal received 1: After four PPR signals received (ITU-T standard)	0: When using ECM in non-standard (NSF/NSS) mode, the machine sends a CTC to drop back the modem rate after receiving a PPR, if the following condition is met in communications at 14.4, 12.0, 9.6, and 7.2 kbps. √NTransmit≤NRe send NTransmit- Number of transmitted frames NResend- Number of transmitted frames NResend- Number of frames to be retransmitted 1: When using ECM, the machine sends a CTC to drop back the modem rate after receiving four PPRs. PPR, CTC: These are ECM protocol signals. This bit is not effective in V.34 communications.				
5	Modem rate used for the next page after receiving a negative code (RTN or PIN) 0: No change 1: Fallback	1: The machine's tx modem rate will fall back before sending the next page if a negative code is received. This bit is ignored if ECM is being used.				
6	Not used	Do not change the settings				
7	Select detection of reverse polarity in ringing 0: Off 1: On	This switch is used to prevent reverse polarity in ringing on the phone line (applied to PSTN-G3 ringing). Do not change this setting 0: No detection (Outside Japan) 1: Detection (Inside Japan only)				

	G3 Switch 04 (SP No. 1-105-005)							
No	Function	Comments						
0-3	Training error detection threshold	0 - F (Hex); 0 - 15 bits If the number of error bits in the received TCF is below this threshold, the machine informs the sender that training has succeeded.						

	G3 Switch 04 (SP No. 1-105-005)								
No	lo Function Comments								
4-7	Not used	Do not change the settings.							

			0	G3 Switch	lo. 1-105-006)	
No			Function			Comments
	Initial Tx	modem r	ate (kbps)		
	Bit 3	Bit 2	Bit 1	Bit O	kbps	
	0	0	0	1	2.4	
	0	0	1	0	4.8	
	0	0	1	1	7.2	
	0	1	0	0	9.6	
	0	1	0	1	12.0	These bits set the initial starting modem rate for transmission.
	0	1	1	0	14.4	Use the dedicated transmission parameters if you
0-3	0	1	1	1	16.8	need to change this for specific receivers. If a modem rate 14.4 kbps or slower is selected,
	1	0	0	0	19.2	V.8 protocol should be disabled manually.
	1	0	0	1	21.6	Cross reference V.8 protocol on/off - G3 switch 03, bit 2
	1	0	1	0	24.0	
	1	0	1	1	26.4	
	1	1	0	0	28.8	
	1	1	0	1	31.2	
	0	0	1	1	33.6	
	Other se	ettings - N	ot used	•		
	Initial mo	odem type	e for 9.6 k	k or 7.2 kl	bps.	These bits set the initial modem type for 9.6 and 7.2 kbps, if the initial modem rate is set at these speeds.
4-5	Bit 5	Bit 4		Setting		

	G3 Switch 05 (SP No. 1-105-006)								
No		Fu	unction	Comments					
	0	0	V.29						
	0	1	V.17	•					
	1	0	V.34						
	1	1	Not used						
6-7	Not used			Do not change the settings.					

			G	3 Switch (. 1-105-007)	
No			Function		Comments	
	Initial Rx	modem ra	ate(kbps)			
	Bit 3	Bit 2	Bit 1	Bit O	kbps	-
	0	0	0	1	2.4	
	0	0	1	0	4.8	-
	0	0	1	1	7.2	-
	0	1	0	0	9.6	These bits set the initial starting modem rate for reception.
	0	1	0	1	12.0	Use a lower setting if high speeds pose
0-3	0	1	1	0	14.4	problems during reception.
0-3	0	1	1	1	16.8	If a modem rate 14.4 kbps or slower is selected, V.8 protocol should be disabled
	1	0	0	0	19.2	manually. Cross reference
	1	0	0	1	21.6	V.8 protocol on/off - G3 switch 03, bit2
	1	0	1	0	24.0	
	1	0	1	1	26.4	
	1	1	0	0	28.8	
	1	1	0	1	31.2	
	Other se	ttings - No	ot used			

	G3 Switch 06 (SP No. 1-105-007)								
No		F	unction			Comments			
	Modem types available for reception The setting of these bits is used to inform the transmitting terminal of the available modem type for the machine in receive mode. If V.34 is not selected, V.8 protocol must be disabled manually. Cross reference V.8 protocol on/off - G3 switch 03, bit 2								
	Bit 7	Bit 6	Bit 5	Bit 4		Туреѕ			
4-7	0	0	0	1	V.27t	er			
	0	0	1	0	V.27t	er, V.29			
	0	0	1	1	V.27t	er, V.29, V.33			
	0	1	0	0	V.27t	er, V.29, V.17/V.33			
	0 1 0 1 V.27					er, V.29, V.17/V33, V.34			
	Other set	tings - Not	used						

G3 Switch 07	(SP No.	1-105-008)
--------------	---------	------------

No	Function			Comments
	PSTN cable equalizer (tx mode: Internal)			Use a higher setting if there is signal loss at higher frequencies because of the length of wire between the modem and the telephone
	Bit 1	Bit O	Setting	exchange.
	0	0	None	Use the dedicated transmission parameters for specific receivers.
0-1	0	1	Low	Also, try using the cable equalizer if one or more
	1	0	Medium	of the following symptoms occurs.
	1	1	High	Communication error
				 Modem rate fallback occurs frequently. Note This setting is not effective in V.34 communications.

	G3 Switch 07 (SP No. 1-105-008)				
No	Function			Comments	
	PSTN cable equalizer (rx mode: Internal)			Use a higher setting if there is signal loss at higher frequencies because of the length of wire between the modem and the telephone	
	Bit 3	Bit 2	Setting	exchange.	
	0	0	None	Also, try using the cable equalizer if one or more of the following symptoms occurs.	
2-3	0	1	Low	Communication error with error codes such as	
	1	0	Medium	0-20, 0-23, etc.	
	1	1	High	Modem rate fallback occurs frequently.	
				• This setting is not effective in V.34 communications.	
	PSTN cable equalizer				
	(V.8/V.17 rx	mode: Externa	I)	K 4L : L :4 4]	
4	0: Disabled			Keep this bit at "1".	
	1: Enabled				
5-7	Not used			Do not change the settings.	

G3 Switch 08 - Not used (do not change the settings)

G3 Switch 09 - Not used (do not change the settings)

	G3 Switch 0A (SP No. 1-105-011)			
No		Function		Comments
	Maximum allowable carrier drop during image data reception			
0-1	Bit 1	Bit O	Value (ms)	These bits set the acceptable modem carrier drop time.
	0	0	200	Try a longer setting if error code 0-22 is frequent.
	0	1	400	

	G3 Switch 0A (SP No. 1-105-011)			
No		Function		Comments
	1	0	800	
	1	1	Not used	
2			on of high-speed RX if t while receiving	This switch setting determines if high-speed receiving ends if the carrier signal is lost when receiving during non-ECM mode
3	Not use	ed		Do not change the settings
4	Maximum allowable frame interval during image data reception. 0: 5 s 1: 13 s			This bit set the maximum interval between EOL (end-of-line) signals and the maximum interval between ECM frames from the other end. Try using a longer setting if error code 0-21 is frequent.
5	Not used			Do not change the settings.
6	Reconstruction time for the first line in receive mode 0: 6 s 1: 12 s		me for the first line in receive	When the sending terminal is controlled by a computer, there may be a delay in receiving page data after the local machine accepts set- up data and sends CFR. This is outside the T.30 recommendation. But, if this delay occurs, set this bit to 1 to give the sending machine more time to send data. Refer to error code 0-20. ITU-T T.30 recommendation: The first line should come within 5 s of CFR.
7	Not used			Do not change the settings.

G3 Switch OB Not used (do not change the settings).

G3 Switch OC Not used (do not change the settings).

G3 Switch OD Not used (do not change the settings).

	G3 Switch 0E (SP No. 1-105-015)			
No	Function Comments			
	Set CNG send time interval Some machines on the receiving side may not be able to automatically switch the 3-second CNG interval.			
0-7	High order bit	3000-2250ms: 3000-50xNms 3000 – 50 x Nms 0F (3000 ms) ≤ N ≤ FF (2250 ms)		
	Low order bit	00-0E(3000-3700ms: 3000+50xNms 3000 – 50 x Nms 0F (3000 ms) ≤ N ≤ 0F (3700 ms)		

	G3 Switch OF (SP No. 1-105-016)			
No	Function	Comments		
0	Alarm when an error occurred in Phase C or later O: Disabled 1: Enabled	If the customer wants to hear an alarm after each error communication, change this bit to "1".		
1	Alarm when the handset is off-hook at the end of communication O: Disabled 1: Enabled	If the customer wants to hear an alarm if the handset is off- hook at the end of fax communication, change this bit to "1".		
2-7	Not used	Do not change the settings.		

G3-2 and G3-3 Switches

These switches require an optional G3 interface unit.

G3-3 switches are the same as for G3-2 switches	ches.
---	-------

	G3-2 Switch 00 (SP No. 1-106-001)				
No	Function	Comments			
0 1	Monitor speaker during communication (tx and rx)	(0, 0): The monitor speaker is disabled all through the communication.			

G3-2 Switch 00 (SP No. 1-106-001)				iP No. 1-106-001)
No	Function			Comments
	Bit 1	Bit O	Setting	
	0	0	Disable	(0, 1): The monitor speaker is on up to phase B in the T.30 protocol.
	0	1	Up to Phase B	(1, 0): Used for testing. The monitor speaker is on
	1	0	All the time	all through the communication. Make sure that you reset these bits after testing.
	1	1	Not used	
2	2 Monitor speaker during memory 2 transmission 0: Disabled 1: Enabled		ring memory	1: The monitor speaker is enabled during memory
			led	transmission.
3-7	-7 Not used			Do not change the settings.

	G3-2 Switch 01 (SP No. 1-106-002)			
No	Function	Comments		
0-3	Not used	Do not change the settings.		
4	DIS frame length 0: 10 bytes 1: 4 bytes	1: The bytes in the DIS frame after the 4th byte will not be transmitted (set to 1 if there are communication problems with PC-based faxes which cannot receive the extended DIS frames).		
5	Not used	Do not change the setting.		
6	Forbid CED/AMsam output 0: Off 1: On (Forbid output)	Do not change this setting (Default: 0: Off), unless communication problem is caused by a CED or ANSam transmission.		
7	Not used	Do not change the setting.		

	G3-2 Switch 02 (SP No. 1-106-003)			
No	Function	Comments		
0	G3 protocol mode used O: Standard and non-standard 1: Standard only	Change this bit to 1 only when the other end can only communicate with machines that send T.30-standard frames only. 1: Disables NSF/NSS signals (these are used in non- standard mode communication)		
1-4	Not used	Do not change the settings.		
5	Use of modem rate history for transmission using Quick/Speed Dials 0: Disabled 1: Enabled	 0: Communications using Quick/Speed Dials always start from the highest modem rate. 1: The machine refers to the modem rate history for communications with the same machine when determining the most suitable rate for the current communication. 		
6	Not Used	Do not change the settings.		
7	Short preamble 0: Disabled 1: Enabled	Refer to Appendix B in the Group 3 Facsimile Manual for details about Short Preamble.		

G3-2 Switch 03 (SP No. 1-106-004)		
No	Function	Comments
0	DIS detection number (Echo countermeasure) O: 1 1: 2	0: The machine will hang up if it receives the same DIS frame twice.1: Before sending DCS, the machine will wait for the second DIS which is caused by echo on the line.
1	Not Used	Do not change the settings.
2	V.8 protocol O: Disabled 1: Enabled	 0: V.8/V.34 communications will not be possible. Note Do not set to 0 unless the line condition is always bad enough to slow down the data rate to 14.4 kbps or lower.
3	ECM frame size 0: 256 bytes	Keep this bit at "0" in most cases.

	G3-2 Switch 03 (SP No. 1-106-004)				
No	Function	Comments			
	1: 64 bytes				
	CTC transmission conditions 0: After one PPR signal received	0: When using ECM in non-standard (NSF/NSS) mode, the machine sends a CTC to drop back the modem rate after receiving a PPR, if the following condition is met in communications at 14.4, 12.0, 9.6, and 7.2 kbps. √NTransmit≤NRe send			
4	1: After four PPR signals received	Ntransmit = Number of transmitted frames			
	(ITU-T standard)	Nresend = Number of frames to be retransmitted			
		1: When using ECM, the machine sends a CTC to drop back the modem rate after receiving four PPRs.			
		PPR, CTC: These are ECM protocol signals.			
		This bit is not effective in V.34 communications.			
5	Modem rate used for the next page after receiving a negative code (RTN or PIN)	1: The machine's tx modem rate will fall back before sending the next page if a negative code is received. This bit is ignored if ECM is being used.			
	0: No change 1: Fallback	g			
6	Not used	Do not change the settings			
7	Select detection of reverse polarity in ringing 0: Off	This switch is used to prevent reverse polarity in ringing on the phone line (applied to PSTN-G3 ringing). Do not change this setting			
	1: On	0: No detection (Outside Japan)			
		1: Detection (Inside Japan only)			

	G3-2 Switch 04 (SP No. 1-106-005)					
No	Function	Comments				
0-3	Training error detection threshold	0 - F (Hex); 0 - 15 bits If the number of error bits in the received TCF is below this threshold, the machine informs the sender that training has succeeded.				

	G3-2 Switc	h 04 (SP No. 1-106-005)			
No	Function Comments				
4-7	Not used	Do not change the settings.			

		G3-2 Switch 05 (SP No. 1-106-006)						
No			Function			Comments		
	Initial Tx	modem r	ate (kbps)				
	Bit 3	Bit 2	Bit 1	Bit O	kbps			
	0	0	0	1	2.4			
	0	0	1	0	4.8			
	0	0 0 1 1 7.2						
	0	1	0	0	9.6	These bits set the initial starting modem rate for		
	0	1	0	1	12.0	transmission. Use the dedicated transmission parameters if you		
0-3	0	1	1	0	14.4	need to change this for specific receivers.		
0-3	0	1	1	1	16.8	If a modem rate 14.4 kbps or slower is selected, V.8 protocol should be disabled manually.		
	1	0	0	0	19.2	Cross reference		
	1	0	0	1	21.6	V.8 protocol on/off - G3 switch 03, bit 2		
	1	0	1	0	24.0			
	1	0	1	1	26.4			
	1	1	0	0	28.8			
	1	1	0	1	31.2			
	Other se	ettings - N	ot used					
	Initial modem type for 9.6 k or 7.2 kbps.				bps.	These hits set the initial modern type for 0.4 and		
4-5	Bit 5	Bit 4		Setting		These bits set the initial modem type for 9.6 and 7.2 kbps, if the initial modem rate is set at these		
	0	0		V.29		speeds.		

	G3-2 Switch 05 (SP No. 1-106-006)						
No		Fu	unction	Comments			
	0	1	V.17				
	1	0	V.34				
	1	1	Not used				
6-7	Not used			Do not change the settings.			

G3-2 Switch 06 (SP No. 1-106-007)							
No			Function			Comments	
	Initial Rx	modem ro	ate(kbps)				
	Bit 3	Bit 2	Bit 1	Bit O	kbps		
	0	0	0	1	2.4		
	0	0	1	0	4.8		
	0	0	1	1	7.2		
	0	1	0	0	9.6	These bits set the initial starting modem rate for reception.	
	0	1	0	1	12.0	Use a lower setting if high speeds pose	
0.0	0	1	1	0	14.4	problems during reception.	
0-3	0	1	1	1	16.8	If a modem rate 14.4 kbps or slower is selected, V.8 protocol should be disabled	
	1	0	0	0	19.2	manually. Cross reference	
	1	0	0	1	21.6	V.8 protocol on/off - G3 switch 03, bit2	
	1	0	1	0	24.0		
	1	0	1	1	26.4		
	1	1	0	0	28.8		
	1	1	0	1	31.2		
	Other se	ttings - Nc	ot used				
4-7	Modem	types avai	lable for r	eception			

	G3-2 Switch 06 (SP No. 1-106-007)								
No		Function			Comments				
	The setting of these bits is used to inform the transmitting terminal of the available modem type for the machine in receive mode.								
	If V.34 is not :	selected, V.8 pr	otocol must be	disabled manu	ally.				
	Cross referen	се							
	V.8 protocol o	V.8 protocol on/off - G3 switch 03, bit 2							
	Bit 7	Bit 6	Bit 5	Bit 4	Types				
	0	0	0	1	V.27ter				
	0	0	1	0	V.27ter				
	0	0	1	1	V.27ter				
	0	1	0	0	V.27ter				
	0	1	0	1	V.27ter				
	Other settings	- Not used	11						

		No. 1-106-008)		
No		Function		Comments
	PSTN cable ed (tx mode: Inter	•		Use a higher setting if there is signal loss at higher frequencies because of the length of wire between the modem and the telephone
	Bit 1	Bit O	Setting	exchange.
	0	0	None	Use the dedicated transmission parameters for specific receivers.
0-1	0	1	Low	Also, try using the cable equalizer if one or more
0-1	1	0	Medium	of the following symptoms occurs.
	1	1	High	Communication error
				 Modem rate fallback occurs frequently. Note This setting is not effective in V.34 communications.

	G3-2 Switch 07 (SP No. 1-106-008)					
No	Function			Comments		
	PSTN cable e (rx mode: Inte			Use a higher setting if there is signal loss at higher frequencies because of the length of wire between the modem and the telephone		
	Bit 3	Bit 2	Setting	exchange.		
	0	0	None	Also, try using the cable equalizer if one or more of the following symptoms occurs.		
2-3	0	1	Low	Communication error with error codes such as		
	1	0	Medium	0-20, 0-23, etc.		
	1 1 High		High	Modem rate fallback occurs frequently.		
				• This setting is not effective in V.34 communications.		
	PSTN cable e	qualizer				
4	(V.8/V.17 rx	mode: Externo	ıl)	Keep this bit at "1".		
-	0: Disabled					
	1: Enabled					
5-7	Not used			Do not change the settings.		

G3-2 Switch 08 - Not used (do not change the settings)

G3-2 Switch 09 - Not used (do not change the settings)

			G3-2 Switch OA (SP	No. 1-106-011)
No		Fur	nction	Comments
		allowable ta reception	carrier drop during n	
	Bit 1 Bit O Value (ms)		Value (ms)	These bits set the acceptable modem carrier drop
0-1	0	0	200	time. Try a longer setting if error code 0-22 is frequent.
	0 1	1	400	Try a longer sening it error code 0-22 is frequeni.
	1 0 800		800	

4

	G3-2 Switch 0A (SP No. 1-106-011)				
No		Fur	nction	Comments	
	1	1	Not used		
2 Select cancellation of high-speed RX if carrier signal lost while receiving 0: Off 1: On			÷ .	This switch setting determines if high-speed receiving ends if the carrier signal is lost when receiving during non-ECM mode	
3	Not used			Do not change the settings	
4	Maximum allowable frame interval during image data reception. O: 5 s 1: 13 s			This bit set the maximum interval between EOL (end-of-line) signals and the maximum interval between ECM frames from the other end. Try using a longer setting if error code 0-21 is frequent.	
5	Not used			Do not change the settings.	
6	Reconstruction time for the first line in receive mode 0: 6 s 1: 12 s		or the first line in receive	When the sending terminal is controlled by a computer, there may be a delay in receiving page data after the local machine accepts set- up data and sends CFR. This is outside the T.30 recommendation. But, if this delay occurs, set this bit to 1 to give the sending machine more time to send data. Refer to error code 0-20. ITU-T T.30 recommendation: The first line should come within 5 s of CFR.	
7	Not used			Do not change the settings.	

G3-2 Switch OB- Not used (do not change the settings)
G3-2 Switch OC- Not used (do not change the settings)
G3-2 Switch OD - Not used (do not change the settings)
G3-2 Switch OE - Not used (do not change the settings)
G3-2 Switch OF - Not used (do not change the settings)

G4 Internal Switches

The G4 internal switches (SW00 to 1F) are displayed but do not change these settings.

G4 Parameter Switches

The G4 parameter switches (SW00 to 0F) are displayed but do not change these settings.

IP Fax Switches

	IP Fax Switch 00 (SP No. 1-111-001)						
No.	Function	Comments					
0	Not used	Do not change this setting.					
1	IP Fax Transport 0: TCP, 1: UDP	Selects TCP or UDP protocol for IP-Fax					
2	IP Fax single port selection 0: OFF, 1: ON (enable)	Selects single data port.					
3	IP Fax double ports (single data port) selection 0: OFF, 1: ON (enable)	Selects whether IP-Fax uses a double port.					
4	IP Fax Gatekeeper 0: OFF, 1: ON (enable)	Enables/disables the gatekeeper for IP-Fax.					
5	IP Fax T30 bit signal reverse O: LSB first, 1: MSB first	Reverses the T30 bit signal.					
6	IP Fax max bit rate setting 0: Not affected, 1: Affected	When "O" is selected, the max bit rate does not affect the value of the DIS/DCS. When "1" is selected, the max bit rate affects the value of the DIS/DCS.					
7	IP Fax received telephone number confirmation 0: No confirmation, 1: Confirmation	When "O" is selected, fax data is received without checking the telephone number. When "1" is selected, fax data is received only when confirming that the telephone number from the sender matches the registered telephone number in					

	IP Fax Switch 00 (SP No. 1-111-001)					
No.	Function Comments					
		this machine. If this confirmation fails, the line is disconnected.				

	IP Fax Switch 01 (SP No. 1-111-002)										
No.		Function			Comments						
	IP Fax delay level setting Selects the acceptable delay level. Level 0 is the highest quality Default is "0000" (level 0).										
0-3	Bit 3	Bit 2	Bit 1	Bit O							
	0	0	0	0	Level O						
	0	0	0	1	Level 1						
	0	0	1	0	Level 2						
	0	0	1	1	Level 3						
4-7	IP Fax pream	ole wait time se	tting	combination. Waiting time: set v	es in this 4-bit binary switch alue level x 100 ms 5) Min: 00 (No wait time)						

	IP Fax Switch 02 (SP No. 1-111-003)						
No.	Function	Comments					
0	IP Fax bit signal reverse setting O: Maker code setting 1: Internal bit switch setting	When "O" is selected, the bit signal reverse method is decided by the maker code. When "1" is selected, the bit signal reverse method is decided by the internal bit switch.					

	IP Fax Switch 02 (SP No. 1-111-003)							
No.	Function	Comments						
		When communicating between IP Fax devices, LSB first is selected.)						
1	IP Fax transmission speed setting 0: Modem speed 1: No limitation	Selects the transmit speed for IP Fax communication.						
2	SIP transport setting 0: TCP 1: UDP	This bit switch sets the transport that has priority for receiving IP Fax data. This function is activated only when the sender has both TCP and UDP.						
3-7	Not used	Do not change these settings.						

	IP Fax Switch 03 (SP No. 1-111-004)							
No.	Function	Comments						
0	Effective field limitation for G3 standard function information 0: OFF, 1: 4byte (DIS)	Limits the effective field for standard G3 function information.						
1	Switching between G3 standard and G3 non standard O: Enable switching 1: G3 standard only	Enables/disables switching between G3 standard and G3 non-standard.						
2	AI modem rate function 0: OFF, 1: ON (enable)	Enables/disables the AI modem rate.						
3	ECM frame size selection at transmitting 0: 256byte, 1: 64byte	Selects the ECM frame size for sending.						
4	DIS detection times for echo prevention 0: 1 time, 1: 2 times	Sets the number of times for DIS to detect echoes.						
5	CTC transmission selection O: PPRx1 1: PPRx4	When "0" is selected, the transmission condition is decided by error frame numbers.						

	IP Fax Switch 03 (SP No. 1-111-004)						
No.	Function	Comments					
		When "1" is selected, the transmission condition is based on the ITU-T method.					
6	Shift down setting at receiving negative code 0: OFF, 1: ON	Selects whether to shift down when negative codes are received.					
7	Not used	Do not change this setting.					

	IP Fax Switch 04 (SP No. 1-111-005)						
No.	No. Function Comments						
0-3	TCF error threshold	Sets the TCF error threshold level. [00 to 0f] The default is "1111" (0fH).					
4-7	Not used	Do not change these settings.					

			IP Fax	1-111-006)		
No.			Function			Comments
	Modem	bit rate set	tting for tro	ansmission	(kbps)	
	Bit 3	Bit 2	Bit 1	Bit O	kbps	
	0	0	0	1	2.4	
	0	0	1	1	4.8	
	0	0	1	1	7.2	
0-3	0	1	0	0	9.6	Sets the modem bit rate for transmission. The default is "0110" (14.4K bps).
	0	1	0	1	12.0	
	0	1	1	0	14.4	
	0	1	1	1	16.8	
	1	0	0	0	19.2	
	1	0	0	1	21.6	

IP Fax Switch 05 (SP No. 1-111-006)							
No.			Function				Comments
	1	0	1		0	24.0	
	1	0	1		1	26.4	
	1	1	0		0	28.8	
	1	1	0		1	31.2	
	1	1	1		0	33.6	
	Modem	setting for	transmissi	on			
	Bit 5	5	Bit 4		T	ypes	
4-5	0		0		١	/29	Sets the modem type for transmission.
4-5	0		1		V17		The default is "00" (V29).
	1		0		V34		
	1		1		Not used		
6-7	Not used	4					Do not change these settings.

	IP Fax Switch 06 (SP No. 1-111-007)										
No.		Function				Comments					
0-3	Modem bit rate setting for reception Sets the modem bit rate for reception. The default is "0110" (14.4K bps).										
	Modem setting for reception Sets the modem type for reception. The default is "0100" (V27ter, V29, V17).										
	Bit 7	Bit 6	Bit 5		Bit 4	Types					
4-7 0 0 0 1 V.27ter						V.27ter					
	0	0	1		0	V.27ter, V.29					
	0	0	1		1	V.27ter, V.29, V.33					
	0	1	0		0	V.27ter, V.29, V.17/V.33					

	IP Fax Switch 06 (SP No. 1-111-007)					
No.	Function Comments					
	Other settings - Not used					

IP Fax Switch 07 (SP No. 1-111-008)						
No.	Function	Comments				
0	TSI information 0: Not added, 1: Added	Adds or does not add TSI information to NSS(S).				
1	DCN transmission setting at T1 timeout 0: Not transmitted 1: Transmitted	Transmits or does not transmit DCN at T1 timeout.				
2	Not used	Do not change this setting.				
3	Hang up setting at DIS reception disabled 0: No hang up 1: Hang up after transmitting DCN	Sets whether the machine disconnects after DIS reception.				
4	Number of times for training 0: 1 time, 1: 2 times	Selects the number of times training is done at the same bit rate.				
5	Space CSI transmission setting at no CSI registration O: Not transmitted 1: Transmitted	When "0" is selected, frame data is enabled. When "1" is selected, the transmitted data is all spaces.				
6-7	Not used	Do not change these settings.				

	IP Fax Switch 08 (SP No. 1-111-009)								
No.		Function		Comments					
	T1 timer adju	stment							
	Bit 1	Bit O		Adjusts the T1 timer.					
0-1	0	0	35 s	The default is "00" (35 seconds).					
	0	1	40 s						

		IP Fo	x Switch 08 (S	SP No. 1-111-009)
No.	Function			Comments
	1	0	50 s	
	1	1	60 s	
	T4 timer adju	stment		
	Bit 3	Bit 2		
2-3	0	0	3 s	Adjust the T4 timer.
Z-3	0	1	3.5 s	The default is "00" (3 seconds).
	1	0	4 s	
	1	1	5 s	
	T0 timer adju	stment		
	Bit 5	Bit 4		Adjusts the fail safe timer. This timer sets the interval
4-5	0	0	75 s	between "setup" data transmission and T.38 phase decision. If your destination return is late on the
4-5	0	1	120 s	network or G3 fax return is late, adjust the longer interval timer.
	1	0	180 s	The default is "00" (75 seconds).
	1	1	240 s	
6-7	Not used			Do not change these settings.

NCU Parameters

The following tables give the RAM addresses and the parameter calculation units that the machine uses for ringing signal detection and automatic dialing. The factory settings for each country are also given. Most of these must be changed by RAM read/write (SP2-102), but some can be changed using NCU Parameter programming (SP2-103, 104 and 105); if SP2-103, 104 and 105 can be used, this will be indicated in the Remarks column. The RAM is programmed in hex code unless (BCD) is included in the Unit column.

Note

- The following addresses describe settings for the standard NCU.
- Change the fourth digit from "5" to "6" (e.g. 680500 to 680600) for the settings for the first optional G3 interface unit and from "5" to "7" (e.g. 680700) for the settings for the second optional G3 interface unit.

Address	Function			Unit	Remarks		
	Country/Area co parameters	ode for NCU					
	Use the Hex value the decimal value				irectly	into this addre	ess, or use
	Country/Area	Decimal	Hex	Country/A	Area	Decimal	Hex
	France	00	00	Hong Kon	g	20	14
	Germany 01 01		South Afric	a	21	15	
	UK	02	02	Australia		22	16
680500	Italy	03	03	New Zealand		23	17
	Austria	04	04	S'pore		24	18
	Belgium	05	05	Malaysia		25	19
	Denmark	06	06	China		26	1A
	Finland	07	07	Taiwan		27	1B
	Ireland	08	08	Korea		28	1C
	Norway	09	09	Turkey		32	20
	Sweden	10	0A	Greece		33	21

Address	Function			Unit	Remarks		
	Switz.	11	OB	Hungary		34	22
	Portugal	12	0C	Czech		35	23
	Country/Area	Decimal	Hex	Country/A	Area	Decimal	Hex
	Holland	13	0D	Poland		36	24
	Spain	14	OE				
	lsrael	15	OF				
	USA	17	11				
680501	Line current detec	tion time				urrent detectior	n is
680502	Line current wait t	ime		20 ms	disabled. Line current is not detected i		tected if
680503	Line current drop	detect time			680501 contains FF.		
680504	PSTN dial tone frequency upper limit (high byte)			Hz	If both addresses contain F (H), tone detection is disabled.		
680505	PSTN dial tone frequency upper limit (low byte)			(BCD)			i
680506	PSTN dial tone frequency lower limit (high byte)			Hz	If both addresses contain F		
680507	PSTN dial tone fre byte)	equency lower lin	nit (low	(BCD)	(H), tone detection is disabled.		i
680508	PSTN dial tone de	etection time					
680509	PSTN dial tone re	set time (LOW))508 contains l achine pauses f	
68050A	PSTN dial tone re	set time (HIGH)			pause	time (address	
68050B	PSTN dial tone continuous tone time			20 ms		0D / 68050E) See Note 2.).
68050C	PSTN dial tone permissible drop time						
68050D	PSTN wait interval (LOW)						
68050E	PSTN wait interval (HIGH)						
68050F	PSTN ring-back to	one detection time	9	20 ms		tion is disabled ins FF.	if this

Address	Function		Unit	Remarks	
680510	PSTN ring-back tone off detection time		20 ms		
680511	PSTN detection time for silent period aft ring-back tone detected (LOW)	ter	20 ms		
680512	PSTN detection time for silent period aft ring-back tone detected (HIGH)	ter	20 ms		
680513	PSTN busy tone frequency upper limit (hi byte)	gh	Hz	If both addresses contain FF	
680514	PSTN busy tone frequency upper limit (lo byte)	wc	(BCD)	(H), tone detection is disabled.	
680515	PSTN busy tone frequency lower limit (hi byte)	gh	Hz	If both addresses contain FF	
680516	PSTN busy tone frequency lower limit (lo byte)	wc	(BCD)	(H), tone detection is disabled.	
680517	PABX dial tone frequency upper limit (hi byte)	gh	Hz	If both addresses contain FF	
680518	PABX dial tone frequency upper limit (lo byte)	w	(BCD)	(H), tone detection is disabled.	
680519	PABX dial tone frequency lower limit (hi byte)	gh	Hz	If both addresses contain FF	
68051A	PABX dial tone frequency lower limit (lo byte)	w	(BCD)	(H), tone detection is disabled.	
68051B	PABX dial tone detection time				
68051C	PABX dial tone reset time (LOW)			If 68051B contains FF, the	
68051D	PABX dial tone reset time (HIGH)			machine pauses for the pause time (680520 /	
68051E	PABX dial tone continuous tone time		20 ms	680521).	
68051F	PABX dial tone permissible drop time				
680520	PABX wait interval (LOW)				
680521	0521 PABX wait interval (HIGH)				

Address		Function			Unit	Remarks		
680522	PABX ring	gback tone detec	tion time		20 ms	If both addresses contain FF		
680523	PABX ring	gback tone off de	tection time		20 ms	(H), tone detection is disabled.		
680524		ection time for sil tone detected (LC	•	fter	20 ms	If both addresses contain FF		
680525		ection time for sil tone detected (H	•	fter	20 ms	(H), tone detection is disabled.		
680526	PABX bus byte)	y tone frequency	upper limit (ł	nigh	Hz	If both addresses contain FF		
680527	PABX bus byte)	y tone frequency	upper limit (low	(BCD)	(H), tone detection is disabled.		
680528	PABX bus byte)	y tone frequency	lower limit (ł	nigh	Hz	If both addresses contain FF		
680529	PABX bus byte)	y tone frequency	lower limit (low	(BCD)	(H), tone detection is disabled.		
68052A	Busy tone	ON time: range	1					
68052B	Busy tone	e OFF time: range	1					
68052C	Busy tone	ON time: range	2		20 ms			
68052D	Busy tone	• OFF time: range	2					
68052E	Busy tone	ON time: range	3					
68052F	Busy tone	• OFF time: range	3			-		
680530	Busy tone	ON time: range	4					
680531	Busy tone OFF time: range 4				20 ms			
680532	Busy tone continuous tone detection time				•			
Busy tone signal state time tolerance for all ranges, and number of cycles require detection (a setting of 4 cycles means that ON-OFF-ON or OFF-ON-OFF must l detected twice).								
000000	Tolerance	e (±)	r					
	Bit 1	Bit O						

Address	Function		Unit	Remarks		
	0	0	75%		·	
	0	1	50%	_		
	1	0	25%	_		
	1	1	12.5%	-		
	Bits 2 and	d 3 must always k	be kept at 0.	1		
	Bits 7, 6,	5, 4 - number of	cycles requi	red for cadence	detection	
680534		nal dial tone frec it (high byte)	luency		If both addresses contain FF	
680535		nal dial tone frec it (low byte)	luency	Hz (BCD)	(H), tone detection is disabled.	
680536		nal dial tone frec it (high byte)	luency	Hz (BCD) (H), tone detect	If both addresses contain FF	
680537		nal dial tone frec it (low byte)	luency			
680538	Internatio	nal dial tone dete	ection time			
680539	Internatio (LOW)	nal dial tone rese	et time		If 680538 contains FF, the	
68053A	Internatio (HIGH)	nal dial tone rese	et time		machine pauses for the pause time (68053D /	
68053B	Internatio time	nal dial tone cont	inuous tone	20 ms	68053E). Belgium: See Note 2.	
68053C	International dial tone permissible drop time					
68053D	Internatio	nal dial wait inte	rval (LOW)			
68053E	Internatio	nal dial wait inter	val (HIGH)			
68053F	Country o limit (HIG	dial tone upper fr H)	equency		If both addresses contain FF	
680540	Country o limit (LOV	dial tone upper fr V)	equency	Hz (BCD)	(H), tone detection is disabled.	

Address	Function	Unit	Remarks
680541	Country dial tone lower frequency limit (HIGH)		If both addresses contain FF (H), tone detection is
680542	Country dial tone lower frequency limit (LOW)		disabled.
680543	Country dial tone detection time		If 680543 contains FF, the
680544	Country dial tone reset time (LOW)	20 ms	machine pauses for the pause time (680548 /
680545	Country dial tone reset time (HIGH)	20 ms	680549).
680546	Country dial tone continuous tone time		
680547	Country dial tone permissible drop time		
680548	Country dial wait interval (LOW)	20 ms	
680549	Country dial wait interval (HIGH)		
68054A	Time between opening or closing the DO relay and opening the OHDI relay	l ms	See Notes 3, 6 and 8. SP2-103-012 (parameter 11).
68054B	Break time for pulse dialing	l ms	See Note 3. SP2-103-013 (parameter 12).
68054C	Make time for pulse dialing	l ms	See Note 3. SP2-103-014 (parameter 13).
68054D	Time between final OHDI relay closure and DO relay opening or closing	1 ms	See Notes 3, 6 and 8. SP2-103-015 (parameter 14). This parameter is only valid in Europe.
68054E	Minimum pause between dialed digits (pulse dial mode)	20 ms	See Note 3 and 8. SP2-103-016 (parameter 15).

Address	Function	Unit	Remarks
68054F	Time waited when a pause is entered at the operation panel		SP2-103-017 (parameter 16). See Note 3.
680550	DTMF tone on time	1 ms	SP2-103-018 (parameter 17).
680551	DTMF tone off time	1 1115	SP2-103-019 (parameter 18).
680552	Tone attenuation level of DTMF signals while dialing	-N x 0.5 –3.5 dBm	SP2-103-020 (parameter 19). See Note 5.
680553	Tone attenuation value difference between high frequency tone and low frequency tone in DTMF signals	-dBm x 0.5	SP2-103-021 (parameter 20). The setting must be less than –5dBm, and should not exceed the setting at 680552h above. See Note 5.
680554	PSTN: DTMF tone attenuation level after dialling	-N x 0.5 –3.5 dBm	SP2-103-022 (parameter 21). See Note 5.
680555	ISDN: DTMF tone attenuation level after dialling	-dBm x 0.5	See Note 5
680556	Not used		Do not change the settings.
680557	Time between 68054Dh (NCU parameter 14) and 68054Eh (NCU parameter 15)	1 ms	This parameter takes effect when the country code is set to France.
680558	Not used		Do not change the setting.
680559	Grounding time (ground start mode)	20 ms	The Gs relay is closed for this interval.
68055A	Break time (flash start mode)	1 ms	The OHDI relay is open for this interval.
68055B	International dial access code (High)	RCD	For a code of 100:
68055C	International dial access code (Low)	BCD	68055B - F1

Address	Function	Unit		Remarks		
				68055C - 00		
68055D	PSTN access pause time	20 ms		This time is waited for each pause input after the PSTN access code. If this address contains FF[H], the pause time stored in address 68054F is used. Do not set a number more than 7 in the UK.		
		Bit 7	Bit d	6	Bit 5	dBm
		0	0		0	-25.0
68055E	Progress tone detection level, and cadence detection enable flags	0	0		1	-35.0
CCCCCL		0	1		0	-30.0
		1	1 0		0	-40.0
		Bits 2, 0 - See Note 2.				
68055F to 680564	Not used			Do not change the settings.		
680565	Long distance call prefix (HIGH)	BCD	Fo	For a code of 0:		
680566	Long distance call prefix (LOW)	BCD		680565 - FF 680566 - FF		
680567 to 680571	Not used		D	Do not change the settings.		e settings.
680572	Acceptable ringing signal frequency: range 1, upper limit			SP2-103-003 (parameter 02).		arameter
680573	Acceptable ringing signal frequency: range 1, lower limit	1000/ N (Hz).		P2-1 3).	03-004 (p	arameter
680574	Acceptable ringing signal frequency: range 2, upper limit			SP2-103-005 (parameter 04).		

Address	F	unction	Unit	Remarks
680575	Acceptable ring range 2, lower	ging signal frequency: limit		SP2-103-006 (parameter 05).
680576	Number of ring	s until a call is detected	1	SP2-103-007 (parameter 06). The setting must not be zero.
680577	Minimum requi ring	red length of the first	20 ms	See Note 4. SP2-103-008 (parameter 07).
680578	Minimum requi second and sub	red length of the osequent rings	20 ms	SP2-103-009 (parameter 08).
680579	Ringing signal ((LOW)	detection reset time	20	SP2-103-010 (parameter 09).
68057A	Ringing signal ((HIGH)	detection reset time	– 20 ms	SP2-103-011 (parameter 10).
68057B to 680580	Not used			Do not change the settings.
680581	and switching the external telephone	en dialing the last digit ne Oh relay over to the one when dialing from anel in handset mode.	20 ms	Factory setting: 500 ms
	Bits 0 and 1 - H	landset off-hook detec	tion time	
	Bit 1	Bit O	Setting	
	0	0	200 ms	
	0 1		800 ms	-
680582		Other	Not used	
	Bits 2 and 3 - H	landset on-hook detec	tion time	
	Bit 3	Bit 2	Setting	
	0	0	200 ms	

Address	I	Function	Unit	Remarks
	0	1	800 ms	
		Other	Not used	
	Bits 4 to 7 - No	t used		
680583				
to	Not used			Do not change the settings.
6805A0				
6805A1	Acceptable CE upper limit (hig	D detection frequency h byte)	BCD (Hz)	If both addresses contain FF (H), tone detection is
6805A2	Acceptable CE upper limit (low	D detection frequency v byte)		disabled.
6805A3	Acceptable CE lower limit (hig	D detection frequency h byte)		If both addresses contain FF
6805A4	Acceptable CE lower limit (low	D detection frequency byte)	– BCD (Hz)	(H), tone detection is disabled.
6805A5	CED detection time		20 ms ± 20 ms	Factory setting: 200 ms
6805A6	Acceptable CN frequency uppe	IG detection er limit (high byte)		If both addresses contain FF
6805A7	Acceptable CN frequency uppe	IG detection er limit (low byte)	– BCD (Hz)	(H), tone detection is disabled.
6805A8	Acceptable CN frequency lowe	IG detection er limit (high byte)		If both addresses contain FF
6805A9	Acceptable CN frequency lowe	IG detection er limit (low byte)	– BCD (Hz)	(H), tone detection is disabled.
6805AA	Not used			Do not change the setting.
6805AB	CNG on time		20 ms	Factory setting: 500 ms
6805AC	CNG off time		20 ms	Factory setting: 3000 ms
6805AD	Number of CN detection	G cycles required for		The data is coded in the same way as address 680533.

Address	Function	Unit	Remarks
6805AE	Not used		Do not change the settings.
6805AF	Acceptable AI short protocol tone (800Hz) detection frequency upper limit (high byte)	Hz (BCD)	If both addresses contain FF (H), tone detection is
6805B0	Acceptable AI short protocol tone (800Hz) detection frequency upper limit (low byte)	nz (BCD)	disabled.
6805B1	Acceptable AI short protocol tone (800Hz) detection frequency lower limit (high byte)		If both addresses contain FF
6805B2	Acceptable AI short protocol tone (800Hz) detection frequency lower limit (low byte)	Hz(BCD)	(H), tone detection is disabled.
6805B3	Detection time for 800 Hz Al short protocol tone	20 ms	Factory setting: 360 ms
6805B4	PSTN: Tx level from the modem	-N – 3 dBm	SP2-103-002 (parameter 01).
6805B5	PSTN: 1100 Hz tone transmission level	- N 6805B4 - See Note 7.	0.5N 6805B5 –3.5 (dB)
6805B6	PSTN: 2100 Hz tone transmission level	- N6805B4 - (See Note 7.	D.5N 6805B6 –3 (dB)
6805B7	PABX: Tx level from the modem	- dBm	
6805B8	PABX: 1100 Hz tone transmission level	- N 6805B7 -	0.5N 6805B8 (dB)
6805B9	PABX: 2100 Hz tone transmission level	- N 6805B7 -	0.5N 6805B9 (dB)
6805BD	Modem turn-on level (incoming signal detection level)	-37-0.5N (dBm)	
6805BE to 6805C6	Not used		Do not change the settings.

Address		Funct	ion				Unit	Remarks
6805C7	Bits 0 to 3 – Not used. Bit 4 – V.34 protocol dump - 0: Simple, 1: Detailed (de Bits 5 to 7 – Not used.							efault)
6805C8 to 6805D9	Not used							Do not change the settings.
6805DA	T.30 T1 t	imer				1 s		
6805E0 bit 3	Maximum wait time for post message						12 s 30 s	1: Maximum wait time for post message (EOP/EOM/ MPS) can be changed to 30 s. Change this bit to "1" if communication errors occur frequently during V.17 reception.
	Voltage setting to detect off-hook for voltage/DP detection for an externally connected line.						Auto Fixed V	Do not change these settings
		summary o r an extern			-		ings (1:	
	Bit 7	Bit 6	Bit 5	B	Bit 4			
6805E3	0	0	0		0	N	ot used	
	0	0	0		1	2.	75 V	
	0	0	1		0	5.	5 V	
	1	0	0		0	22	2 V	
	1	1	1		1	41	.25 V	
6805E4	Bit I sets the level of the call		Bit 1		0	RT=O (Lov RT=1 (Hig		
000314	signal, Bit 3 sets the call signal impedance Bit 3				3	0	RZ=0 (High)	

Address		Funct	ion			Unit	Remarks
					1	RZ=1 (Composite)	•
	DI: O			Bit O	0	RT=0 (Low)	
		ets the ring de 1, Bit 1 sets th		ЫГО	1	RT=1 (High	If any setting is changed, select a setting that is higher
	detection fixed.	on method w	hen	Bit 1	0	Use RDTP	than the default setting.
	integ.			DILI	1	Use RDTN	
		a summary o k for DP dete		etection of			
6805E5	Bit 7	Bit 6	Bit 5	Bit 4			
	0	0	0	0		Not used	
	0	0	0	1		2.75 V	
	0	0	1	0		5.5 V	
	1	0	0	0		22 V	
	1	1	1	1		41.25 V	

Notes

- 1. If a setting is not required, store FF in the address.
- 2. Italy and Belgium only

RAM address 68055E: the lower four bits have the following meaning.

- Bit 2 1: International dial tone cadence detection enabled (Belgium)
- Bit 1 Not used

Bit 0 - 1: PSTN dial tone cadence detection enabled (Italy)

If bit 0 or bit 2 is set to 1, the functions of the following RAM addresses are changed.

680508 (if bit 0 = 1) or 680538 (if bit 2 = 1): tolerance for on or off state

duration (%), and number of cycles required for detection, coded as in address 680533.

68050B (if bit 0 = 1) or 68053B (if bit 2 = 1): on time, hex code (unit = 20 ms)

68050C (if bit 0 = 1) or 68053C (if bit 2 = 1): off time, hex code (unit = 20 ms)

3. Pulse dial parameters (addresses 68054A to 68054F) are the values for 10 pps. If 20 pps is used, the machine automatically compensates.

- 4. The first ring may not be detected until 1 to 2.5 wavelengths after the time specified by this parameter.
- 5. The calculated level must be between 0 and 10.

The attenuation levels calculated from RAM data are:

High frequency tone: - 0.5 x N680552/680554-3.5 dBm

– 0.5 x N680555 dBm

Low frequency tone:- 0.5 x (N680552/680554 + N680553) -3.5 dBm

– 0.5 x (N680555 + N680553) dBm

N680552, for example, means the value stored in address 680552(H)

6. Ds and Di relay timing

68054A: Europe - Between Ds opening and Di opening, France - Between Ds closing and Di opening 68054D: Europe - Between Ds closing and Di closing, France - Between Ds opening and Di closing

- 7. Tone signals which frequency is lower than 1500Hz (e.g., 800Hz tone for AI short protocol) refer to the setting at 6805B5h. Tones which frequency is higher than 1500Hz refer to the setting at 6805B6h.
- 8. 68054A, 68054D, 68054E: The actual inter-digit pause (pulse dial mode) is the sum of the period specified by the RAM addresses 68054A, 68054D, and 68054E.

Dedicated Transmission Parameters

There are two sets of transmission parameters: Fax and E-mail

Each Quick Dial Key and Speed Dial Code has eight bytes of programmable parameters allocated to it. If transmissions to a particular machine often experience problems, store that terminal's fax number as a Quick Dial or Speed Dial, and adjust the parameters allocated to that number.

The programming procedure will be explained first. Then, the eight bytes will be described.

Programming Procedure

- 1. Set the bit 0 of System Bit Switch 00 to 1.
- Enter Address Book Management mode ([User Tools]> System Settings> Key Operator> Address Book Management).
- 3. Select the address book that you want to program.
- For the fax parameter, select "Fax Dest.", for the E-mail parameter, select "E-mail", then press "Start". Make sure that the LED of the Start button lights green.
- 5. The settings for the switch 00 are now displayed. Press the bit number that you wish to change.
- 6. To scroll through the parameter switches, either:
- 7. Do one of the following:

Select the next switch: press "Next"

or

Select the previous switch: "Prev." until the correct switch is displayed. Then go back to step 6.

- 8. After the setting is changed, press "OK".
- 9. After finishing, reset bit 0 of System Bit Switch 00 to 0.

Parameters

Fax Parameters

The initial settings of the following fax parameters are all FF(H). This means that all the parameters are disabled.

	Switch 00
	Function and Comments
ITU-T T1 time (for PSTN G3 mode)	

4

Switch 00

Function and Comments

If the connection time to a particular terminal is longer than the NCU parameter setting, adjust this byte. The T1 time is the value stored in this byte (in hex code), multiplied by 1 second.

Range: 0 to 120 s (00h to 78h)

FFh - The local NCU parameter factory setting is used.

Do not program a value between 79h and FEh.

						Switch 01	I
No			Fu	unction			Function
	Tx leve	əl					
	Bit 4	Bit 3	Bit 2	Bit 1	Bit O		
	0	0	0	0	0	0	If communication with a particular remote terminal often contains errors, the signal level
	0	0	0	0	1	-1	may be inappropriate. Adjust the Tx level for communications with that terminal until the
0	0	0	0	1	0	-2	results are better.
to 4	0	0	0	1	1	-3	If the setting is "Disabled", the NCU parameter 01 setting is used.
	0	0	1	0	0	-4	♦ Note
			and :	so on u	ntil	1	• Do not use settings other than listed on the left.
	0	1	1	1	1	-15	the left.
	lf all fi	ve bits o	are at 1	, the se	tting is 'Di	isabled'.	-
	Cable	equaliz	zer				Use a higher setting if there is signal loss at
	Bit 7	Bit d	5 E	Bit 5			higher frequencies because of the length of wire between the modem and the telephone
5	0	0		0	No	one	exchange when calling the number stored in
to	0	0		1	Lo	w	this Quick/Speed Dial. Also, try using the cable equalizer if one or
7	0	1		0	Med	dium	more of the following symptoms occurs.
	0	1		1	Hi	gh	• Communication error with error codes such as 0-20, 0-23, etc.
	1	1		1	Disa	bled	 Modem rate fallback occurs frequently.

	Switch 01	
No	Function	Function
		↓ Note
		 Do not use settings other than listed on the left.
		 If the setting is "Disabled", the bit switch setting is used.

	Switch 02								
No			Functior	ı		Comments			
	Initial T	x modem	rate (kbp	os)					
	Bit 3	Bit 2	Bit 1	Bit O					
	0	0	0	0	Not used				
	0	0	0	1	2.4				
	0	0	1	0	4.8				
	0	0	1	1	7.2	If training with a particular remote terminal always takes too long, the initial modem rate may be too			
	0 1 0 0 9.6 0 1 0 1 12.0	9.6	high. Reduce the initial Tx modem rate using these bits.						
0		12.0	For the settings 14.4 or kbps slower, Switch 04 bit						
to 3	0	1	1	0	14.4	4 must be changed to 0.			
3	0	1	1	1	16.8	• Other settings: Not used			
	1	0	0	0	19.2	If the setting is "Disabled", the bit switch setting is			
	1	0	0	1	21.6	used.			
	1	0	1	0	24.0				
	1	0	1	1	26.4				
		28.8							
		31.2							
	If all bi	ts are at '	1′, the set	tting is 'Di	sabled'				

	Switch 02					
No	Function	Comments				
	V Note					
	• Other settings: Not used					
4-7	Not used	Do not change the settings.				

			Switch 03	
No			Function	Comments
	Inch-mm	conversior	n before tx	
	Bit 1	Bit O	Setting	The machine uses inch-based resolutions for scanning. If "inch only" is selected, the
	0	0	Inch-mm conversion available	printed copy may be slightly distorted at the
0-1	0	1	Inch only	other end if that machine uses mm-based resolutions.
	1	0	Not used	If the setting is "Disabled", the bit switch
	1	1	Disabled	setting is used.
	DIS/NSF	detection	method	
	Bit 3	Bit 2	Setting	(0, 1): Use this setting if echoes on the line
	0	0	First DIS or NSF	are interfering with the set-up protocol at the start of transmission. The machine will then
2-3	0	1	Second DIS or NSF	wait for the second DIS or NSF before sending DCS or NSS.
	1	0	Not used	If the setting is "Disabled", the bit switch
	1	1	Disabled	setting is used.
4	V.8 proto 0: Off 1: Disabl			If transmissions to a specific destination always end at a lower modem rate (14,400 bps or lower), disable V.8 protocol so as not to use V.34 protocol. 0: V.34 communication will not be possible. If the setting is "Disabled", the bit switch setting is used.

			Switch 03			
No			Function	Comments		
5	Compres 0: MH or		s available in transmit mode	This bit determines the capabilities that are informed to the other terminal during transmission.		
	1: Disabl	ed		If the setting is "Disabled", the bit switch setting is used.		
	ECM dur	ing transm	ission	For example, if ECM is switched on but is		
	Bit 7	Bit 6	Setting	not wanted when sending to a particular		
6	0	0	Off	terminal, use the (0, 0) setting. Note that V.8/V.34 protocol and JBIG		
7	0	1	On	compression are automatically disabled if		
	1	0	Not used	ECM is disabled. If the setting is "Disabled", the bit switch		
	1	1	Disabled	setting is used.		

Switch 04 - Not used (do not change the settings)	
Switch 05 - Not used (do not change the settings)	
Switch 06 - Not used (do not change the settings)	
Switch 07 - Not used (do not change the settings)	
Switch 08 - Not used (do not change the settings)	
Switch 09 - Not used (do not change the settings)	

E-mail Parameters

The initial settings of the following e-mail parameters are all "0" (all parameters disabled).

Switch 00		
No	Function	Comments
0	HM Compression mode for e- mail attachments 0: Off	Switches HM compression on and off for files attached to e- mails for sending.

Switch 00		
No	Function	Comments
	1: On	
1	HR Compression mode for e- mail attachments 0: Off 1: On	Switches HR compression on and off for files attached to e- mails for sending.
2	MMR Compression mode for e-mail attachments 0: Off 1: On	Switches MMR compression on and off for files attached to e-mails for sending.
3-6	Not used	Do not change these settings.
7	Designates the bits to reference for compression method of e-mail attachments 0: Registered (Bit 0 to 6) 1: No registration.	The "0" selection (default) references the settings for Bits 00, 01, 02 above. The "1" selection ignores the selections of Bits 00, 01, 02.

Switch 01		
No	Function	Comments
0	Original width of e-mail attachment: A4 0: Off 1: On	Sets the original width of the e-mail attachment as A4.
1	Original width of e-mail attachment: B4 0: Off 1: On	Sets the original width of the e-mail attachment as B4.
2	Original width of e-mail attachment: A3 0: Off 1: On	Sets the original width of the e-mail attachment as A3.

Switch 01		
No	Function	Comments
3-6	Not used	Do not change these settings.
7	Designates the bits to reference for original size of e-mail attachments O: Registered (Bit 0 to 6) 1: No registration.	The "0" selection (default) references the settings for Bits 00, 01, 02 above. The "1" selection ignores the selections of Bits 00, 01, 02.

	Switch 02		
No	Function	Comments	
0	Line resolution of e-mail attachment: 200 x 100 0: Off 1: On	Sets the line resolution of the e-mail attachment as 200 x 100.	
1	Line resolution of e-mail attachment: 200 x 200 0: Off 1: On	Sets the line resolution of the e-mail attachment as 200 x 200.	
2	Line resolution of e-mail attachment: 200 x 400 0: Off 1: On	Sets the line resolution of the e-mail attachment as 200 x 400.	
3	Not used	Do not change these settings.	
4	Line resolution of e-mail attachment: 400 x 400 0: Off 1: On	Sets the line resolution of the e-mail attachment as 400 x 400.	
5-6	Not used	Do not change these settings.	
7	Designates the bits to reference for original size of e-mail attachments	The "0" selection (default) references the settings for Bits 00, 01, 02, 04 above. The "1" selection ignores the selections of Bits 00, 01, 02, 04.	

Switch 02		
No	Function	Comments
	0: Registered (Bit 0 to 6)	
	1: No registration.	

Switch 03 - Not used (do not change the settings)
Switch 04 - Not used (do not change the settings)
Switch 05 - Not used (do not change the settings)
Switch 06 - Not used (do not change the settings)
Switch 07 - Not used (do not change the settings)
Switch 08 - Not used (do not change the settings)
Switch 09 - Not used (do not change the settings)

Service RAM Addresses

Note

• Do not change the settings which are marked as "Not used" or "Read only."

680001 to 680004(H) - ROM version (Read only)

- 680001(H) Revision number (BCD)
- 680002(H) Year (BCD)
- 680003(H) Month (BCD)
- 680004(H) Day (BCD)

680006 to 680015(H) - Machine's serial number (16 digits - ASCII)

680018(H) - Total program checksum (low)

680019(H) - Total program checksum (high)

680020 to 68003F(H) - System bit switches

680050 to 68005F(H) - Printer bit switches

680060 to 68007F(H) - Communication bit switches

680080 to 68008F(H) - G3 bit switches

680090 to 68009F(H) - G3-2 bit switches

6800A0 to 6800AF(H) - G3-3 bit switches

6800D0(H) - User parameter switch 00 (SWUER_00): Not used

6800D1(H) - User parameter switch 01 (SWUSR_01): Not used

6800D2(H) - User parameter switch 02 (SWUSR_02)

- Bit 0: Forwarding mark printing on forwarded messages, 0: Disabled, 1: Enabled
- Bit 1: Center mark printing on received copies (this switch is not printed on the user parameter list), 0: Disabled, 1: Enabled
- Bit 2: Reception time printing (this switch is not printed on the user parameter list), 0: Disabled, 1: Enabled
- Bit 3: TSI print on received messages, 0: Disabled, 1: Enabled
- Bit 4: Checkered mark printing (this switch is not printed on the user parameter list), 0: Disabled, 1: Enabled
- Bit 5: Not used
- Bit 6: Not used
- Bit 7: Not used

6800D3(H) - User parameter switch 03 (SWUSR_03: Automatic report printout)

• Bit 0: Transmission result report (memory transmissions), 0: Off, 1: On

- Bit 1: Not used
- Bit 2: Memory storage report, 0: Off, 1: On
- Bit 3: Polling reserve report (polling reception), 0: Off, 1: On
- Bit 4: Polling result report (polling reception), 0: Off, 1: On
- Bit 5: Transmission result report (immediate transmissions), 0: Off, 1: On
- Bit 6: Polling clear report, 0: Off, 1: On
- Bit 7: Journal, 0: Off, 1: On

6800D4(H) - User parameter switch 04 (SWUSR_04: Automatic report printout)

- Bit 0: Automatic confidential reception report output, 0: Off, 1: On
- Bit 1: Automatic communication failure report and transfer result report output, 0: Off, 1: On
- Bits 2 to 3: Not used
- Bit 4: Indicates the parties, 0: Not indicated, 1: Indicated
- Bit 5: Include sender's name on reports, 0: Off, 1: On
- Bit 6: Not used
- Bit 7: Inclusion of a sample image on reports, 0: Off, 1: On

6800D5(H) - User parameter switch 05 (SWUSR_05)

- Bit 0: Substitute reception when the base copier is in an SC condition, 0: Enabled, 1: Disabled
- Bits 1 and 2: Condition for substitute rx when the machine cannot print messages (Paper end, toner end, jam, and during night mode)

Bit 2	Bit 1	Setting
0	0	The machine receives all the fax messages.
0	1	The machine receives fax messages with RTI or CSI.
1	0	The machine receives fax messages with the same ID code.
1	1	The machine does not receive anything.

- Bit 3: Not used
- Bit 4: Not used
- Bit 5: Just size printing, 0: Off, 1: On
- Bit 6: Not used
- Bit 7: Add paper display when a cassette is empty. 0: Off, 1: On

6800D6(H) - User parameter switch 06 (SWUSR_06)

- Bits 0 to 5: Not used
- Bit 6: Scan sequence in Book transmission, 0: Left page then right page, 1: Right page then left page

• Bit 7: Not used

6800D7(H) - User parameter switch 07 (SWUSR_07)

- Bits 0 and 1: Not used
- Bit 2: Parallel memory transmission, 0: Off, 1: On
- Bits 3 to 7: Not used

6800D8(H) - User parameter switch 08 (SWUSR_08)

- Bits 0 and 1: Not used
- Bit 2: Authorized reception
 - 0: Only faxes from senders whose RTIs/CSIs are specified for this feature are accepted.
 - 1: Only faxes from senders whose RTIs/CSIs are not specified for this feature are accepted.
- Bits 3 to 7: Not used

6800D9(H) - User parameter switch 09 (SWUSR_09): Not used

6800DA(H) - User parameter switch 10 (SWUSR_OA)

- Bit 0: Not used
- Bit 1: 2 into 1, 0: Off, 1: On
- Bit 2: Not used
- Bit 3: Page reduction, 0: Off, 1: On
- Bit 4: Not used
- Bit 5: Reception file printout, 0: Disabled, 1: Enabled
- Bit 6: Use both e-mail notification and printed reports to confirm the transmission results, 0: Off, 1: On
- Bit 7: Not used

6800DB(H) - User parameter switch 11 (SWUSR_OB)

- Bit 0: Not used
- Bit 1: Not used
- Bits 2 to 5: Not used
- Bit 6: Printout of messages received while acting as a forwarding station, 0: Off, 1: On
- Bit 7: Polling Standby duration, 0: Once, 1: No limit

6800DC(H) - User parameter switch 12 (SWUSR_OC): Not used

6800DD(H) - User parameter switch 13 (SWUSR_0D): Not used

6800DE(H) - User parameter switch 14 (SWUSR_OE)

- Bit 0: Message printout while the machine is in Night Printing mode, 0: On, 1: Off
- Bit 1: Maximum document length detection

0: Double letter, 1: Longer than double-letter (well log) – up to 1,200 mm

- Bit 2: Batch transmission, 0: Off, 1: On
- Bit 3: Fax mode settings, such as resolution, before a mode key (Copy, Fax, Printer, or Scanner) is pressed, 0: Not cleared, 1: Cleared
- Bits 4 to 6: Not used
- Bit 7: Manual service call (sends the system parameter list to the service station), 0: Off, 1: On

6800DF(H) - User parameter switch 15 (SWUSR_OF)

Note

• This switch is not printed on the user parameter list.

Bits 0, 1 and 2: Cassette for fax printout

Bit 2	Bit 1	Bit O	Setting
0	0	1	1 st paper feed station
0	1	0	2nd paper feed station
0	1	1	3rd paper feed station
1	0	0	4th paper feed station
1	0	1	LCT

Other settings: Not used

- Bits 3 and 4: Not used
- Bit 5: Using the cassette specified by bits 0, 1 and 2 above only, 0: On, 1: Off
- Bits 6 and 7: Not used

6800E0(H) - User parameter switch 16 (SWUSR_10)

Vote

- This switch is not printed on the user parameter list.
- Bits 0 and 1: Not used
- Bit 2: Paper size selection priority for an A4 size fax message when A4/LT size paper is not available,
 O: A3 has priority, 1: B4 has priority
- Bits 3 to 7: Not used

6800E1(H) - User parameter switch 17 (SWUSR_11)

• Bit 0: IFAX Group Destination Selection/Release Method

0 Priority Select Mode

	Select the priority destination according to input mode. The Group button reflects either email or fax input mode. Released as soon as the entry mode is selected, regardless of the current entry mode.
1	All Select Mode
	Acquires all registered members regardless of entry mode. If both email and fax are registered, both are selected. The Group button reflects either email or fax input mode. All registered members are released, regardless of the entry mode. If both email/fax are registered, both are released.

- Bit 1: Not used
- Bit 2: Inclusion of the "Add" button when a sequence of Quick/Speed dials is selected for broadcasting, 0:Not needed, 1: Needed
- Bits 3 to 6: Not used
- Bit 7: Press "Start" key without an original when using the on hook dial or the external telephone
 - 0: Displays "Cannot detect original size"
 - 1: Receives fax messages.

6800E2(H) - User parameter switch 18 (SWUSR_12)

- Bit 0: TTI date, 0: Off, 1: On
- Bit 1: TTI sender, 0: Off, 1: On
- Bit 2: TTI file number, 0: Off, 1: On
- Bit 3: TTI page number, 0: Off, 1: On
- Bit 4 to 7: Not used

6800E3(H) - User parameter switch 19 (SWUSR_13)

- Bit 0: Offset sort function for the fax (only using the shift tray on the 1,000 sheet finisher), 0: Disabled, 1: Enabled
- Bit 1: Journal format

O: The Journal is separated into transmissions and receptions

- 1: The Journal is separated into G3-1, G3-2, and G3-3 communications
- Bit 2: Action when the paper cassette that was selected by the specified cassette selection feature becomes empty.

(This switch is not printed on the user parameter list.)

0: The machine will not print any received files until paper is added.

1: The machine will use other cassettes to print received files that are not specified by this feature.

• Bit 3: 90° image rotation during B5 portrait Tx, 0: Off, 1: On

(This switch is not printed on the user parameter list.)

147

- Bit 4: Reduction of sample images on reports to 50% in the main scan and sub-scan directions. (This switch is not printed on the user parameter list.)
 - O: Technician adjustment (printer switch OE bits 3 and 4)
 - 1: 50% reduction
- Bit 5: Use of A5 size paper for reports (This switch is not printed on the user parameter list.)
 Off, 1: On
- Bits 6 and 7: Not used

6800E4(H) - User parameter switch 20 (SWUSR_14)

- Bit 0: Automatic printing of the LAN fax result report, 0: Off, 1: On
- Bit 1: Not used
- Bits 2 to 5: Store documents in memory which could not be printed from PC fax (LAN fax) driver

Bit 5	Bit 4	Bit 3	Bit 2	Setting (minutes)
0	0	0	0	0
0	0	0	1	1
and so on, until				
1	1	1	0	14
1	1	1	1	15

• Bits 6 and 7: Not used.

6800E5(H) - User parameter switch 21 (SWUSR_15)

- Bit 0: Print results of sending reception notice request message, 0: Disabled (print only when error occurs), 1: Enabled
- Bit 1: Respond to e-mail reception acknowledgment request, 0: Disabled, 1: Enabled
- Bit 2: Not used
- Bit 3: File format for forwarded folders, 0: TIFF, 1:PDF
- Bit 4: Transmit Journal by E-mail, O: Disabled, 1: Enabled
- Bit 5: Not used
- Bit 6: Network error display, 0: Displayed, 1: Not displayed
- Bit 7: Transmit error mail notification, 0: Enabled, 1: Disabled

6800E6(H) - User parameter switch 22 (SWUSR_16)

Note

• This switch is not printed on the user parameter list.

- Bit 0: Dial tone detection (PSTN 1), 0: Disabled, 1: Enabled
- Bit 1: Dial tone detection (PSTN 2), 0: Disabled, 1: Enabled
- Bit 2: Dial tone detection (PSTN 3), 0: Disabled, 1: Enabled
- Bits 3 to 7: Not used

6800E7(H) - User parameter switch 23 (SWUSR_17) : Not used

6800E8(H) - User parameter switch 24 (SWUSR_18)

• Bits 0 and 1: File retention time (Cross reference: System switch 02 bit 4)

Bit 1	Bit O	Setting
0	0	File retention impossible
0	1	24 hours
1	0	File retention impossible
1	1	72 hours

• Bits 2 to 7: Not used

6800E9(H) - User parameter switch 25 (SWUSR_19)

- Bit 0 and 1: Not used
- Bit 2: Not used
- Bit 3: Not used
- Bit 4: RDS operation

0: Not acceptable

1: Acceptable for the limit specified by system switch 03

Note

- This bit is only effective when RDS operation can be selected by the user (see system switch 02).
- Bits 5 to 7: Not used

6800EA(H) to 6800EF(H) - User parameter switches 26 to 31 (SWUSR_1A to 1F): Not used

6800F0(H) - User parameter switch 32 (SWUSR_20)

• Bit 0: Quotation priority for a destination when there is no destination of the specified type

0: Paper output priority

Priority order

- 1. IP-fax destination, 2. Fax Number, 3. E-mail address, 4. Folder
- 1: Electric output order

Priority order

- 1. E-mail address, 2. Folder, 3. IP-fax destination, 4. Fax number
- Bits 1 to 7: Not used

6800F1(H) - User parameter switch 33 (SWUSR_21): Not used

- 6800F2(H) User parameter switch 34 (SWUSR_22)
 - Bit O: Gatekeeper server used with IP-Fax, O: Disabled, 1: Enabled
 - Bit 1: SIP server used with IP-Fax, 0: Disabled, 1: Enabled

680100 to 68010F(H) - G4 Parameter Switches – Not used

680110 to 68012F(H) - G4 Internal Switches – Not used

- 680170 to 68017F(H) IFAX Switches
- 680180 to 68018F(H) IP-FAX Switches
- 680190 to 6801AF(H) Service station's fax number (SP3-101)
- 6801B0 to 6801B9(H) Own fax PABX extension number
- 6801BA to 6801C3(H) Own fax number (PSTN)
- 6801C4 to 6801D7(H) Own fax number (ISDN G4) Not used
- 6801D8 to 6801E3(H) The first subscriber number (ISDN G3) Not used
- 6801E4 to 6801EF(H) The second subscriber number (ISDN G3) Not used
- 6801F0 to 6801FB(H) The first subscriber number (ISDN G4) Not used
- 6801FC to 680207(H) The second subscriber number (ISDN G4) Not used
- 680208 to 68021B(H) PSTN-1 RTI (Max. 20 characters ASCII) See the following note.
- 68021C to 68022F(H) PSTN-2 RTI (Max. 20 characters ASCII) See the following note.
- 680230 to 680246(H) PSTN-3 RTI (Max. 20 characters ASCII) See the following note.
- 680247 to 680286(H) TTI 1 (Max. 64 characters ASCII) See the following note.
- 680287 to 6802C6(H) TTI 2 (Max. 64 characters ASCII) See the following note.
- 6802C7 to 680306(H) TTI 3 (Max. 64 characters ASCII) See the following note.
- 680307 to 68031A(H) PSTN-1 CSI (Max. 20 characters ASCII)
- 68031B to 68032E(H) PSTN-2 CSI (Max.20 characters ASCII)
- 68032F to 680342(H) PSTN-3 CSI (Max.20 characters ASCII)
- 680343(H) Number of PSTN-1 CSI characters (Hex)
- 680344(H) Number of PSTN-2 CSI characters (Hex)
- 680345(H) Number of PSTN-3 CSI characters (Hex)-
 - If the number of characters is less than the maximum (20 for RTI, 64 for TTI), add a stop code (00[H]) after the last character.

680380 to 680387(H) - Last power off time (Read only)

Service RAM Addresses

- 680380(H) 01(H) 24-hour clock, 00(H) 12-hour clock (AM), 02(H) 12-hour clock (PM)
- 680381(H) Year (BCD)
- 680382(H) Month (BCD)
- 680383(H) Day (BCD)
- 680384(H) Hour
- 680385(H) Minute
- 680386(H) Second
- 680387(H) 00: Monday, 01: Tuesday, 02: Wednesday, . . . and so on until . . ., 06: Sunday

680394(H) - Optional equipment (Read only – Do not change the settings)

- Bit 0: Page Memory, 0: Not installed, 1: Installed
- Bit 1: SAF Memory, 0: Not installed, 1: Installed
- Bits 2 to 7: Not used

680395(H) - Optional equipment (Read only – Do not change the settings)

- Bits 0 to 3: Not used
- Bit 4: G3-2, 0: Not installed, 1: Installed
- Bit 5: G3-3, 0: Not installed, 1: Installed
- Bit 6 and 7: Not used

680406 to 68040A - Option G3 board (G3-2) ROM information (Read only)

- 680406(H) Suffix (BCD)
- 680407(H) Version (BCD)
- 680408(H) Year (BCD)
- 680409(H) Month (BCD)
- 68040A(H) Day (BCD)

68040B to 68040F - Option G3 board (G3-3) ROM information (Read only)

- 68040B(H) Suffix (BCD)
- 68040C(H) Version (BCD)
- 68040D(H) Year (BCD)
- 68040E(H) Month (BCD)
- 68040F(H) Day (BCD)

680410(H) - G3-1 Modem ROM version (Read only)

680412(H) - G3-2 Modem ROM version (Read only)

680414(H) - G3-3 Modem ROM version (Read only)

680420(H) - Number of multiple sets print (Read only)

- 680476(H) Time for economy transmission (hour in 24h clock format BCD)
- 680477(H) Time for economy transmission (minute BCD)
- 680492(H) Transmission monitor volume, 00 07(H)
- 680493(H) Reception monitor volume, 00 07(H)
- 680494(H) On-hook monitor volume, 00 07(H)
- 680495(H) Dialing monitor volume, 00 07(H)
- 680496(H) Buzzer volume, 00 07(H)
- 680497(H) Beeper volume, 00 07(H)

69ED04 to 69F003(H) - SIP server address (Read only)

- 69ED04(H) Proxy server Main (Max. 128 characters ASCII)
- 69ED84(H) Proxy server Sub (Max. 128 characters ASCII)
- 69EE04(H) Redirect server Main (Max. 128 characters ASCII)
- 69EE84(H) Redirect server Sub (Max. 128 characters ASCII)
- 69EF04(H) Registrar server Main (Max. 128 characters ASCII)
- 69EF84(H) Registrar server Sub (Max. 128 characters ASCII)
- 69F004(H) Gatekeeper server address Main (Max. 128 characters ASCII)
- 69F084(H) Gatekeeper server address Sub (Max. 128 characters ASCII)
- 69F104(H) Alias Number (Max. 128 characters ASCII)
- 69F184(H) SIP user name (Max. 128 characters ASCII)
- 69F204(H) Gateway address information (Max. 128 characters ASCII)
- 6A0DC0(H) Stand-by port number for H.232 connection
- 6A0DC2(H) Stand-by port number for SIP connection
- 6A0DC4(H) RAS port number
- 6A0DC6(H) Gatekeeper port number
- 6A0DC8(H) Port number of data waiting for T.38
- 6A0DCA(H) Port number of SIP server
- 6A0DCC(H) Priority for SIP and H.323, 0: H.323, 1: SIP
- 6A0DCD(H) SIP function, 0: Disabled, 1: Enabled
- 6A0DCE(H) H.323 function, O: Disabled, 1: Enabled
- 6BEBFE(H) Dial tone detection frequency Upper limit (High)
- Defaults: NA: 06, EU: 06, ASIA: 06
- 6BEBFF(H) Dial tone detection frequency Upper Limit (Low)
- Defaults: NA: 50, EU: 50, ASIA: 50

6BECOO(H) - Dial tone detection frequency – Lower Limit (High)

Defaults: NA: 03, EU: 02, ASIA: 02

6BEC01(H) - Dial tone detection frequency – Lower Limit (Low)

Defaults: NA: 60, EU: 90, ASIA: 90

6BEC02(H) - Dial tone detection waiting time (20 ms)

Defaults: NA: 64, EU 64, ASIA: 64

6BEC03 to 6BEC04 - Dial tone detection monitoring time (20 ms)

Defaults

Area	6BEC03	6BEC04
NA	F4	01
EU	F4	01
ASIA	F4	01

6BEC05(H) - Dial tone detect judge time (20 ms)


Defaults: NA: 64, EU: 1B, ASIA: 32

6BECO6(H) - Dial tone disconnect permission time (20 ms)

Defaults: NA: 11, EU: OF, ASIA: 11

4. Service Table

Overview



The basic fax unit consists of two PCBs: an FCU and an MBU.


The FCU controls all the fax communications and fax features, in cooperation with the controller board. The MBU contains the ROM and SRAM. Also, the FCU has an NCU circuit.

Fax Options:

- Extra G3 Interface option: This provides one more analog line interface. This allows full dual access. Two extra G3 interface options can be installed.
- Memory Expansion: This expands the SAF memory and the page memory (used for image rotation); without this expansion, the page memory is not big enough for image rotation at 400 dpi, so transmission at 400 dpi is not possible.

Boards

FCU



The FCU (Facsimile Control Unit) controls fax communications, the video interface to the base copier's engine, and all the fax options.

FACE3 (Fax Application Control Engine)

- CPU
- Data compression and reconstruction (DCR)
- DMA control
- Clock generation
- DRAM backup control

Modem (FAME)

• V.34, V33, V17, V.29, V.27ter, V.21, and V.8

DRAM

- The 16 MB of DRAM is shared as follows.
 - SAF memory: 4MB
 - Working memory: 4MB
 - Page memory: 8MB

• The SAF memory is backed up by a rechargeable battery.

Memory Back-up

• A rechargeable battery backs up the SAF memory (DRAM) for 1 hour.

MBU

On this board, the flash ROM contains the FCU firmware, and the SRAM contains the system data and user parameters. Even if the FCU is changed, the system data and user parameters are kept on the MBU board.

ROM

- 3MB flash ROMs for system software storage
- 2MB (16bit x 1MB) + 1MB (16bit x 512K)

SRAM

• The 256 KB SRAM for system and user parameter storage is backed up by a lithium battery.


Memory Back-up

• A lithium battery backs up the system parameters and programmed items in the SRAM, in case the base copier's main switch is turned off.

Switches

ltem	Description
SW1	Switches the SRAM backup battery on/off.

SG3 Board



The SG3 board allows up to three simultaneous communications when used in combination with the FCU and optional G3 boards. The NCU is on the same board as the common SG-3 board. This makes the total board structure smaller. But, the specifications of the SG3 board do not change.

NCCP (New Communication Control Processor)

- Controls the SG3 board.
- CPU (RU30)
- DPRAM (Dual Port RAM): Handshaking with the FCU is done through this block.
- DMA controller
- JBIG
- DSP V34 modem (RL5T892): Includes the DTMF Receiver function
- DCR for MH, MR, MMR, and JBIG compression and decompression

FROM

• 1 Mbyte flash ROM for SG3 software storage and modem software storage

SDRAM

• 4Mbyte DRAM shared between ECM buffer, line buffer, and working memory

AFE (Analog Front End)

158

• Analog processing

CODEC (COder-DECoder)


• A/D & D/A conversions for modem

REG

• Generates +3.3 V from the +5V from the FCU

Video Data Path

Transmission



Memory Transmission and Parallel Memory Transmission

The base copier's scanner scans the original at the selected resolution in inch format. The IPU processes the data and transfers it to the FCU.

Vote

• When scanning a fax original, the IPU uses the MTF, independent dot erase and thresholding parameter settings programmed in the fax unit's scanner bit switches, not the copier's SP modes.

Then, the FCU converts the data to mm format, and compresses the data in MMR or raw format to store it in the SAF memory. If image rotation will be done, the image is rotated in page memory before compression.

At the time of transmission, the FCU decompresses the stored data, then re-compresses and/or reduces the data if necessary for transmission. The NCU transmits the data to the line.

Immediate Transmission

The base copier's scanner scans the original at the resolution agreed with the receiving terminal. The IPU video processes the data and transfers it to the FCU.

Note

• When scanning a fax original, the IPU uses the MTF, independent dot erase and thresholding parameter settings programmed in the fax unit's scanner bit switches, not the copier's SP modes.

Then the FCU stores the data in page memory, and compresses the data for transmission. The NCU transmits the data to the line.

JBIG Transmission


Memory transmission: If the receiver has JBIG compression, the data goes from the DCR to the QM-Coder. Then the NCU transmits the data to the line. When an optional G3 unit (SG3) is installed and PSTN2 is selected as the line type, JBIG compression is available, but only for the PSTN-2 line.

Immediate transmission: If the receiver has JBIG compression, the data goes from the page memory to the QM-Coder. Then the NCU transmits the data to the line. When an optional G3 unit (SG3) is installed and PSTN2 is selected as the line type, JBIG compression is available, but only for the PSTN-2 line.

Adjustments

• Priority for the line used for G3 transmissions (PSTN 1/PSTN 2 or 3): System switch 16 bit 1

Reception



First, the FCU stores the incoming data from either an analog line to the SAF memory. (The data goes to the FACE3 at the same time, and is checked for error lines/frames.)

The FCU then decompresses the data and transfers it to page memory. If image rotation will be done, the image is rotated in the page memory. The data is transferred to the IPU.

If the optional G3 unit is installed, the line that the message comes in on depends on the telephone number dialled by the other party (the optional G3 unit has a different telephone number from the main fax board).

JBIG Reception

When data compressed with JBIG comes in on PSTN-1 (the standard analog line), the data is sent to the QM-CODER for decompression. Then the data is stored in the page memory, and transferred to the IPU.

When data compressed with JBIG comes in on PSTN-2 (optional extra analog line), the data is sent to the QM-CODER on the SG3 board for decompression.


Fax Communication Features

Multi-port

When the optional extra G3 Interface Unit is installed, communication can take place at the same time through the two or three lines at once.

Option	Available Line Type	Available protocol Combinations
Standard only	PSTN	G3
Extra G3 Interface Unit (single)	PSTN + PSTN	G3 + G3
Extra G3 Interface Unit (double)	PSTN + PSTN +PSTN	G3 + G3 +G3

Document Server



The base copier's scanner scans the original at the selected resolution. The IPU video processes the data and transfers it to the controller board.

Then the controller stores the data in the page memory for the copier function, and compresses the data in MMR (by software) to store it in the HDD. If image rotation will be done, the image is rotated in the page memory before compression.

For transmission, the stored image data is transferred to the FCU. The FCU decompresses the image data, then recompresses and/or reduces the data if necessary for transmission. The NCU transmits the data to the line.

The documents can be stored in the HDD (Document Server) from the fax application. The stored documents in the document sever can be used for the fax transmission in many times. More than one document and the scanned document can be combined into one file and then the file can be transmitted.

- When using the document server, the SAF memory is not used.
- The document is compressed with MMR and stored.
- Up to 9,000 pages can be stored (1 file: Up to 1,000 pages) from the fax application.
- Only stored documents from the fax application can be transmitted.
- Scanned documents are given a name automatically, such as "FAXOO1". But it is possible to change the file name, user name and password.
- Up to 30 files can be selected at once.

Note

- The compression method of the fax application is different from the copy application. The storing time is longer than the copier storing.
- When selecting "Print 1 st page", the stored document will be reduced to A4 size.

Internet Mail Communication

Mail Transmission

T.37 simple and full modes

This machine supports T.37 full mode. (ITU-RFC232). The difference between T.37 simple mode and full mode is as follows.

Function	T.37 Simple Mode	T.37 Full Mode
		200 x100
Develution	200 x 100	200 x 200
Resolution	200 x 200	200 x 400
		400 x 400 (if available)
RX Paper Width	A4	A4, B4, A3

Function	T.37 Simple Mode	T.37 Full Mode
RX Data Compression Method	мн	MH (default), MR, MMR,
Signals	Image data transmission only	Image data transmission, exchange of capability information between the two terminals, and acknowledgement of receipt of fax messages

Data Formats

The scanned data is converted into a TIFF-F formatted file.

The fields of the e-mail and their contents are as follows:

Field	Content
From	Mail address of the sender
Reply To	Destination requested for reply
То	Mail address of the destination
Всс	Backup mail address
Subject	From CSI or RTI (Fax Message No. xxxx)
Content Type	Multipart/mixed Attached files: image/tiff
Content Transfer Encoding	Base 64, 7-bit, 8-bit, Quoted Printable
Message Body	MIME-converted TIFF-F (MIME standards specify how files are attached to e-mail messages)

Direct SMTP Transmission

Internet Fax documents can be sent directly to their destinations without going through the SMTP server. (Internet Faxes normally transmit via the SMTP server.)

For example:

e-mail address:	gts@ricoh.co.jp
SMTP server address:	gts.abcd.com

In this case, this feature destination e-mail address (gts@ricoh.co.jp) is read as the SMTP server address "gts.abcd.com", and the transmissions bypass the SMTP server.

Selectable Options

These options are available for selection:

- With the default settings, the scan resolution can be either standard or detail. Inch-mm conversion before TX depends on IFAX SW01 Bit 7. Detail resolution will be used if Super Fine resolution is selected, unless Fine resolution is enabled with IFAX SW01.
- The requirements for originals (document size, scan width, and memory capacity) are the same as for G3 fax memory TX.
- The default compression is TIFF-F format.
- IFAX SW00: Acceptable paper widths for sending
- IFAX SW09: Maximum number of attempts to the same destination

Secure Internet Transmission

SMTP Authentication:

• User Tools> System Settings> File Transfer> SMTP Authentication

POP Before SMTP:

• User Tools> System Settings> File Transfer> POP Before SMTP

Mail Reception

Three Types

This machine supports three types of e-mail reception:

- POP3 (Post Office Protocol Ver. 3.)
- IMAP4 (Internet Messaging Access Protocol)
- SMTP (Simple Mail Transfer Protocol)

🕓 Note

 For details: Core Technology Manual – Facsimile Processes – Faxing from a PC – Internet/LAN Fax Boards – Mail Reception

POP3/IMAP4 Mail Reception Procedure

The machine automatically picks up e-mail from the server at an interval which is adjustable in the range 2 to 1440 min. in 1-minute steps:

• User Tools> System Settings> File Transfer> E-mail Reception Interval

SMTP Reception

The IFAX must be registered as an SMTP server in the MX record of the DNS server, and the address
of the received mail must specify the IFAX.

- 2. To enable SMTP reception: User Tools> System Settings> File Transfer> Reception Protocol
 - Even if the MX record on the DNS server includes the IFAX, mail cannot be received with SMTP until SMTP reception is enabled:
 - However, if SMTP reception is selected and the machine is not registered in the MX record of the DNS server, then either IMAP4 or POP3 is used, depending on the setting: User Tools> System Settings> File Transfer> Reception Protocol

Mail Delivery Conditions: Transferring Mail Received With SMTP

- 1. The machine must be set up for SMTP mail delivery:
 - User Tools> Facsimile Features> E-mail Settings> SMTP RX File Delivery Settings
- If the user wishes to limit this feature so that the machine will only deliver mail from designated senders, the machine's "Auth. E-mail RX" feature must be set (User Tools> Facsimile Features> E-mail Settings> SMTP RX File Delivery Settings).
- If the "SMTP RX File Delivery Setting" is set to 0 to prohibit SMTP receiving, and if there is mail designated for delivery, then the machine responds with an error. (User Tools> Facsimile Features> E-mail Settings> SMTP RX File Delivery Settings)
- 4. If the quick dial, speed dial, or group dial entry is incorrect, the mail transmission is lost, and the IFAX issues an error to the SMTP server and outputs an error report.

Auth. E-mail RX

In order to limit access to mail delivery with IFAX, the addresses of senders must be limited using the Access Limit Entry. Only one entry can be registered.

1. Access Limit Entry

For example, to limit access to @IFAX.ricoh.co.jp:

gts@IFAX.ricoh.co.jp	Matches and is delivered.
gts@IFAX.abcde.co.jp	Does not match and is not delivered.
IFAX@ricoh.co.jp	Does not match and is not delivered.

- 2. Conditions
 - The length of the Access Limit Entry is limited to 127 characters.
 - If the Access Limit Entry address and the mail address of the incoming mail do not match, the incoming mail is discarded and not delivered, and the SMTP server responds with an error. However, in this case an error report is not output.
 - If the Access Limit Entry address is not registered, and if the incoming mail specifies a delivery destination, then the mail is delivered unconditionally.

Handling Mail Reception Errors

Abnormal files

When an error of this type occurs, the machine stops receiving and commands the server to erase the message. Then the machine prints an error report and sends information about the error by e-mail to the sender address (specified in the "From" or "Reply-to" field of the message). If there is an incomplete received message in the machine memory, it will be erased.

The machine prints an error message when it fails to send the receive error notification after a certain number of attempts.

The following types of files are judged to be abnormal if one or more of the following are detected:

1. Unsupported MIME headers.

Supported types of MIME header

Header	Supported Types
Content-Type	Multipart/mixed, text/plain, message/rfc822 Image/tiff
Charset	US-ASCII, ISO 8859 X. Other types cannot be handled, and some garbage may appear in the data.
Content-Transfer-Encoding	Base 64, 7-bit, 8-bit, Quoted Printable

- 2. MIME decoding errors
- 3. File format not recognized as TIFF-F format
- 4. Resolution, document size, or compression type cannot be accepted

Remaining SAF capacity error

The machine calls the server but does not receive e-mail if the remaining SAF capacity is less than a certain value (the value depends on IFAX Switch 08. The e-mail will be received when the SAF capacity increases (for example, after substitute reception files have been printed). The error handling method for this type of error is the same as for "Abnormal files".

If the capacity of the SAF memory drops to zero during reception, the machine operates in the same way as when receiving an abnormal file (refer to "Abnormal files" above).

Secure Internet Reception

To enable password encryption and higher level security: User Tools> System Settings> File Transfer> POP3/IMAP4 Settings> Encryption (set to "On")

Transfer Request: Request By Mail

For details: Core Technology Manual – Facsimile Processes – Faxing from a PC – Internet/LAN Fax Boards – Transfer Request

The fields of the e-mail and their contents are as follows:

Field	Content
From	E-mail address of the requesting terminal
То	Destination address (Transfer Station address)
Всс	Backup mail address
Subject	From TSI (Fax Message No. xxxx)
Content-Type	Multipart/mixed Text/Plain (for a text part), image/tiff (for attached files)
Content-Transfer-Encoding	Base 64, 7-Bit, 8-bit, Quoted Printable
Mail body (text part)	RELAY-ID-: xxxx (xxxx: 4 digits for an ID code) RELAY: #01#*X#**01
Message body	MIME-converted TIFF-F.

E-Mail Options (Sub TX Mode)

The following features are available as options for mail sending: entering a subject, designating the level of importance, confirming reception of the mail.

Subject and Level of Importance

You can enter a subject message with: Sub TX Mode> E-mail Options

The Subject entry for the mail being sent is limited to 64 characters. The subject can also be prefixed with an "Urgent" or "High" notation.

Mail Type	Item 1		Item 2	ltem 3
Subject Entry		Entry Condition		Fax Message No.
No Subject		1. "CSI" ("RTI")		+
Entry		2. "RTI"	CSI not registered	File No.

- How the Subject Differs According to Mail Type -

Mail Type	Item 1		Item 2	Item 3	
		3. "CSI"	RTI not registered		
		4. None	CSI, RTI not registered		
		1. "CSI" ("RTI")		Normal:	
Confirmation of Reception	From	2. "RTI"	CSI not registered	Return Receipt (dispatched). You can select "displayed" with IFAX SW02 Bits 2 and 3.	
		3. "CSI"	RTI not registered	Error:	
		4. None	CSI, RTI not registered	Return Receipt (processed/error)	
	ivery, SMTP From g and	RTI or CSI of the station designated for delivery	Mail delivery		
Mail delivery, memory transfer, SMTP		RTI or CSI of sender	Mail sending from G3 memory	Fax Message No. + File Number	
receiving and delivery		Mail address of sender	Memory sending	Number	
		Mail address of sender	SMTP receiving and delivery (Off Ramp Gateway)		
Mail error notification		Error Message No. xxxx From CSI (RTI)			

Items 1, 2, and 3 in the table above are in the Subject.

- Subjects Displayed on the PC -

 Sender	▲ Date	🖌 Size 🗸	Subject	<u>.</u>
Substation 2 Substation 2			Parts List Specifications	
Main Station	05/09/2002		🗟 [Urgent] Memo 2041	
		21,624,288		1
				b766d907

E-mail Messages

After entering the subject, you can enter a message with: Sub TX Mode> E-mail Options

An e-mail message (up to 5 lines) can be pre-registered with: User Tools> System Settings> File Transfer> Program/Change/Delete E-mail Message

- Limitations on Entries -

ltem	Maximum
Number of Lines	5 lines
Line Length	80 characters
Name Length	20 characters

Message Disposition Notification (MDN)

For details: Core Technology Manual – Facsimile Processes – Faxing from a PC – Internet/LAN Fax Boards – E-mail Options

The network system administrator can confirm whether a sent mail has been received correctly or not. This confirmation is done in four steps.

- Send request for confirmation of mail reception. To enable or disable this request (known as MDN): Sub TX Mode> E-mail Options
- 2. Mail reception (receive confirmation request)
- 3. Send confirmation of mail reception
- 4. Receive confirmation of mail reception

The other party's machine will not respond to the request unless the two conditions below are met:

- The other party's machine must be set up to respond to the confirmation request.
- The other party's machine must support MDN (Message Disposition Notification).

- Setting up the Receiving Party -

The receiving party will respond to the confirmation request if:

- 1. The "Disposition Notification To" field is in the received mail header (automatically inserted in the 4th line in the upper table on the previous page, if MDN is enabled), and
- 2. Sending the disposition notification must be enabled (User Parameter Setting SW21 (15 [H]) Bit 1 for this model). The content of the response is as follows:

Normal reception:	"Return Receipt (dispatched)" in the Subject line
IFAX SW02 (Bit 2, 3)	"Return Receipt (displayed)" in the Subject line
Error:	"Return Receipt (processed/error)" in the Subject line

Handling Reports

- Sending a Request for a Return Receipt by Mail -

After the mail sender transmits a request for a return receipt, the mail sender's journal is annotated with two hyphens (--) in the Result column and a "Q" in the Mode column.

- Mail Receipt (Request for Receipt Confirmation) and Sending Mail Receipt Response -

After the mail receiver sends a response to the request for a return receipt, the mail receiver's journal is annotated with two hyphens (--) in the Result column and an "A" in the Mode column.

- Receiving the Return Receipt Mail -

- After the mail sender receives a return receipt, the information in the mail sender's journal about the receipt request is replaced, i.e. the journal is annotated with "OK" in the Result column.
- When the return receipt reports an error, the journal is annotated with an "E" in the Result column.
- The arrival of the return receipt is not recorded in the journal as a separate communication. Its arrival is only reported by the presence of "OK" or "E" in the Result column.
- If the mail address used by the sender specifies a mailing list (i.e., a Group destination; the machine sends the mail to more than one location. See "How to set up Mail Delivery"), the Result column of the Journal is updated every time a return receipt is received. For example, if the mailing list was to 5 destinations, the Result column indicates the result of the communication with the 5th destination only. The results of the communications to the first 4 destinations are not shown.

Exceptions:

If one of the communications had an error, the Result column will indicate E, even if subsequent communications were OK.

If two of the communications had an error, the Journal will indicate the destination for the first error only.

- Report Sample -

DATE	TIME		TIME	PAGE
		RESULT		
MAY. 5	10:15	fuser_01@dom1g. ricoh. co. Mail SM (09"	2
	10:16	fuser_01@dom1g. $\bar{ ext{ricoh}}$. co. Mail SMQ 0	'05 "	1
	10:17	s_tadashi@dom1g. ricoh. co. Mail SMQ 0	'09"	2
	10:19	m_masataka@dom1g. ricoh. co. Mail SMA	0'05"	1

b771d506

IP-Fax

What is IP-FAX?

For details: Core Technology Manual – Facsimile Processes – Faxing from a PC – Internet/LAN Fax Boards – IP-FAX

T.38 Packet Format

TCP is selected by default for this machine, but you can change this to UDP with IPFAX SW 00 Bit 1.

UDP Related Switches

	IP-Fax Switch 01							
No.	Function					Comments		
	Select IF	P FAX Del	ay Level			Raise the level by selecting a higher setting if too		
	Bit 3	Bit 2	Bit 1	Bit O	Level	many transmission errors are occurring on the network.		
	0	0	0	0	0	If TCP/UDP is enabled on the network, raise this		
0-3	0	0	0	1	1	setting on the T.30 machine. Increasing the delay time allows the recovery of more lost		
	0	0	1	0	2	packets.		
						If only UDP is enabled, increase the number of redundant packets.		
	0 0 1 1	3	Level 1~2: 3 Redundant packets					
			Level 3: 4 Redundant packets					

Settings

User parameter switch 34 (22[H]), bit 0

IP-Fax Gate Keeper usage, 0: No, 1: Yes

IP Fax Switches: Various IP-FAX settings (see the bit switch table)

General Specifications

Туре:	Desktop type transceiver				
Circuit	PSTN (max. 3ch.)				
Circuit:	PBX				
Connection:	Direct couple				
	Book (Face down)				
	Maximum Length: 432 mm [17 ins]				
	Maximum Width: 297 mm [11.7 ins]				
	ARDF (Face up)				
0	Single-sided document				
Original Size:	• Length: 128 - 1200 mm [5.0 - 47.2 ins]				
	• Width: 105 - 297 mm [4.1 - 11.7 inch]				
	Double-sided document				
	• Length: 128 - 432 mm [5.0 - 17 inch]				
	• Width: 105 - 297 mm [4.1 - 11.7 inch]				
Scanning Method:	Flat bed, with CCD				
	G3				
	• 8 x 3.85 lines/mm (Standard)				
	• 8 x 7.7 lines/mm (Detail)				
	• 8 x 15.4 line/mm (Fine) Note1				
Resolution:	 16 x15.4 line/mm (Super Fine) See Note. 				
	• 200 x 100 dpi (Standard)				
	• 200 x 200 dpi (Detail)				
	 400 x 400 dpi (Super Fine) Note - Optional Expansion Memory required. 				
Transmission Time:	G3: 3 s at 28800 bps; Measured with G3 ECM using memory for an ITU- T #1 test document (Slerexe letter) at standard resolution				
Data Compression:	MH, MR, MMR				

	JBIG
Protocol:	Group 3 with ECM
Modulation:	V.34, V.33, V.17 (TCM), V.29 (QAM), V.27ter (PHM), V.8, V.21 (FM)
Data Rate:	G3: 33600/31200/28800/26400/24000/21600/ 19200/16800/14400/12000/9600/7200/4800/2400 bps Automatic fallback
I/O Rate:	With ECM: 0 ms/line Without ECM: 2.5, 5, 10, 20, or 40 ms/line
Memory Capacity:	ECM: 128 KB SAF • Standard: 4 MB • With optional Expansion Memory: 28 MB (4 MB+ 24 MB) Page Memory • Standard: 4 MB (Print: 2 MB + Scanner: 2 MB) • With optional Expansion Memory: 12 MB (4 MB + 8 MB) (Print 8 MB + Scanner: 4 MB)

Capabilities of Programmable Items

The following table shows how the capabilities of each programmable item will change after the optional Fax Function Upgrade Unit is installed.

ltem	Standard
Quick Dial	2000
Groups	100
Destination per Group	500
Destinations dialed from the ten-key pad overall	500
Programs	100
Auto Document	6
Communication records for Journal stored in the memory	200
Specific Senders	30

The following table shows how the capabilities of the document memory will change after the optional Fax Function Upgrade Unit and the Expansion Memory are installed.

	Without the Expansion Memory	With the Expansion Memory
Memory Transmission files	400	400
Maximum number of pages for memory transmission	1000	1000
Memory capacity for memory transmission (see the Note below)	320	2240

Note

• Measured using an ITU-T #1 test document (Slerexe letter) at standard resolution, with auto image density mode, and in Text mode.


IFax Specifications

Connectivity	
Local area network	
Ethernet 100base-Tx/10base-T	
IEEE1394 (IP over 1394)	
IEEE802.11b (wireless LAN)	
Resolution	
Main scan: 400 dpi, 200 dpi	
Sub scan: 400 dpi, 200 dpi, 100 dpi	Protocol
Note: To use 400 dpi, IFAX SW01 Bit 4 must be	Transmission: SMTP, TCP/IP
set to "1".	Reception: POP3, SMTP, IMAP4, TCP/IP
Transmission Time	Data rate
1 s (through a LAN to the server)	100 Mbps(100base-Tx)
Conditions:	10 Mbps (10base-T)
 ITU-T #1 test document (Slerexe Letter) 	Authentication method
MTF correction: OFF	SMTP-AUTH
• TTI: None	POP before SMTP
• Resolution: 200 x 100 dpi	A-POP
Communication speed: 10 Mbps	Remark
Correspondent device: E-mail server	The machine must be set up as an e-mail client
• Line conditions: No terminal access	before installation. Any client PCs connected to the machine through a LAN must also be e-mail clients, or some features will not work (e.g. Autorouting).
Document Size	
Maximum message width is A4/LT.	
Note: To use B4 and A3 width, IFAX SW00 Bit 1 (B4) and/or Bit 2 (A3) must be set to "1".	
E-mail File Format	
Single/multi-part	
MIME conversion	
Image: TIFF-F (MH, MR, MMR)	

IP-Fax Specifications

Network:	LAN: Ethernet/10base-T, 100base-TX IEEE1394 (IP over 1394), IEEE802.11b (wireless LAN)		
Scan line density:	8 x 3.85 lines/mm, 200x100dpi (standard character), 8 x 7.7lines/mm, 200x200dpi (detail character), 8 x 15.4lines/mm (fine character: optional expansion memory required), 16 x 15.4lines/mm, 400x400dpi (super fine character: optional expansion memory required)		
Original size:	Maximum A3 or 11"x 17" (DLT)		
Maximum scanning size:	Standard: A3, 297mm x 432mm Irregular: 297mm x 1200mm		
Transmission protocol:	Recommended: T.38 Annex protocol, TCP, UDP/IP communication		
Compatible machines:	IP-Fax compatible machines		
IP-Fax transmission:	Specify IP address and send fax to an IP-Fax compatible fax through a network. Also capable of sending fax from a G3 fax connected to the public telephone lines via a VoIP gateway.		
IP-Fax reception:	Receive a fax sent from an IP-Fax compatible fax through a network. Also capable of receiving fax from a G3 fax connected the public telephone lines via a VoIP gateway.		

Fax Unit Configuration



Component	Code	No.	Remarks
FCU		6	
MBU	D361	7	Included with fax unit
Speaker		1	
CCU I/F Board	- D361	3	
G3 Board		4	Included with optional G3 unit.
G3 Board	D361	5	Included with optional G3 unit.
Expansion Memory	G578	2	Common with R-C4/4.5
Handset Type 1018	B433		USA only. Common with R-C4/4.5