

# Network Interface Board Type GX2

For Machine Code: J007

(Code:J508-17)

INSTALLATION GUIDE

## Important

- Be sure to switch the printer off before installing or removing the network interface board.
- To install or remove the network interface board, use a coin to turn the screw on the board.
- After installing the network interface board, be sure to reattach the network interface board cover to the printer.
- Before touching the network interface board, ground yourself by touching something metal to discharge any static electricity.
- Do not subject the network interface board to impact or other physical stress.

**1** Check that the power cord of the printer is not plugged in.

**2** Using a coin, turn the network interface board cover screw counterclockwise, and then remove the cover.


**3** Remove the spacer in the network interface board cover.



AKR1305

The removed spacer will not be used again.

**4** Align network interface board notch with the triangular mark on the printer, and then push in the network interface board in by pressing the part marked "PUSH".



AKR1315

**5 Reattach the network interface board cover to the printer, and then fasten it using the screw.**

 **Note**

- Be sure to push the network interface board fully into the printer.
- If the network interface board is not installed properly, repeat the entire installation procedure.
- To check whether the network interface board has been installed correctly, print the configuration page. If the network interface board has been installed correctly, its device name appears under "Connection Equipment".
- If you cannot install it properly even after attempting reinstallation, contact your sales or service representative.

 **Reference**

For details about specifying the network settings and printing the configuration page, see Quick Installation Guide.

Dispose of the removed component as general plastic waste or hand it in for collection.